

# Package ‘MARVEL’

October 31, 2022

**Title** Revealing Splicing Dynamics at Single-Cell Resolution

**Version** 1.4.0

## **Description**

Alternative splicing represents an additional and underappreciated layer of complexity underlying gene expression profiles. Nevertheless, there remains hitherto a paucity of software to investigate splicing dynamics at single-cell resolution. ‘MARVEL’ enables splicing analysis of single-cell RNA-sequencing data generated from plate- and droplet-based library preparation methods.

**Imports** ggplot2 (>= 3.3.2), Matrix (>= 1.3-3), methods, plyr (>= 1.8.4), scales (>= 1.1.1)

**Suggests** AnnotationDbi (>= 1.48.0), Biostrings (>= 2.56.0), BSgenome (>= 1.56.0), BSgenome.Hsapiens.NCBI.GRCh38 (>= 1.3.1000), clusterProfiler (>= 3.16.0), factoextra (>= 1.0.7), FactoMineR (>= 2.3), fitdistrplus (>= 1.1-1), GenomicRanges (>= 1.42.0), ggnewscale (>= 0.4.5), ggrepel (>= 0.9.1), gridExtra (>= 2.3), gtools (>= 3.9.2), IRanges (>= 2.24.1), kableExtra (>= 1.3.1), knitr (>= 1.29), kSamples (>= 1.2-9), markdown (>= 1.1), MAST (>= 1.16.0), org.Hs.eg.db (>= 3.10.0), org.Mm.eg.db (>= 3.11.4), parallel, pheatmap (>= 1.0.12), reshape2 (>= 1.4.4), rmarkdown (>= 2.3), S4Vectors (>= 0.26.1), stringr (>= 1.4.0), textclean (>= 0.9.3), twosamples (>= 1.1.1), wiggleplotr (>= 1.12.1)

**Encoding** UTF-8

**License** GPL-3

**RoxygenNote** 7.2.0

**VignetteBuilder** knitr

**ByteCompile** true

**NeedsCompilation** no

**Author** Sean Wen [aut, cre]

**Maintainer** Sean Wen <sean.wenwx@gmail.com>

**Depends** R (>= 3.5.0)

**Repository** CRAN

**Date/Publication** 2022-10-31 10:22:50 UTC

**R topics documented:**

|                                                 |    |
|-------------------------------------------------|----|
| adhocGene.DE.Gene.10x . . . . .                 | 4  |
| adhocGene.DE.PSI.10x . . . . .                  | 4  |
| adhocGene.PlotDEValues.10x . . . . .            | 5  |
| adhocGene.PlotSJPosition.10x . . . . .          | 7  |
| adhocGene.TabulateExpression.Gene.10x . . . . . | 8  |
| adhocGene.TabulateExpression.PSI.10x . . . . .  | 10 |
| AnnotateGenes.10x . . . . .                     | 11 |
| AnnotateSJ.10x . . . . .                        | 11 |
| AnnoVolcanoPlot . . . . .                       | 12 |
| AssignModality . . . . .                        | 13 |
| BioPathways . . . . .                           | 14 |
| BioPathways.10x . . . . .                       | 16 |
| BioPathways.Plot . . . . .                      | 17 |
| BioPathways.Plot.10x . . . . .                  | 18 |
| CheckAlignment . . . . .                        | 19 |
| CheckAlignment.10x . . . . .                    | 20 |
| CheckAlignment.Exp . . . . .                    | 21 |
| CheckAlignment.PSI . . . . .                    | 22 |
| CheckAlignment.PSI.Exp . . . . .                | 22 |
| CheckAlignment.SJ . . . . .                     | 23 |
| CompareExpr . . . . .                           | 23 |
| CompareValues . . . . .                         | 24 |
| CompareValues.Exp . . . . .                     | 27 |
| CompareValues.Exp.Spliced . . . . .             | 29 |
| CompareValues.Genes.10x . . . . .               | 31 |
| CompareValues.PSI . . . . .                     | 32 |
| CompareValues.SJ.10x . . . . .                  | 34 |
| ComputePSI . . . . .                            | 36 |
| ComputePSI.A3SS . . . . .                       | 38 |
| ComputePSI.A5SS . . . . .                       | 38 |
| ComputePSI.AFE . . . . .                        | 39 |
| ComputePSI.ALE . . . . .                        | 40 |
| ComputePSI.MXE . . . . .                        | 40 |
| ComputePSI.RI . . . . .                         | 41 |
| ComputePSI.SE . . . . .                         | 43 |
| CountEvents . . . . .                           | 44 |
| CreateMarvelObject . . . . .                    | 45 |
| CreateMarvelObject.10x . . . . .                | 46 |
| DetectEvents . . . . .                          | 49 |
| DetectEvents.AFE . . . . .                      | 50 |
| DetectEvents.AFE.NegStrand . . . . .            | 51 |
| DetectEvents.AFE.PosStrand . . . . .            | 52 |
| DetectEvents.ALE . . . . .                      | 53 |
| DetectEvents.ALE.NegStrand . . . . .            | 54 |
| DetectEvents.ALE.PosStrand . . . . .            | 55 |
| FilterGenes.10x . . . . .                       | 56 |

|                                        |     |
|----------------------------------------|-----|
| FindPTC . . . . .                      | 57  |
| FindPTC.A3SS.NegStrand . . . . .       | 58  |
| FindPTC.A3SS.PosStrand . . . . .       | 59  |
| FindPTC.A5SS.NegStrand . . . . .       | 60  |
| FindPTC.A5SS.PosStrand . . . . .       | 61  |
| FindPTC.RI.NegStrand . . . . .         | 62  |
| FindPTC.RI.PosStrand . . . . .         | 63  |
| FindPTC.SE.NegStrand . . . . .         | 64  |
| FindPTC.SE.PosStrand . . . . .         | 65  |
| IsoSwitch . . . . .                    | 66  |
| IsoSwitch.10x . . . . .                | 67  |
| IsoSwitch.PlotExpr . . . . .           | 69  |
| ModalityChange . . . . .               | 70  |
| ParseGTF . . . . .                     | 71  |
| PctASE . . . . .                       | 71  |
| PlotDEValues . . . . .                 | 73  |
| PlotDEValues.Exp.Global . . . . .      | 75  |
| PlotDEValues.Exp.Spliced . . . . .     | 76  |
| PlotDEValues.Genes.10x . . . . .       | 78  |
| PlotDEValues.PSI.Distance . . . . .    | 80  |
| PlotDEValues.PSI.Mean . . . . .        | 81  |
| PlotDEValues.PSI.Mean.g2vsg1 . . . . . | 82  |
| PlotDEValues.SJ.10x . . . . .          | 84  |
| PlotPctExprCells.Genes.10x . . . . .   | 85  |
| PlotPctExprCells.SJ.10x . . . . .      | 87  |
| PlotValues . . . . .                   | 88  |
| PlotValues.Exp . . . . .               | 91  |
| PlotValues.PCA.CellGroup.10x . . . . . | 92  |
| PlotValues.PCA.Gene.10x . . . . .      | 94  |
| PlotValues.PCA.PSI.10x . . . . .       | 95  |
| PlotValues.PSI . . . . .               | 97  |
| PropModality . . . . .                 | 99  |
| PropModality.Bar . . . . .             | 101 |
| PropModality.Doughnut . . . . .        | 102 |
| PropPTC . . . . .                      | 103 |
| RunPCA . . . . .                       | 104 |
| RunPCA.Exp . . . . .                   | 106 |
| RunPCA.PSI . . . . .                   | 107 |
| SubsetCrypticA3SS . . . . .            | 109 |
| SubsetSamples . . . . .                | 110 |
| TransformExpValues . . . . .           | 111 |
| ValidateSJ.10x . . . . .               | 112 |

---

adhocGene.DE.Gene.10x *Differential gene expression analysis of specified gene*

---

**Description**

Performs differential gene expression analysis specified gene across for all possible pairs of cell groups. The gene and cell groups were defined earlier in `adhocGene.TabulateExpression.Gene.10x` function.

**Usage**

```
adhocGene.DE.Gene.10x(MarvelObject)
```

**Arguments**

`MarvelObject` Marvel object. S3 object generated from `adhocGene.TabulateExpression.Gene.10x` function.

**Value**

An object of class S3 with new slots `MarvelObject$adhocGene$DE$Gene$Data`.

**Examples**

```
marvel.demo.10x <- readRDS(system.file("extdata/data",
                                     "marvel.demo.10x.rds",
                                     package="MARVEL"))

marvel.demo.10x <- adhocGene.DE.Gene.10x(MarvelObject=marvel.demo.10x)

# Check output
marvel.demo.10x$adhocGene$DE$Gene$Data
```

---

adhocGene.DE.PSI.10x *Differential splice junction analysis of specified gene*

---

**Description**

Performs differential splice junction analysis specified gene across for all possible pairs of cell groups. The gene and cell groups were defined earlier in `adhocGene.TabulateExpression.Gene.10x` function.

**Usage**

```
adhocGene.DE.PSI.10x(MarvelObject)
```

## Arguments

**MarvelObject** Marvel object. S3 object generated from `adhocGene.TabulateExpression.PSI.10x` function.

## Value

An object of class S3 with new slots `MarvelObject$adhocGene$DE$PSI$Data`.

## Examples

```
marvel.demo.10x <- readRDS(system.file("extdata/data",
                                     "marvel.demo.10x.rds",
                                     package="MARVEL"))

marvel.demo.10x <- adhocGene.DE.PSI.10x(MarvelObject=marvel.demo.10x)

# Check output
marvel.demo.10x$adhocGene$DE$PSI$Data
```

---

`adhocGene.PlotDEValues.10x`

*Plot differential splice junction analysis results for a specified gene*

---

## Description

Scatterplot of results from differential gene and splice junction analysis. x-axis represents the gene expression log<sub>2</sub> fold change between the different pairs of cell groups. y-axis represents the PSI differences or log<sub>2</sub> fold change between the different pairs of cell groups.

## Usage

```
adhocGene.PlotDEValues.10x(
  MarvelObject,
  coord.intron,
  log2fc.gene = 0.5,
  delta.sj = 5,
  label.size = 2,
  point.size = 2,
  xmin = NULL,
  xmax = NULL,
  ymin = NULL,
  ymax = NULL
)
```

**Arguments**

|              |                                                                                                                                                               |
|--------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------|
| MarvelObject | Marvel object. S3 object generated from <code>adhocGene.DE.Gene.10x</code> and <code>adhocGene.DE.PSI.10x</code> functions.                                   |
| coord.intron | Character string. Coordinates of splice junction whose differential splice junction results will be plotted.                                                  |
| log2fc.gene  | Numeric value. Absolute log2 fold change, above which, the gene is considered differentially expressed.                                                       |
| delta.sj     | Numeric value. Absolute differences in average PSI values between the two cell groups, above which, the splice junction is considered differentially spliced. |
| label.size   | Numeric value. The font size of the group comparison labels on the plot will be adjusted to the size specified here. Default is 2.                            |
| point.size   | Numeric value. Size of data points. Default is 2.                                                                                                             |
| xmin         | Numeric value. Minimum x-axis value.                                                                                                                          |
| xmax         | Numeric value. Maximum x-axis value.                                                                                                                          |
| ymin         | Numeric value. Minimum y-axis value.                                                                                                                          |
| ymax         | Numeric value. Maximum y-axis value.                                                                                                                          |

**Value**

An object of class S3 with a new slots `MarvelObject$adhocGene$DE$VolcanoPlot$Plot` and `MarvelObject$adhocGene$DE$VolcanoPlot$Table`.

**Examples**

```
marvel.demo.10x <- readRDS(system.file("extdata/data",
                                     "marvel.demo.10x.rds",
                                     package="MARVEL"))

# Define SJ to plot
coord.intron <- marvel.demo.10x$adhocGene$DE$PSI$Data$coord.intron[1]

# Plot SJ vs gene
marvel.demo.10x <- adhocGene.PlotDEValues.10x(
  MarvelObject=marvel.demo.10x,
  coord.intron=coord.intron,
  log2fc.gene=0.5,
  delta.sj=5,
  label.size=2,
  point.size=2,
  xmin=-2.0,
  xmax=2.0,
  ymin=-25,
  ymax=25
)

# Check output
marvel.demo.10x$adhocGene$DE$VolcanoPlot$Plot
```

---

 adhocGene.PlotSJPosition.10x

*Plots the locations of specified splice junction relative to isoforms*


---

## Description

Plots the locations of specified splice junction relative to isoforms. List of isoforms are retrieved from GTF.

## Usage

```
adhocGene.PlotSJPosition.10x(
  MarvelObject,
  coord.intron,
  coord.intron.ext = 50,
  rescale_introns = FALSE,
  show.protein.coding.only = TRUE,
  anno.label.size = 3,
  anno.colors = c("black", "gray", "red")
)
```

## Arguments

|                          |                                                                                                                                                                                 |
|--------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| MarvelObject             | Marvel object. S3 object generated from CheckAlignment.10x function.                                                                                                            |
| coord.intron             | Character string. Coordinates of splice junction whose splice junction will be plotted.                                                                                         |
| coord.intron.ext         | Numeric value. Number of bases to extend the splice junction start and end coordinates into the exons. Helpful to enhance splice junction locations on the plot. Default is 50. |
| rescale_introns          | Logical value. If set to TRUE, the intron length will be shorten. Helpful when introns are very long and focus visualisation of exons and splice junctions. Default is FALSE.   |
| show.protein.coding.only | Logical value. If set to TRUE (default), only protein-coding isoforms will be displayed.                                                                                        |
| anno.label.size          | Numeric value. Font size of isoform ID labels. Default is 3.                                                                                                                    |
| anno.colors              | Vector of character strings. Colors for non-coding UTRs, coding exons, and splice junctions, respectively. Default is c("black", "gray", "red").                                |

## Value

An object of class S3 with new slots `MarvelObject$adhocGene$SJPosition$Plot`, `MarvelObject$adhocGene$SJPosition$exonfile`, and `MarvelObject$adhocGene$SJPosition$cdfsfile`.

**Examples**

```
marvel.demo.10x <- readRDS(system.file("extdata/data",
                                     "marvel.demo.10x.rds",
                                     package="MARVEL"))

marvel.demo.10x <- adhocGene.PlotSJPosition.10x(
  MarvelObject=marvel.demo.10x,
  coord.intron="chr1:100:1001",
  rescale_introns=FALSE,
  show.protein.coding.only=TRUE,
  anno.label.size=1.5
)
```

---

```
adhocGene.TabulateExpression.Gene.10x
```

*Dotplot of gene expression values for a specified gene*

---

**Description**

Creates a dotplot of average expression value of a specified gene across different cell groups.

**Usage**

```
adhocGene.TabulateExpression.Gene.10x(
  MarvelObject,
  cell.group.list,
  gene_short_name,
  log2.transform = TRUE,
  min.pct.cells = 10,
  downsample = FALSE,
  seed = 1
)
```

**Arguments**

|                 |                                                                                                                                              |
|-----------------|----------------------------------------------------------------------------------------------------------------------------------------------|
| MarvelObject    | Marvel object. S3 object generated from CheckAlignment.10x function.                                                                         |
| cell.group.list | List of character strings. Each element of the list is a vector of cell IDs corresponding to a cell group.                                   |
| gene_short_name | Character string. Gene names whose expression will be plotted.                                                                               |
| log2.transform  | Logical value. If set to TRUE (default), normalised gene expression values will be off-set by 1 and then log2-transformed prior to plotting. |



|               |                                                                                                                                                                                                                                                          |
|---------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| min.pct.cells | Numeric value. Percentage of cell expressing the gene in a cell group, below which, the value be re-coded as missing and appear will be omitted from the plot. A gene is considered to be expressed in a given cell if it has non-zero normalised count. |
| downsample    | Logical value. If set to TRUE, the number of cells in each cell group will be down-sampled so that all cell groups will have the same number of cells. The number of cells to down-sample will be based on the smallest cell group. Default is FALSE.    |
| seed          | Numeric value. Random number generator to be fixed for down-sampling.                                                                                                                                                                                    |

### Value

An object of class S3 with new slots `MarvelObject$adhocGene$Expression$Gene$Table`, `MarvelObject$adhocGene$Exp`, `MarvelObject$adhocGene$cell.group.list`, and `MarvelObject$adhocGene$gene_short_name`.

### Examples

```
marvel.demo.10x <- readRDS(system.file("extdata/data",
                                     "marvel.demo.10x.rds",
                                     package="MARVEL")
                          )

# Define cell groups
# Retrieve sample metadata
sample.metadata <- marvel.demo.10x$sample.metadata

# iPSC
index <- which(sample.metadata$cell.type=="iPSC")
cell.ids.1 <- sample.metadata[index, "cell.id"]
length(cell.ids.1)

# Cardio day 10
index <- which(sample.metadata$cell.type=="Cardio day 10")
cell.ids.2 <- sample.metadata[index, "cell.id"]
length(cell.ids.2)

# Save into list
cell.group.list <- list("iPSC"=cell.ids.1,
                       "Cardio d10"=cell.ids.2
                       )

# Gene expression profiling
marvel.demo.10x <- adhocGene.TabulateExpression.Gene.10x(
  MarvelObject=marvel.demo.10x,
  cell.group.list=cell.group.list,
  gene_short_name="TPM2",
  min.pct.cells=10,
  downsample=TRUE
)
```

```
# Check output
marvel.demo.10x$adhocGene$Expression$Gene$Plot
marvel.demo.10x$adhocGene$Expression$Gene$Table
```

---

```
adhocGene.TabulateExpression.PSI.10x
```

*Dotplot of splice junction expression values for a specified gene*

---

## Description

Creates a dotplot of splice junction expression value of a specified gene across different cell groups. The gene and cell groups were defined earlier in `adhocGene.TabulateExpression.Gene.10x` function.

## Usage

```
adhocGene.TabulateExpression.PSI.10x(MarvelObject, min.pct.cells = 10)
```

## Arguments

|               |                                                                                                                                                                                                                                                                      |
|---------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| MarvelObject  | Marvel object. S3 object generated from <code>adhocGene.TabulateExpression.Gene.10x</code> function.                                                                                                                                                                 |
| min.pct.cells | Numeric value. Percentage of cell expressing the splice junction in a cell group, below which, the value be re-coded as missing and appear will be omitted from the plot. A splice junction is considered to be expressed in a given cell if it has count $\geq 1$ . |

## Value

An object of class S3 with new slots `MarvelObject$adhocGene$Expression$PSI$Table` and `MarvelObject$adhocGene$Expression$PSI$Plot`.

## Examples

```
marvel.demo.10x <- readRDS(system.file("extdata/data",
                                     "marvel.demo.10x.rds",
                                     package="MARVEL"))

# SJ usage profiling
marvel.demo.10x <- adhocGene.TabulateExpression.PSI.10x(
  MarvelObject=marvel.demo.10x,
  min.pct.cells=10
)

# Check output
marvel.demo.10x$adhocGene$Expression$PSI$Plot
```

---

AnnotateGenes.10x      *Annotate splice junctions*

---

**Description**

Annotates the each gene in the gene metadata with the gene type, e.g. protein-coding, antisense etc.. Annotations are retrieved from GTF. Only genes found in gene metadata and GTF will be retained.

**Usage**

```
AnnotateGenes.10x(MarvelObject)
```

**Arguments**

MarvelObject      Marvel object. S3 object generated from CreateMarvelObject.10x function.

**Value**

An object of class S3 containing the updated slots `MarvelObject$gene.metadata` and `gene.norm.matrix`.

**Examples**

```
# Load un-processed MARVEL object
marvel.demo.10x.raw <- readRDS(system.file("extdata/data",
                                         "marvel.demo.10x.raw.rds",
                                         package="MARVEL"))

# Annotate gene metadata
marvel.demo.10x <- AnnotateGenes.10x(MarvelObject=marvel.demo.10x.raw)
```

---

AnnotateSJ.10x      *Annotate splice junctions*

---

**Description**

Annotates the splice junctions by assigning the gene name to the start and end of the splice junction. Annotations are retrieved from GTF.

**Usage**

```
AnnotateSJ.10x(MarvelObject)
```

**Arguments**

MarvelObject      Marvel object. S3 object generated from AnnotateGenes.10x function.

**Value**

An object of class S3 containing the updated slot `MarvelObject$sj.metadata`.

**Examples**

```
# Load un-processed MARVEL object
marvel.demo.10x.raw <- readRDS(system.file("extdata/data",
                                         "marvel.demo.10x.raw.rds",
                                         package="MARVEL"))

# Annotate gene metadata
marvel.demo.10x <- AnnotateGenes.10x(MarvelObject=marvel.demo.10x.raw)

# Annotate junction metadata
marvel.demo.10x <- AnnotateSJ.10x(MarvelObject=marvel.demo.10x)
```

---

AnnoVolcanoPlot      *Annotate volcano plot with nonsense-mediated decay (NMD) genes*

---

**Description**

Annotate volcano plot generated from differential gene expression analysis with genes predicted to undergo splicing-induced NMD.

**Usage**

```
AnnoVolcanoPlot(
  MarvelObject,
  anno = FALSE,
  anno.gene_short_name = NULL,
  label.size = NULL,
  point.size = 1,
  xlabel.size = 8
)
```

**Arguments**

|                                   |                                                                                                                                                                                   |
|-----------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>MarvelObject</code>         | Marvel object. S3 object generated from <code>CompareExpr</code> function.                                                                                                        |
| <code>anno</code>                 | Logical value. If set to <code>TRUE</code> , selected gene names will be annotated on the plot as defined in <code>gene.label.x</code> below and <code>gene.label.y</code> above. |
| <code>anno.gene_short_name</code> | Vector of character strings. When <code>anno</code> set to <code>TRUE</code> , the gene names to annotate on the plot.                                                            |
| <code>label.size</code>           | Numeric value. When <code>anno</code> set to <code>TRUE</code> , the size of gene labels.                                                                                         |
| <code>point.size</code>           | Numeric value. Size of data points. Default value is 1.                                                                                                                           |
| <code>xlabel.size</code>          | Numeric value. Font size of the xtick labels. Default is 8.                                                                                                                       |

**Value**

An object of class S3 with new slots `MarvelObject$NMD$AnnoVolcanoPlot$Table` and `MarvelObject$NMD$AnnoVolcanoP`

**Examples**

```
marvel.demo <- readRDS(system.file("extdata/data", "marvel.demo.rds", package="MARVEL"))

marvel.demo <- AnnoVolcanoPlot(MarvelObject=marvel.demo)

# Check outputs
head(marvel.demo$NMD$AnnoVolcanoPlot$Table)
marvel.demo$NMD$AnnoVolcanoPlot$Plot
```

---

AssignModality

*Assign modalities*


---

**Description**

Assigns modalities to each splicing event for a specified group of cells.

**Usage**

```
AssignModality(
  MarvelObject,
  sample.ids,
  min.cells = 25,
  sigma.sq = 0.001,
  bimodal.adjust = TRUE,
  bimodal.adjust.fc = 3,
  bimodal.adjust.diff = 50,
  seed = 1,
  tran_ids = NULL
)
```

**Arguments**

|                             |                                                                                                                                                                                         |
|-----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>MarvelObject</code>   | Marvel object. S3 object generated from <code>TransformExpValues</code> function.                                                                                                       |
| <code>sample.ids</code>     | Vector of character strings. Sample IDs that constitute the cell group.                                                                                                                 |
| <code>min.cells</code>      | Numeric value. The minimum no. of cells expressing the splicing event for the event to be included for modality assignment.                                                             |
| <code>sigma.sq</code>       | Numeric value. The variance threshold below which the included/excluded modality will be defined as primary sub-modality, and above which it will be defined as dispersed sub-modality. |
| <code>bimodal.adjust</code> | Logical. When set to <code>TRUE</code> , MARVEL will identify false bimodal modalities and reassign them as included/excluded modality.                                                 |

|                                  |                                                                                                                                                                                                                                                                                                        |
|----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>bimodal.adjust.fc</code>   | Numeric value. The ratio between the proportion of cells with >0.75 PSI vs <0.25 PSI (and vice versa) below which the splicing event will be classified as bimodal. Only applicable when <code>bimodal.adjust</code> set to TRUE. To be used in conjunction with <code>bimodal.adjust.diff</code> .    |
| <code>bimodal.adjust.diff</code> | Numeric value. The difference between the percentage of cells with >0.75 PSI vs <0.25 PSI (and vice versa) below which the splicing event will be classified as bimodal. Only applicable when <code>bimodal.adjust</code> set to TRUE. To be used in conjunction with <code>bimodal.adjust.fc</code> . |
| <code>seed</code>                | Numeric value. Ensure the <code>fitdist</code> function returns the same values for alpha and beta paramters each time this function is executed using the same random number generator.                                                                                                               |
| <code>tran_ids</code>            | Character strings. Specific vector of transcript IDs for modality assignment. This will be a subset of all transcripts expressed in sufficient number of cells as defined in <code>min.cells</code> option.                                                                                            |

**Value**

An object of class S3 containing with new slot `MarvelObject$Modality$Results`.

**Author(s)**

Sean Wen <sean.wenwx@gmail.com>

**Examples**

```
marvel.demo <- readRDS(system.file("extdata/data", "marvel.demo.rds", package="MARVEL"))

df.pheno <- marvel.demo$SplicePheno
sample.ids <- df.pheno[which(df.pheno$cell.type=="iPSC"), "sample.id"]

# Assign modality
marvel.demo <- AssignModality(MarvelObject=marvel.demo,
                             sample.ids=sample.ids,
                             min.cells=5
                             )

# Check output
head(marvel.demo$Modality$Results)
```

**Description**

Performs pathway enrichment analysis on differentially spliced genes or user-specified custom set of genes.

**Usage**

```
BioPathways(
  MarvelObject,
  method = NULL,
  pval = NULL,
  delta = 0,
  n.top = NULL,
  method.adjust = "fdr",
  custom.genes = NULL,
  species = "human"
)
```

**Arguments**

|               |                                                                                                                                                                                                                                                                                                                                       |
|---------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| MarvelObject  | Marvel object. S3 object generated from CompareValues function.                                                                                                                                                                                                                                                                       |
| method        | Character string. The statistical method used for differential splicing analysis.                                                                                                                                                                                                                                                     |
| pval          | Numeric value. Alternative to n.top and custom.genes, i.e. choose one of these three options. Adjusted p-value below which the splicing events are considered differentially spliced and their corresponding genes are included for gene ontology analysis. If this argument is specified, then n.top must not be specified.          |
| delta         | Numeric value. The absolute difference between the means PSI values of cell group 1 and 2, above which, the splicing event is considered differentially spliced and their corresponding genes are included for gene ontology analysis.                                                                                                |
| n.top         | Numeric value. Alternative to pval to custom.genes, i.e. choose one of these three options.. Indicate the top n splicing events with the smallest adjusted p-values are differentially spliced and their corresponding genes are included for gene ontology analysis. If this argument is specified, then pval must not be specified. |
| method.adjust | Character string. Adjust p-values for multiple testing. Options available as per p.adjust function.                                                                                                                                                                                                                                   |
| custom.genes  | Character strings. Alternative to pval and n.top, i.e. choose one of these three options.. Vector of gene names to be assessed for enrichment of biological pathways.                                                                                                                                                                 |
| species       | Character strings. Takes the value "human" or "mouse", which corresponds to human and mouse genes, respectively. Default value is "human". This will enable MARVEL to retrieve the relevant database for GO analysis.                                                                                                                 |

**Value**

An object of class S3 with new slot `MarvelObject$DE$BioPathways$Table`.

**Examples**

```
marvel.demo <- readRDS(system.file("extdata/data", "marvel.demo.rds", package="MARVEL"))
marvel.demo <- BioPathways(MarvelObject=marvel.demo,
```

```
method="ad",
custom.genes=c("RPL26", "SNRPN")
)
```

---

BioPathways.10x

*Pathway enrichment analysis*


---

## Description

Performs pathway enrichment analysis on differentially spliced genes or user-specified custom set of genes.

## Usage

```
BioPathways.10x(
  MarvelObject,
  pval = 0.05,
  log2fc = NULL,
  delta = 5,
  min.gene.norm = 0,
  method.adjust = "fdr",
  custom.genes = NULL,
  species = "human",
  remove.ribo = FALSE
)
```

## Arguments

|               |                                                                                                                                                                                                                       |
|---------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| MarvelObject  | Marvel object. S3 object generated from CompareValues.Genes.10x function.                                                                                                                                             |
| pval          | Numeric value. p-value, above which, the splice junction is considered differentially spliced. Default is 0.05.                                                                                                       |
| log2fc        | Numeric value. Absolute log2 fold change from differential splicing analysis, above which, the splice junction is considered differentially spliced. This option should be NULL if delta has been specified.          |
| delta         | Numeric value. Absolute difference in average PSI values between the two cell groups, above which, the splice junction is considered differentially spliced. This option should be NULL if log2fc has been specified. |
| min.gene.norm | Numeric value. The average normalised gene expression across the two cell groups above which the splice junction is considered differentially spliced. Default is 0.                                                  |
| method.adjust | Character string. Adjust p-values for multiple testing. Options available as per p.adjust function.                                                                                                                   |
| custom.genes  | Character strings. Alternative to pval and delta. Vector of gene names to be assessed for enrichment of biological pathways.                                                                                          |
| species       | Character strings. Takes the value "human" or "mouse", which corresponds to human and mouse genes, respectively. Default value is "human".                                                                            |



|             |                                                                                                                                                                                                                                  |
|-------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| remove.ribo | Logical value. If set to TRUE, ribosomal genes will be removed prior to GO analysis. This may prevent high-expressing ribosomal genes from overshadowing more biological relevant genes for GO analysis. Default value is FALSE. |
| method      | Character string. The statistical method used for differential splicing analysis.                                                                                                                                                |

**Value**

An object of class S3 containing new slot `MarvelObject$DE$BioPathways$Table`.

**Examples**

```
marvel.demo.10x <- readRDS(system.file("extdata/data",
                                     "marvel.demo.10x.rds",
                                     package="MARVEL"))

marvel.demo.10x <- BioPathways.10x(
  MarvelObject=marvel.demo.10x,
  custom.genes=c("TPM2", "GNAS"),
  species="human"
)
```

---

 BioPathways.Plot

*Plot pathway enrichment analysis results*


---

**Description**

Plots user-specified enriched pathways.

**Usage**

```
BioPathways.Plot(
  MarvelObject,
  go.terms,
  y.label.size = 10,
  offset = 0.5,
  x.axis = "enrichment"
)
```

**Arguments**

|              |                                                                                                                                                                 |
|--------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| MarvelObject | Marvel object. S3 object generated from BioPathways function.                                                                                                   |
| go.terms     | Vector of character strings. Names of pathways to plot. Should match pathway names in column Description of <code>MarvelObject\$DE\$BioPathways\$Table</code> . |
| y.label.size | Numeric value. Size of y-axis tick labels, i.e. gene set names.                                                                                                 |
| offset       | Numeric value. The $-\log_{10}(\text{p-value})$ on the x-axis to subtract or add to increase the plot margins.                                                  |

**x.axis** Character string. If set to "enrichment" (default) the pathway enrichment will be displayed on the x-axis while the color intensity of the data points will reflect the  $-\log_{10}$ (adjusted p-value). If set to "pval" the  $-\log_{10}$ (adjusted p-value) will be displayed on the x-axis while the color intensity of the data points will reflect the pathway enrichment.

### Details

This function plots selected gene sets returned from gene ontology analysis performed previously using BioPathways

### Value

An object of class S3 with new slot `MarvelObject$DE$BioPathways$Plot`.

### Examples

```
marvel.demo <- readRDS(system.file("extdata/data", "marvel.demo.rds", package="MARVEL"))

# Define go terms to plot
df <- marvel.demo$DE$BioPathways$Table
go.terms <- df$Description[c(1:10)]

# Plot
marvel.demo <- BioPathways.Plot(MarvelObject=marvel.demo,
                                go.terms=go.terms,
                                offset=10
                                )

# Check output
marvel.demo$DE$BioPathways$Plot
```

---

BioPathways.Plot.10x *Plot pathway enrichment analysis results*

---

### Description

Plots user-specified enriched pathways.

### Usage

```
BioPathways.Plot.10x(MarvelObject, go.terms, y.label.size = 10, offset = 0.5)
```

### Arguments

**MarvelObject** Marvel object. S3 object generated from BioPathways.10x function.

**go.terms** Vector of character strings. Names of pathways to plot. Should match pathway names in column Description of `MarvelObject$DE$BioPathways$Table`.

`y.label.size` Numeric value. Size of y-axis tick labels, i.e. pathway names.

`offset` Numeric value. The value on the x-axis to subtract or add to increase the plot margins.

**Value**

An object of class S3 containing with new slot `MarvelObject$DE$BioPathways$Plot`.

**Examples**

```
marvel.demo.10x <- readRDS(system.file("extdata/data",
                                     "marvel.demo.10x.rds",
                                     package="MARVEL"))

# Define top pathways to plot
go.terms <- marvel.demo.10x$DE$BioPathways$Table$Description
go.terms <- go.terms[c(1:10)]

# Plot
marvel.demo.10x <- BioPathways.Plot.10x(
  MarvelObject=marvel.demo.10x,
  go.terms=go.terms
)

# Check output
marvel.demo.10x$DE$BioPathways$Plot
```

---

CheckAlignment      *Pre-flight check*

---

**Description**

Checks if the metadata aligns with the columns and rows of the matrix for splicing or gene data. This is a wrapper function for `CheckAlignment.PSI`, `CheckAlignment.Exp`, `CheckAlignment.PSI.Exp`, and `CheckAlignment.SJ`.

**Usage**

```
CheckAlignment(MarvelObject, level)
```

**Arguments**

`MarvelObject` Marvel object. S3 object generated from `CreateMarvelObject` function.

`level` Character string. Indicate "SJ", "splicing" or "gene" for splice junction, splicing or gene data, respectively. "SJ" typically specified before computing PSI values. "splicing" or "gene" typically specified after computing PSI values.

**Value**

An object of class S3 with updated slots `MarvelObject$SpliceJunction`, `MarvelObject$IntronCoverage`, `MarvelObject$SplicePheno`, `MarvelObject$SpliceFeatureValidated`, and `MarvelObject$PSI` or `MarvelObject$GenePheno`, `MarvelObject$GeneFeature`, and `MarvelObject$Gene` are updated for splicing or gene data, respectively.

**Examples**

```
marvel.demo <- readRDS(system.file("extdata/data", "marvel.demo.rds", package="MARVEL"))

marvel.demo <- CheckAlignment(MarvelObject=marvel.demo,
                             level="SJ"
                             )
```

---

CheckAlignment.10x     *Pre-flight check*

---

**Description**

Ensures only overlapping cells found in both gene and splice junction data are retained. Also ensures matrix columns matches cell IDs in sample metadata and matrix rows matches gene name or splice junction coordinates in feature metadata.

**Usage**

```
CheckAlignment.10x(MarvelObject)
```

**Arguments**

`MarvelObject`     Marvel object. S3 object generated from `FilterGenes.10x` function.

**Value**

An object of class S3 containing updated slots `MarvelObject$gene.norm.matrix`, `MarvelObject$sample.metadata`, `MarvelObject$gene.metadata`, `MarvelObject$gene.count.matrix`, `MarvelObject$sj.count.matrix`, `MarvelObject$sj.metadata`.

**Examples**

```
# Load un-processed MARVEL object
marvel.demo.10x.raw <- readRDS(system.file("extdata/data",
                                         "marvel.demo.10x.raw.rds",
                                         package="MARVEL")
                             )

# Annotate gene metadata
marvel.demo.10x <- AnnotateGenes.10x(MarvelObject=marvel.demo.10x.raw)
```

```
# Annotate junction metadata
marvel.demo.10x <- AnnotateSJ.10x(MarvelObject=marvel.demo.10x)

# Validate junctions
marvel.demo.10x <- ValidateSJ.10x(MarvelObject=marvel.demo.10x)

# Subset CDS genes
marvel.demo.10x <- FilterGenes.10x(MarvelObject=marvel.demo.10x,
                                   gene.type="protein_coding"
                                   )

# Pre-flight check
marvel.demo.10x <- CheckAlignment.10x(MarvelObject=marvel.demo.10x)
```

---

CheckAlignment.Exp      *Check gene data*

---

## Description

Checks if the metadata aligns with the columns and rows of the matrix for gene data.

## Usage

```
CheckAlignment.Exp(MarvelObject)
```

## Arguments

MarvelObject      Marvel object. S3 object generated from CreateMarvelObject function.

## Value

An object of class S3 with updated slots `MarvelObject$SplicePheno`, `MarvelObject$SpliceFeature`, and `MarvelObject$PSI`.

## Examples

```
marvel.demo <- readRDS(system.file("extdata/data", "marvel.demo.rds", package="MARVEL"))

marvel.demo <- CheckAlignment.Exp(MarvelObject=marvel.demo)
```

---

CheckAlignment.PSI     *Check splicing data*

---

**Description**

Checks if the metadata aligns with the columns and rows of the matrix for splicing data.

**Usage**

```
CheckAlignment.PSI(MarvelObject)
```

**Arguments**

MarvelObject     Marvel object. S3 object generated from CreateMarvelObject function.

**Value**

An object of class S3 with updated slots MarvelObject\$SplicePheno, MarvelObject\$SpliceFeature, and MarvelObject\$PSI.

**Examples**

```
marvel.demo <- readRDS(system.file("extdata/data", "marvel.demo.rds", package="MARVEL"))  
marvel.demo <- CheckAlignment.PSI(MarvelObject=marvel.demo)
```

---

CheckAlignment.PSI.Exp  
                          *Check splicing and gene data against each other*

---

**Description**

Subsets overlapping samples between splicing and gene data.

**Usage**

```
CheckAlignment.PSI.Exp(MarvelObject)
```

**Arguments**

MarvelObject     S3 object generated from CheckAlignment.PSI and CheckAlignment.Exp function.

**Value**

An object of class S3 with updated slots MarvelObject\$SplicePheno, MarvelObject\$PSI, MarvelObject\$GenePheno, and MarvelObject\$Exp.

**Examples**

```
marvel.demo <- readRDS(system.file("extdata/data", "marvel.demo.rds", package="MARVEL"))
marvel.demo <- CheckAlignment.PSI.Exp(MarvelObject=marvel.demo)
```

---

CheckAlignment.SJ      *Check splice junction data*

---

**Description**

Checks if the metadata aligns with the columns and rows of the matrix for splice junction data prior to PSI computation.

**Usage**

```
CheckAlignment.SJ(MarvelObject)
```

**Arguments**

MarvelObject      Marvel object. S3 object generated from CreateMarvelObject function.

**Value**

An object of class S3 with updated slots MarvelObject\$SplicePheno, MarvelObject\$PSI and MarvelObject\$IntronCounts.

**Examples**

```
marvel.demo <- readRDS(system.file("extdata/data", "marvel.demo.rds", package="MARVEL"))
marvel.demo <- CheckAlignment.SJ(MarvelObject=marvel.demo)
```

---

CompareExpr      *Compares gene expression changes based on nonsense-mediated decay (NMD) status*

---

**Description**

Compares gene expression changes based on NMD status for each splicing event type.

**Usage**

```
CompareExpr(MarvelObject, xlabel.size = 8)
```

**Arguments**

`MarvelObject`    Marvel object. S3 object generated from `FindPTC` function.  
`xlabels.size`    Numeric value. Size of the x-axis tick labels. Default is 8.

**Value**

An object of class `S3 new slots MarvelObject$NMD$NMD.Expr$Table, MarvelObject$NMD$NMD.Expr$Plot, and MarvelObject$NMD$NMD.Expr$Plot.Stats`.

**Examples**

```
marvel.demo <- readRDS(system.file("extdata/data", "marvel.demo.rds", package="MARVEL"))

marvel.demo <- CompareExpr(MarvelObject=marvel.demo)

# Check outputs
head(marvel.demo$NMD$NMD.Expr$Table)
marvel.demo$NMD$NMD.Expr$Plot
marvel.demo$NMD$NMD.Expr$Plot.Stats
```

---

CompareValues

*Differential splicing and gene expression analysis*

---

**Description**

Performs differential splicing and gene expression analysis between 2 groups of cells. This is a wrapper function for `CompareValues.PSI` and `CompareValues.Exp` functions.

**Usage**

```
CompareValues(
  MarvelObject,
  cell.group.g1 = NULL,
  cell.group.g2 = NULL,
  downsample = FALSE,
  seed = 1,
  min.cells = 25,
  pct.cells = NULL,
  method = NULL,
  nboots = 1000,
  n.permutations = 1000,
  method.adjust = "fdr",
  level,
  event.type = NULL,
  show.progress = TRUE,
  annotate.outliers = TRUE,
  n.cells.outliers = 10,
```



```

    assign.modality = TRUE,
    custom.gene_ids = NULL,
    psi.method = NULL,
    psi.pval = NULL,
    psi.delta = NULL,
    method.de.gene = NULL,
    method.adjust.de.gene = NULL,
    mast.method = "bayesglm",
    mast.ebayes = TRUE
  )

```

### Arguments

|                |                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|----------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| MarvelObject   | Marvel object. S3 object generated from TransformExpValues function.                                                                                                                                                                                                                                                                                                                                                                 |
| cell.group.g1  | Vector of character strings. Cell IDs corresponding to Group 1 (reference group).                                                                                                                                                                                                                                                                                                                                                    |
| cell.group.g2  | Vector of character strings. Cell IDs corresponding to Group 2.                                                                                                                                                                                                                                                                                                                                                                      |
| downsample     | Logical value. If set to TRUE, the number of cells in each cell group will be downsampled to the sample size of the smaller cell group so that both cell groups will have the sample size prior to differential expression analysis. Default is FALSE.                                                                                                                                                                               |
| seed           | Numeric value. The seed number for the random number generator to ensure reproducibility during during down-sampling of cells when downsample set to TRUE, during permutation testing when method set to "permutation", and during modality assignment which will be performed automatically.                                                                                                                                        |
| min.cells      | Numeric value. The minimum no. of cells expressing the splicing event or genes for the event or genes to be included for differential splicing analysis.                                                                                                                                                                                                                                                                             |
| pct.cells      | Numeric value. The minimum percentage of cells expressing the splicing event or genes for the event or genes to be included for differential splicing analysis. If pct.cells is specified, then pct.cells will be used as threshold instead of min.cells.                                                                                                                                                                            |
| method         | Character string. Statistical test to compare the 2 groups of cells. "ks", "kuiper", "ad", "dts", "wilcox", and "t.test" for Kolmogorov-Smirnov, Kuiper, Anderson-Darling, DTS, Wilcox, and t-test, respectively. Additional "mast" option is available for differential gene expression analysis. If "mast" is specified, the log2fc and p-values will be corrected using the gene detection rate as per the MAST package tutorial. |
| nboots         | Numeric value. Only applicable when level set to "splicing". When method set to "dts", the number of bootstrap iterations for computing the p-value.                                                                                                                                                                                                                                                                                 |
| n.permutations | Numeric value. Only applicable when level set to "splicing". When method set to "permutation", this argument indicates the number of permutations to perform for generating the null distribution for subsequent p-value inference. Default is 1000 times.                                                                                                                                                                           |
| method.adjust  | Character string. Adjust p-values for multiple testing. Options available as per p.adjust function.                                                                                                                                                                                                                                                                                                                                  |
| level          | Character string. Indicate "splicing" or "gene" for differential splicing or gene expression analysis, respectively.                                                                                                                                                                                                                                                                                                                 |

|                                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>event.type</code>            | Character string. Only applicable when <code>level</code> set to "splicing". Indicate which splicing event type to include for analysis. Can take value "SE", "MXE", "RI", "A5SS", or "A3SS" which represents skipped-exon (SE), mutually-exclusive exons (MXE), retained-intron (RI), alternative 5' splice site (A5SS), and alternative 3' splice site (A3SS), respectively.                                                                                         |
| <code>show.progress</code>         | Logical value. If set to TRUE, progress bar will be displayed so that users can estimate the time needed for differential analysis. Default value is TRUE.                                                                                                                                                                                                                                                                                                             |
| <code>annotate.outliers</code>     | Numeric value. Only applicable when <code>level</code> set to "splicing". When set to TRUE, statistical difference in PSI values between the two cell groups that is driven by outlier cells will be annotated.                                                                                                                                                                                                                                                        |
| <code>n.cells.outliers</code>      | Numeric value. Only applicable when <code>level</code> set to "splicing". When method set to "dts", the minimum number of cells with non-1 or non-0 PSI values for included-to-included or excluded-to-excluded modality change, respectively. The p-values will be re-coded to 1 when both cell groups have less than this minimum number of cells. This is to avoid false positive results.                                                                          |
| <code>assign.modality</code>       | Logical value. Only applicable when <code>level</code> set to "splicing". If set to TRUE (default), modalities will be assigned to each cell group.                                                                                                                                                                                                                                                                                                                    |
| <code>custom.gene_ids</code>       | Character string. Only applicable when <code>level</code> set to "gene". Instead of specified the genes to include for DE analysis with <code>min.cells</code> , users may input a custom vector of gene IDs to include for DE analysis.                                                                                                                                                                                                                               |
| <code>psi.method</code>            | Vector of character string(s). Only applicable when <code>level</code> set to "gene.spliced" and when <code>CompareValues</code> function has been ran with <code>level</code> set to "splicing" earlier. To include significant events from these method(s) for differential gene expression analysis.                                                                                                                                                                |
| <code>psi.pval</code>              | Vector of numeric value(s). Only applicable when <code>level</code> set to "gene.spliced" and when <code>CompareValues</code> function has been ran with <code>level</code> set to "splicing" earlier. The adjusted p-value, below which, the splicing event is considered differentially spliced, and the corresponding genes will be included for differential gene expression analysis.                                                                             |
| <code>psi.delta</code>             | Numeric value. Only applicable when <code>level</code> set to "gene.spliced" and when <code>CompareValues</code> function has been ran with <code>level</code> set to "splicing" earlier. The absolute difference in mean PSI values between <code>cell.group.g1</code> and <code>cell.group.g1</code> , above which, the splicing event is considered differentially spliced, and the corresponding genes will be included for differential gene expression analysis. |
| <code>method.de.gene</code>        | Character string. Only applicable when <code>level</code> set to "gene.spliced" and when <code>CompareValues</code> function has been ran with <code>level</code> set to "splicing" earlier. Same as <code>method</code> .                                                                                                                                                                                                                                             |
| <code>method.adjust.de.gene</code> | Character string. Only applicable when <code>level</code> set to "gene.spliced" and when <code>CompareValues</code> function has been ran with <code>level</code> set to "splicing" earlier. Same as <code>method.adjust</code> .                                                                                                                                                                                                                                      |

|             |                                                                                                                                                                                                               |
|-------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| mast.method | Character string. Only applicable when level set to "gene" or "gene.spliced". As per the method option of the zlm function from the MAST package. Default is "bayesglm", other options are "glm" and "glmer". |
| mast.ebays  | Logical value. Only applicable when level set to "gene" or "gene.spliced". As per the ebays option of the zlm function from the MAST package. Default is TRUE.                                                |

### Value

An object of class S3 containing with new slot `MarvelObject$DE$PSI$Table[["method"]]` or `MarvelObject$DE$Exp$Table` when level option specified as "splicing" or "gene", respectively.

### Examples

```
marvel.demo <- readRDS(system.file("extdata/data", "marvel.demo.rds", package="MARVEL"))

# Define cell groups for analysis
df.pheno <- marvel.demo$SplicePheno
cell.group.g1 <- df.pheno[which(df.pheno$cell.type=="iPSC"), "sample.id"]
cell.group.g2 <- df.pheno[which(df.pheno$cell.type=="Endoderm"), "sample.id"]

# DE
marvel.demo <- CompareValues(MarvelObject=marvel.demo,
                             cell.group.g1=cell.group.g1,
                             cell.group.g2=cell.group.g2,
                             min.cells=5,
                             method="t.test",
                             method.adjust="fdr",
                             level="splicing",
                             event.type=c("SE", "MXE", "RI", "A5SS", "A3SS", "AFE", "ALE"),
                             show.progress=FALSE
                             )

# Check output
head(marvel.demo$DE$PSI$Table[["ad"]])
```

---

CompareValues.Exp      *Differential gene expression analysis*

---

### Description

Performs differential gene expression analysis between 2 groups of cells.

### Usage

```
CompareValues.Exp(
  MarvelObject,
  cell.group.g1 = NULL,
```

```

cell.group.g2 = NULL,
downsample = FALSE,
seed = 1,
min.cells = 25,
pct.cells = NULL,
method,
method.adjust,
show.progress = TRUE,
nboots = 1000,
custom.gene_ids = NULL,
mast.method = "bayesglm",
mast.ebayes = TRUE
)

```

### Arguments

|                 |                                                                                                                                                                                                                                                                                                                                                                                         |
|-----------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| MarvelObject    | Marvel object. S3 object generated from TransformExpValues function.                                                                                                                                                                                                                                                                                                                    |
| cell.group.g1   | Vector of character strings. Cell IDs corresponding to Group 1 (reference group).                                                                                                                                                                                                                                                                                                       |
| cell.group.g2   | Vector of character strings. Cell IDs corresponding to Group 2.                                                                                                                                                                                                                                                                                                                         |
| downsample      | Logical value. If set to TRUE, the number of cells in each cell group will be downsampled to the sample size of the smaller cell group so that both cell groups will have the sample size prior to differential expression analysis. Default is FALSE.                                                                                                                                  |
| seed            | Numeric value. The seed number for the random number generator to ensure reproducibility during during down-sampling of cells when downsample set to TRUE.                                                                                                                                                                                                                              |
| min.cells       | Numeric value. The minimum no. of cells expressing the gene for the gene to be included for differential splicing analysis.                                                                                                                                                                                                                                                             |
| pct.cells       | Numeric value. The minimum no. of cells expressing the gene for the gene to be included for differential splicing analysis. If pct.cells is specified, then pct.cells will be used as threshold instead of min.cells.                                                                                                                                                                   |
| method          | Character string. Statistical test to compare the 2 groups of cells. "ks", "kuiper", "ad", "dts", "wilcox", and "t.test" for Kolmogorov-Smirnov, Kuiper, Anderson-Darling, DTS, Wilcox, and t-test, respectively. Additional option is "mast". If set to "mast" is specified, the log2fc and p-values will be corrected using the gene detection rate as per the MAST package tutorial. |
| method.adjust   | Character string. Adjust p-values for multiple testing. Options available as per p.adjust function.                                                                                                                                                                                                                                                                                     |
| show.progress   | Logical value. If set to TRUE, progress bar will be displayed so that users can estimate the time needed for differential analysis. Default value is TRUE.                                                                                                                                                                                                                              |
| nboots          | Numeric value. When method set to "dts", the number of bootstrap iterations for computing the p-value.                                                                                                                                                                                                                                                                                  |
| custom.gene_ids | Character string. Instead of specified the genes to include for DE analysis with min.cells, users may input a custom vector of gene IDs to include for DE analysis.                                                                                                                                                                                                                     |

|             |                                                                                                                                                   |
|-------------|---------------------------------------------------------------------------------------------------------------------------------------------------|
| mast.method | Character string. As per the method option of the zlm function from the MAST package. Default is "bayesglm", other options are "glm" and "glmer". |
| mast.ebayes | Logical value. As per the ebayes option of the zlm function from the MAST package. Default is TRUE.                                               |

**Value**

An object of class S3 new slot `MarvelObject$DE$Exp$Table`.

**Examples**

```
marvel.demo <- readRDS(system.file("extdata/data", "marvel.demo.rds", package="MARVEL"))

# Define cell groups for analysis
df.pheno <- marvel.demo$SplicePheno
cell.group.g1 <- df.pheno[which(df.pheno$cell.type=="iPSC"), "sample.id"]
cell.group.g2 <- df.pheno[which(df.pheno$cell.type=="Endoderm"), "sample.id"]

# DE
marvel.demo <- CompareValues.Exp(MarvelObject=marvel.demo,
                                cell.group.g1=cell.group.g1,
                                cell.group.g2=cell.group.g2,
                                min.cells=5,
                                method="t.test",
                                method.adjust="fdr",
                                show.progress=FALSE
                                )

# Check output
head(marvel.demo$DE$Exp$Table)
```

---

CompareValues.Exp.Spliced

*Differential gene expression analysis for differentially spliced genes*

---

**Description**

Performs differential gene expression analysis between 2 groups of cells only on differentially spliced genes.

**Usage**

```
CompareValues.Exp.Spliced(
  MarvelObject,
  cell.group.g1 = NULL,
  cell.group.g2 = NULL,
  psi.method,
  psi.pval,
  psi.delta,
```

```

method.de.gene = "wilcox",
method.adjust.de.gene = "fdr",
downsample = FALSE,
seed = 1,
show.progress = TRUE,
mast.method = "bayesglm",
mast.ebayes = TRUE
)

```

### Arguments

|                                    |                                                                                                                                                                                                                                                                                             |
|------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>MarvelObject</code>          | Marvel object. S3 object generated from <code>TransformExpValues</code> function.                                                                                                                                                                                                           |
| <code>cell.group.g1</code>         | Vector of character strings. Cell IDs corresponding to Group 1 (reference group).                                                                                                                                                                                                           |
| <code>cell.group.g2</code>         | Vector of character strings. Cell IDs corresponding to Group 2.                                                                                                                                                                                                                             |
| <code>psi.method</code>            | Vector of character string(s). To include significant events from these method(s) for differential gene expression analysis.                                                                                                                                                                |
| <code>psi.pval</code>              | Vector of numeric value(s). The adjusted p-value, below which, the splicing event is considered differentially spliced, and the corresponding genes will be included for differential gene expression analysis.                                                                             |
| <code>psi.delta</code>             | Numeric value. The absolute difference in mean PSI values between <code>cell.group.g1</code> and <code>cell.group.g2</code> , above which, the splicing event is considered differentially spliced, and the corresponding genes will be included for differential gene expression analysis. |
| <code>method.de.gene</code>        | Character string. Same as <code>method</code> in <code>CompareValues</code> function.                                                                                                                                                                                                       |
| <code>method.adjust.de.gene</code> | Character string. Same as <code>method</code> in <code>CompareValues</code> function.                                                                                                                                                                                                       |
| <code>downsample</code>            | Logical value. If set to <code>TRUE</code> , the number of cells in each cell group will be downsampled to the sample size of the smaller cell group so that both cell groups will have the sample size prior to differential expression analysis. Default is <code>FALSE</code> .          |
| <code>seed</code>                  | Numeric value. The seed number for the random number generator to ensure reproducibility during down-sampling of cells when <code>downsample</code> set to <code>TRUE</code> .                                                                                                              |
| <code>show.progress</code>         | Logical value. If set to <code>TRUE</code> , progress bar will be displayed so that users can estimate the time needed for differential analysis. Default value is <code>TRUE</code> .                                                                                                      |
| <code>mast.method</code>           | Character string. As per the <code>method</code> option of the <code>zlm</code> function from the MAST package. Default is "bayesglm", other options are "glm" and "glmer".                                                                                                                 |
| <code>mast.ebayes</code>           | Logical value. As per the <code>ebayes</code> option of the <code>zlm</code> function from the MAST package. Default is <code>TRUE</code> .                                                                                                                                                 |

### Value

An object of class S3 new slot `MarvelObject$DE$Exp$Table`.

**Examples**

```

marvel.demo <- readRDS(system.file("extdata/data", "marvel.demo.rds", package="MARVEL"))

# Define cell groups for analysis
df.pheno <- marvel.demo$SplicePheno
cell.group.g1 <- df.pheno[which(df.pheno$cell.type=="iPSC"), "sample.id"]
cell.group.g2 <- df.pheno[which(df.pheno$cell.type=="Endoderm"), "sample.id"]

# DE
marvel.demo <- CompareValues.Exp.Spliced(MarvelObject=marvel.demo,
                                         cell.group.g1=cell.group.g1,
                                         cell.group.g2=cell.group.g2,
                                         psi.method="ad",
                                         psi.pval=0.10,
                                         psi.delta=0,
                                         method.de.gene="t.test",
                                         method.adjust.de.gene="fdr",
                                         show.progress=FALSE
                                         )

# Check output
head(marvel.demo$DE$Exp.Spliced$Table)

```

---

CompareValues.Genes.10x

*Differential gene expression analysis*

---

**Description**

Performs differential gene expression analysis between two groups of cells. Only among cells and genes previously included for splice junction analysis.

**Usage**

```

CompareValues.Genes.10x(
  MarvelObject,
  log2.transform = TRUE,
  show.progress = TRUE,
  method = "wilcox",
  mast.method = "bayesglm",
  mast.ebayes = TRUE
)

```

**Arguments**

**MarvelObject** Marvel object. S3 object generated from CompareValues.SJ.10x function.

**log2.transform** Logical value. If set to TRUE (default), normalised gene expression values will be off-set by 1 and then log2-transformed prior to analysis. This option is automatically set to TRUE if method option is set to "mast".

|                            |                                                                                                                                                                                                                                                                                |
|----------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>show.progress</code> | Logical value. If set to TRUE (default), the progress bar will appear.                                                                                                                                                                                                         |
| <code>method</code>        | Character string. Statistical test to compare the 2 groups of cells. Default is "wilcox" as recommended by Seurat. Another option is "mast". If "mast" is specified, the log2fc and p-values will be corrected using the gene detection rate as per the MAST package tutorial. |
| <code>mast.method</code>   | Character string. As per the method option of the zlm function from the MAST package. Default is "bayesglm", other options are "glm" and "glmer".                                                                                                                              |
| <code>mast.ebayes</code>   | Logical value. As per the ebayes option of the zlm function from the MAST package. Default is TRUE.                                                                                                                                                                            |

**Value**

An object of class S3 with a updated slot `MarvelObject$DE$SJ$Table`.

**Examples**

```
marvel.demo.10x <- readRDS(system.file("extdata/data",
                                     "marvel.demo.10x.rds",
                                     package="MARVEL"))

marvel.demo.10x <- CompareValues.Genes.10x(
  MarvelObject=marvel.demo.10x,
  show.progress=FALSE
)

# Check output
head(marvel.demo.10x$DE$SJ$Table)
```

---

CompareValues.PSI      *Differential splicing analysis*

---

**Description**

Performs differentially splicing analysis between 2 groups of cells.

**Usage**

```
CompareValues.PSI(
  MarvelObject,
  cell.group.g1,
  cell.group.g2,
  downsample = FALSE,
  seed = 1,
  min.cells = 25,
  pct.cells = NULL,
```



```

method,
nboots = 1000,
n.permutations = 1000,
method.adjust = "fdr",
event.type,
show.progress = TRUE,
annotate.outliers = TRUE,
n.cells.outliers = 10,
assign.modality = TRUE
)

```

### Arguments

|                |                                                                                                                                                                                                                                                                                                                     |
|----------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| MarvelObject   | Marvel object. S3 object generated from TransformExpValues function.                                                                                                                                                                                                                                                |
| cell.group.g1  | Vector of character strings. Cell IDs corresponding to Group 1 (reference group).                                                                                                                                                                                                                                   |
| cell.group.g2  | Vector of character strings. Cell IDs corresponding to Group 2.                                                                                                                                                                                                                                                     |
| downsample     | Logical value. If set to TRUE, the number of cells in each cell group will be downsampled to the sample size of the smaller cell group so that both cell groups will have the sample size prior to differential expression analysis. Default is FALSE.                                                              |
| seed           | Numeric value. The seed number for the random number generator to ensure reproducibility during during down-sampling of cells when downsample set to TRUE, during permutation testing when method set to "permutation", and during modality assignment which will be performed automatically.                       |
| min.cells      | Numeric value. The minimum no. of cells expressing the splicing event for the event to be included for differential splicing analysis.                                                                                                                                                                              |
| pct.cells      | Numeric value. The minimum percentage of cells expressing the splicing event for the event to be included for differential splicing analysis. If pct.cells is specified, then pct.cells will be used as threshold instead of min.cells.                                                                             |
| method         | Character string. Statistical test to compare the 2 groups of cells. "ks", "kuiper", "ad", "dts", "wilcox", "t.test", and "permutation" for Kolmogorov-Smirnov, Kuiper, Anderson-Darling, DTS, Wilcox, t-test, and, permutation approach respectively.                                                              |
| nboots         | Numeric value. When method set to "dts", the number of bootstrap iterations for computing the p-value.                                                                                                                                                                                                              |
| n.permutations | Numeric value. When method set to "permutation", this argument indicates the number of permutations to perform for generating the null distribution for subsequent p-value inference. Default is 1000 times.                                                                                                        |
| method.adjust  | Character string. Adjust p-values for multiple testing. Options available as per p.adjust function.                                                                                                                                                                                                                 |
| event.type     | Character string. Indicate which splicing event type to include for analysis. Can take value "SE", "MXE", "RI", "A5SS", or "A3SS" which represents skipped-exon (SE), mutually-exclusive exons (MXE), retained-intron (RI), alternative 5' splice site (A5SS), and alternative 3' splice site (A3SS), respectively. |
| show.progress  | Logical value. If set to TRUE, progress bar will be displayed so that users can estimate the time needed for differential analysis. Default value is TRUE.                                                                                                                                                          |

`annotate.outliers`  
 Numeric value. When set to TRUE, statistical difference in PSI values between the two cell groups that is driven by outlier cells will be annotated.

`n.cells.outliers`  
 Numeric value. When `annotate.outliers` set to TRUE, the minimum number of cells with non-1 or non-0 PSI values for included-to-included or excluded-to-excluded modality change, respectively. The p-values will be re-coded to 1 when both cell groups have less than this minimum number of cells. This is to avoid false positive results.

`assign.modality`  
 Logical value. If set to TRUE (default), modalities will be assigned to each cell group.

### Value

An object of class data frame containing the output of the differential splicing analysis.

### Examples

```
marvel.demo <- readRDS(system.file("extdata/data", "marvel.demo.rds", package="MARVEL"))

# Define cell groups for analysis
df.pheno <- marvel.demo$SplicePheno
cell.group.g1 <- df.pheno[which(df.pheno$cell.type=="iPSC"), "sample.id"]
cell.group.g2 <- df.pheno[which(df.pheno$cell.type=="Endoderm"), "sample.id"]

# DE
results <- CompareValues.PSI(MarvelObject=marvel.demo,
                             cell.group.g1=cell.group.g1,
                             cell.group.g2=cell.group.g2,
                             min.cells=5,
                             method="t.test",
                             method.adjust="fdr",
                             event.type=c("SE", "MXE", "RI", "A5SS", "A3SS", "AFE", "ALE"),
                             show.progress=FALSE
                             )

# Check output
head(results)
```

---

CompareValues.SJ.10x *Differential splice junction analysis*

---

### Description

Performs differential splice junction analysis between two groups of cells.

**Usage**

```

CompareValues.SJ.10x(
  MarvelObject,
  coord.introns = NULL,
  cell.group.g1,
  cell.group.g2,
  min.pct.cells.genes = 10,
  min.pct.cells.sj = 10,
  min.gene.norm = 1,
  seed = 1,
  n.iterations = 100,
  downsample = FALSE,
  show.progress = TRUE
)

```

**Arguments**

|                     |                                                                                                                                                                                                                                                                                                                                                                 |
|---------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| MarvelObject        | Marvel object. S3 object generated from CheckAlignment.10x function.                                                                                                                                                                                                                                                                                            |
| coord.introns       | Character strings. Specific splice junctions to be included for analysis. Default is NULL.                                                                                                                                                                                                                                                                      |
| cell.group.g1       | Vector of Character strings. Cell IDs corresponding to Group 1 (reference group).                                                                                                                                                                                                                                                                               |
| cell.group.g2       | Vector of Character strings. Cell IDs corresponding to Group 2.                                                                                                                                                                                                                                                                                                 |
| min.pct.cells.genes | Numeric value. Minimum percentage of cells in which the gene is expressed for that gene to be included for splice junction expression distribution analysis. Expressed genes defined as genes with non-zero normalised UMI counts. This threshold may be determined from PlotPctExprCells.SJ.10x function. Default is 10.                                       |
| min.pct.cells.sj    | Numeric value. Minimum percentage of cells in which the splice junction is expressed for that splice junction to be included for splice junction expression distribution analysis. Expressed splice junctions defined as splice junctions with raw UMI counts $\geq 1$ . This threshold may be determined from PlotPctExprCells.SJ.10x function. Default is 10. |
| min.gene.norm       | Numeric value. The average normalised gene expression across the two cell groups above which the splice junction will be included for analysis. Default is 1.0.                                                                                                                                                                                                 |
| seed                | Numeric value. Random number generator to be fixed for permutations test and down-sampling.                                                                                                                                                                                                                                                                     |
| n.iterations        | Numeric value. Number of times to shuffle the cell group labels when building the null distribution. Default is 100.                                                                                                                                                                                                                                            |
| downsample          | Logical value. If set to TRUE, both cell groups will be down-sampled so that both cell groups will have the same number of cells. The number of cells to downsample will be based on the smallest cell group. Default is FALSE.                                                                                                                                 |
| show.progress       | Logical value. If set to TRUE (default), the progress bar will appear.                                                                                                                                                                                                                                                                                          |

**Value**

An object of class S3 with a new slots `MarvelObject$DE$SJ$Table`, `MarvelObject$DE$SJ$cell.group.g1`, and `MarvelObject$DE$SJ$cell.group.g2`.

**Examples**

```
marvel.demo.10x <- readRDS(system.file("extdata/data",
                                     "marvel.demo.10x.rds",
                                     package="MARVEL")
                          )

# Define cell groups
# Retrieve sample metadata
sample.metadata <- marvel.demo.10x$sample.metadata

# Group 1 (reference)
index <- which(sample.metadata$cell.type=="iPSC")
cell.ids.1 <- sample.metadata[index, "cell.id"]
length(cell.ids.1)

# Group 2
index <- which(sample.metadata$cell.type=="Cardio day 10")
cell.ids.2 <- sample.metadata[index, "cell.id"]
length(cell.ids.2)

# DE
marvel.demo.10x <- CompareValues.SJ.10x(
  MarvelObject=marvel.demo.10x,
  cell.group.g1=cell.ids.1,
  cell.group.g2=cell.ids.2,
  min.pct.cells.genes=10,
  min.pct.cells.sj=10,
  min.gene.norm=1.0,
  seed=1,
  n.iterations=100,
  downsample=TRUE,
  show.progress=FALSE
)

# Check output
head(marvel.demo.10x$DE$SJ$Table)
```

---

 ComputePSI

---

*Compute percent spliced-in (PSI) values*


---

**Description**

Validate splicing events and subsequently computes percent spliced-in (PSI) values these high-quality splicing events. This is a wrapper function for `ComputePSI.SE`, `ComputePSI.MXE`, `ComputePSI.A5SS`, `ComputePSI.A3SS`, `ComputePSI.RI`, `ComputePSI.AFE`, and `ComputePSI.ALE` functions.

**Usage**

```

ComputePSI(
  MarvelObject,
  CoverageThreshold,
  EventType,
  thread = NULL,
  UnevenCoverageMultiplier = 10,
  read.length = 1
)

```

**Arguments**

|                          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|--------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| MarvelObject             | Marvel object. S3 object generated from CreateMarvelObject function.                                                                                                                                                                                                                                                                                                                                                                                                                            |
| CoverageThreshold        | Numeric value. Coverage threshold below which the PSI of the splicing event will be censored, i.e. annotated as missing (NA). Coverage defined as the total number of reads supporting both included and excluded isoforms.                                                                                                                                                                                                                                                                     |
| EventType                | Character string. Indicate which splicing event type to calculate the PSI values for. Can take value "SE", "MXE", "RI", "A5SS", or "A3SS" which represents skipped-exon (SE), mutually-exclusive exons (MXE), retained-intron (RI), alternative 5' splice site (A5SS), and alternative 3' splice site (A3SS), respectively.                                                                                                                                                                     |
| thread                   | Numeric value. Only applicable when EventType set to "RI" Set number of threads..                                                                                                                                                                                                                                                                                                                                                                                                               |
| UnevenCoverageMultiplier | Numeric value. Maximum allowable fold difference between two included junction counts for SE or two included or two excluded junction counts for MXE. Only applicable when EventType set to "SE" or "MXE", respectively.                                                                                                                                                                                                                                                                        |
| read.length              | Numeric value. The length of read. Only applicable when EventType set to "RI". This number will be specific to the sequencing mode. E.g. read length should be set to 150 when samples were sequenced in 150bp paired-end or single-end. This option should only be specified when users used read-counting approach for computing intron counts. The option should be left with its default value 1 when users tabulated the per-base count and summed them up to arrive at the intron counts. |

**Value**

An object of class S3 with new slots \$SpliceFeatureValidated and \$PSI.

**Examples**

```

marvel.demo <- readRDS(system.file("extdata/data", "marvel.demo.rds", package="MARVEL"))

marvel.demo <- ComputePSI(MarvelObject=marvel.demo,
  CoverageThreshold=10,
  EventType="SE",
  UnevenCoverageMultiplier=10
)

```

---

|                 |                                                                                  |
|-----------------|----------------------------------------------------------------------------------|
| ComputePSI.A3SS | <i>Compute Alternative 3' Splice Site (A3SS) Percent Spliced-in (PSI) Values</i> |
|-----------------|----------------------------------------------------------------------------------|

---

**Description**

Validate A3SS splicing events and subsequently computes percent spliced-in (PSI) values these high-quality splicing events.

**Usage**

```
ComputePSI.A3SS(MarvelObject, CoverageThreshold)
```

**Arguments**

**MarvelObject**    Marvel object. S3 object generated from CreateMarvelObject function.

**CoverageThreshold**  
 Numeric value. Coverage threshold below which the PSI of the splicing event will be censored, i.e. annotated as missing (NA). Coverage defined as the total number of reads supporting both included and excluded isoforms.

**Value**

An object of class S3 containing with new slots \$SpliceFeatureValidated\$A3SS and \$PSI\$A3SS.

**Examples**

```
marvel.demo <- readRDS(system.file("extdata/data", "marvel.demo.rds", package="MARVEL"))

marvel.demo <- ComputePSI.A3SS(MarvelObject=marvel.demo,
                               CoverageThreshold=10
                              )
```

---

|                 |                                                                                  |
|-----------------|----------------------------------------------------------------------------------|
| ComputePSI.A5SS | <i>Compute alternative 5' splice site (A5SS) percent spliced-in (PSI) values</i> |
|-----------------|----------------------------------------------------------------------------------|

---

**Description**

Validate A5SS splicing events and subsequently computes percent spliced-in (PSI) values these high-quality splicing events.

**Usage**

```
ComputePSI.A5SS(MarvelObject, CoverageThreshold)
```

**Arguments**

MarvelObject    Marvel object. S3 object generated from CreateMarvelObject function.  
 CoverageThreshold    Numeric value. Coverage threshold below which the PSI of the splicing event will be censored, i.e. annotated as missing (NA). Coverage defined as the total number of reads supporting both included and excluded isoforms.

**Value**

An object of class S3 with new slots \$SpliceFeatureValidated\$A5SS and \$PSI\$A5SS.

**Examples**

```
marvel.demo <- readRDS(system.file("extdata/data", "marvel.demo.rds", package="MARVEL"))
marvel.demo <- ComputePSI.A5SS(MarvelObject=marvel.demo,
                               CoverageThreshold=10
                              )
```

---

|                |                                                                             |
|----------------|-----------------------------------------------------------------------------|
| ComputePSI.AFE | <i>Compute alternative first exon (AFE) percent spliced-in (PSI) values</i> |
|----------------|-----------------------------------------------------------------------------|

---

**Description**

Computes percent spliced-in (PSI) for alternative first exon (ALE) splicing events.

**Usage**

```
ComputePSI.AFE(MarvelObject, CoverageThreshold = 10)
```

**Arguments**

MarvelObject    Marvel object. S3 object generated from DetectEvents function.  
 CoverageThreshold    Numeric value. Coverage threshold below which the PSI of the splicing event will be censored, i.e. annotated as missing (NA). Coverage defined as the total number of reads supporting both included and excluded isoforms.

**Value**

An object of class S3 containing with new slots \$SpliceFeatureValidated\$AFE and \$PSI\$AFE.

**Examples**

```
marvel.demo <- readRDS(system.file("extdata/data", "marvel.demo.rds", package="MARVEL"))
marvel.demo <- ComputePSI.AFE(MarvelObject=marvel.demo,
                               CoverageThreshold=10
                              )
```

---

ComputePSI.ALE      *Compute alternative last exon (ALE) percent spliced-in (PSI) values*

---

**Description**

Computes percent spliced-in (PSI) for alternative last exon (ALE) splicing events.

**Usage**

```
ComputePSI.ALE(MarvelObject, CoverageThreshold = 10)
```

**Arguments**

MarvelObject      Marvel object. S3 object generated from DetectEvents function.

CoverageThreshold  
 Numeric value. Coverage threshold below which the PSI of the splicing event will be censored, i.e. annotated as missing (NA). Coverage defined as the total number of reads supporting both included and excluded isoforms.

**Value**

An object of class S3 containing with new slots \$SpliceFeatureValidated\$ALE and \$PSI\$ALE.

**Examples**

```
marvel.demo <- readRDS(system.file("extdata/data", "marvel.demo.rds", package="MARVEL"))

marvel.demo <- ComputePSI.ALE(MarvelObject=marvel.demo,
                              CoverageThreshold=10
                              )
```

---

ComputePSI.MXE      *Compute mutually exclusive exons (MXE) percent spliced-in (PSI) values*

---

**Description**

Validate MXE splicing events and subsequently computes percent spliced-in (PSI) values these high-quality splicing events.

**Usage**

```
ComputePSI.MXE(MarvelObject, CoverageThreshold, UnevenCoverageMultiplier = 10)
```



**Arguments**

- MarvelObject**     Marvel object. S3 object generated from CreateMarvelObject function.
- CoverageThreshold**  
                     Numeric value. Coverage threshold below which the PSI of the splicing event will be censored, i.e. annotated as missing (NA). Coverage defined as the total number of reads supporting both included and excluded isoforms.
- UnevenCoverageMultiplier**  
                     Numeric value. Maximum allowable fold difference between two included or two excluded junction counts for MXE.

**Details**

This function computes the PSI for each MXE splicing event. Splicing events provided in SpliceFeature data frame will first be cross-checked against the splice junctions provided in SpliceJunction data frame. Only events whose junctions are found in SpliceJunction are retained. The formula for computing PSI is the number of junction reads supporting the included isoform divided by the total number of reads supporting both included and excluded isoforms.

**Value**

An object of class S3 with new slots \$SpliceFeatureValidated\$MXE and \$PSI\$MXE.

**Author(s)**

Sean Wen <sean.wenwx@gmail.com>

**Examples**

```
marvel.demo <- readRDS(system.file("extdata/data", "marvel.demo.rds", package="MARVEL"))

marvel.demo <- ComputePSI.MXE(MarvelObject=marvel.demo,
                             CoverageThreshold=10,
                             UnevenCoverageMultiplier=10
                             )
```

---

 ComputePSI.RI

---

*Compute retained-intron (RI) percent spliced-in (PSI) values*


---

**Description**

Validate RI splicing events and subsequently computes percent spliced-in (PSI) values these high-quality splicing events.

**Usage**

```

ComputePSI.RI(
  MarvelObject,
  CoverageThreshold,
  IntronCounts,
  thread,
  read.length = 1
)

```

**Arguments**

|                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|-------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| MarvelObject      | Marvel object. S3 object generated from CreateMarvelObject function.                                                                                                                                                                                                                                                                                                                                                                                |
| CoverageThreshold | Numeric value. Coverage threshold below which the PSI of the splicing event will be censored, i.e. annotated as missing (NA). Coverage defined as the total number of reads supporting both included and excluded isoforms.                                                                                                                                                                                                                         |
| IntronCounts      | Data frame. Columns indicate sample IDs, rows indicate intron coordinates, and values indicate total intron coverage. The first column needs to be named coord.intron. These values will be combined with splice junction counts in the MARVEL object to compute PSI values.                                                                                                                                                                        |
| thread            | Numeric value. Set number of threads.                                                                                                                                                                                                                                                                                                                                                                                                               |
| read.length       | Numeric value. The length of read. This number will be specific to the sequencing mode. E.g. read length should be set to 150 when samples were sequenced in 150bp paired-end or single-end. This option should only be specified when users used read-counting approach for computing intron counts. The option should be left with its default value 1 when users tabulated the per-base count and summed them up to arrive at the intron counts. |

**Value**

An object of class S3 with new slots `$SpliceFeatureValidated$RI` and `$PSI$RI`.

**Examples**

```

marvel.demo <- readRDS(system.file("extdata/data", "marvel.demo.rds", package="MARVEL"))

marvel.demo <- ComputePSI.RI(MarvelObject=marvel.demo,
                             CoverageThreshold=10,
                             IntronCounts=marvel.demo$IntronCounts,
                             thread=1
                             )

```

---

`ComputePSI.SE`*Compute skipped-exon (SE) percent spliced-in (PSI) values*

---

### Description

Validate SE splicing events and subsequently computes percent spliced-in (PSI) values these high-quality splicing events.

### Usage

```
ComputePSI.SE(MarvelObject, CoverageThreshold, UnevenCoverageMultiplier = 10)
```

### Arguments

`MarvelObject` S3 object generated from `CreateMarvelObject` function.

`CoverageThreshold`

Numeric value. Coverage threshold below which the PSI of the splicing event will be censored, i.e. annotated as missing (NA). Coverage defined as the total number of reads supporting both included and excluded isoforms.

`UnevenCoverageMultiplier`

Numeric value. Maximum allowable fold difference between two included junction counts.

### Details

This function computes the PSI for each SE splicing event. Splicing events provided in `SpliceFeature` data frame will first be cross-checked against the splice junctions provided in `SpliceJunction` data frame. Only events whose junctions are found in `SpliceJunction` are retained. The formula for computing PSI is the number of junction reads supporting the included isoform divided by the total number of reads supporting both included and excluded isoforms.

### Value

An object of class S3 with new slots `$SpliceFeatureValidated$SE $PSI$SE`.

### Examples

```
marvel.demo <- readRDS(system.file("extdata/data", "marvel.demo.rds", package="MARVEL"))
```

```
marvel.demo <- ComputePSI.SE(MarvelObject=marvel.demo,  
                             CoverageThreshold=10,  
                             UnevenCoverageMultiplier=10  
                             )
```

---

CountEvents

*Tabulate the number of expressed splicing events*


---

### Description

Tabulates and plots the number of expressed splicing events for each splicing event category for a specified cell group.

### Usage

```
CountEvents(MarvelObject, sample.ids, min.cells, event.group.colors = NULL)
```

### Arguments

|                    |                                                                                                                                                                                                 |
|--------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| MarvelObject       | Marvel object. S3 object generated from TransformExpValues function.                                                                                                                            |
| sample.ids         | Vector of character strings. Sample IDs that constitute the cell group.                                                                                                                         |
| min.cells          | Numeric value. Minimum number of cells expressing the splicing event for the event to be included for tabulation. A splicing event is defined as expressed when it has a non-missing PSI value. |
| event.group.colors | Vector of character strings. Colors for the event groups. If not specified, default ggplot2 colors will be used.                                                                                |

### Value

An object of class S3 with new slots `MarvelObject$N.Events$Table` and `MarvelObject$N.Events$Plot`.

### Examples

```
marvel.demo <- readRDS(system.file("extdata/data", "marvel.demo.rds", package="MARVEL"))

# Define cell group for analysis
df.pheno <- marvel.demo$SplicePheno
sample.ids <- df.pheno[which(df.pheno$cell.type=="iPSC"), "sample.id"]

# Tabulate expressed events
marvel.demo <- CountEvents(MarvelObject=marvel.demo,
                           sample.ids=sample.ids,
                           min.cells=5,
                           event.group.colors=NULL
                           )

# Check outputs
marvel.demo$N.Events$Table
marvel.demo$N.Events$Plot
```

---

CreateMarvelObject      *Create Marvel object for plate-based RNA-sequencing data*

---

### Description

Creates an S3 object named `Marvel` for downstream analysis, specifically for plate-based RNA-sequencing data.

### Usage

```
CreateMarvelObject(  
  SplicePheno = NULL,  
  SpliceJunction = NULL,  
  IntronCounts = NULL,  
  SpliceFeature = NULL,  
  SpliceFeatureValidated = NULL,  
  PSI = NULL,  
  GeneFeature = NULL,  
  Exp = NULL,  
  GTF = NULL  
)
```

### Arguments

|                                     |                                                                                                                      |
|-------------------------------------|----------------------------------------------------------------------------------------------------------------------|
| <code>SplicePheno</code>            | Data frame. Sample metadata.                                                                                         |
| <code>SpliceJunction</code>         | Data frame. Splice junction counts matrix.                                                                           |
| <code>IntronCounts</code>           | Data frame. Intron coverage matrix.                                                                                  |
| <code>SpliceFeature</code>          | List of data frames. Each data frame is the exon-level alternative splicing event metadata.                          |
| <code>SpliceFeatureValidated</code> | List of data frames. Each data frame is the validated (high-quality) exon-level alternative splicing event metadata. |
| <code>PSI</code>                    | Data frame. PSI matrix.                                                                                              |
| <code>GeneFeature</code>            | Data frame. Gene metadata.                                                                                           |
| <code>Exp</code>                    | Data frame. Normalised, non-log2-transformed gene expression matrix.                                                 |
| <code>GTF</code>                    | Data frame. GTF used for generating the exon-level alternative splicing event metadata.                              |

### Value

An object of class S3.

**Examples**

```

marvel.demo <- readRDS(system.file("extdata/data", "marvel.demo.rds", package="MARVEL"))

SpliceJunction <- marvel.demo$SpliceJunction
SpliceJunction[1:5,1:5]

SplicePheno <- marvel.demo$SplicePheno
SplicePheno[1:5,]

SpliceFeature <- marvel.demo$SpliceFeature
SpliceFeature[["SE"]][1:5, ]

IntronCounts <- marvel.demo$IntronCounts
IntronCounts[1:5,1:5]

GeneFeature <- marvel.demo$GeneFeature
GeneFeature[1:5, ]

Exp <- marvel.demo$Exp
Exp[1:5,1:5]

marvel <- CreateMarvelObject(SpliceJunction=SpliceJunction,
                             SplicePheno=SplicePheno,
                             SpliceFeature=SpliceFeature,
                             IntronCounts=IntronCounts,
                             GeneFeature=GeneFeature,
                             Exp=Exp
                             )

class(marvel)

```

---

CreateMarvelObject.10x

*Create Marvel object for droplet-based RNA-sequencing data*

---

**Description**

Creates an S3 object named `Marvel` for downstream analysis, specifically for droplet-based RNA-sequencing data.

**Usage**

```

CreateMarvelObject.10x(
  gene.norm.matrix = NULL,
  gene.norm.pheno = NULL,
  gene.norm.feature = NULL,
  gene.count.matrix = NULL,
  gene.count.pheno = NULL,
  gene.count.feature = NULL,
  sj.count.matrix = NULL,

```



```

)
# Gene expression (Normalised)
# Matrix
df.gene.norm <- marvel.demo.10x.raw$gene.norm.matrix
df.gene.norm[1:5, 1:5]

# phenoData
df.gene.norm.pheno <- marvel.demo.10x.raw$sample.metadata
head(df.gene.norm.pheno)

# featureData
df.gene.norm.feature <- data.frame("gene_short_name"=rownames(df.gene.norm),
                                  stringsAsFactors=FALSE
)
head(df.gene.norm.feature)

# Gene expression (Counts)
# Matrix
df.gene.count <- marvel.demo.10x.raw$gene.count.matrix
df.gene.count[1:5, 1:5]

# phenoData
df.gene.count.pheno <- data.frame("cell.id"=colnames(df.gene.count),
                                  stringsAsFactors=FALSE
)
head(df.gene.count.pheno)

# featureData
df.gene.count.feature <- data.frame("gene_short_name"=rownames(df.gene.count),
                                  stringsAsFactors=FALSE
)
head(df.gene.count.feature)

# SJ (Counts)
# Matrix
df.sj.count <- marvel.demo.10x.raw$sj.count.matrix
df.sj.count[1:5, 1:5]

# phenoData
df.sj.count.pheno <- data.frame("cell.id"=colnames(df.sj.count),
                                stringsAsFactors=FALSE
)
head(df.sj.count.pheno)

# featureData
df.sj.count.feature <- data.frame("coord.intron"=rownames(df.sj.count),
                                  stringsAsFactors=FALSE
)
head(df.sj.count.feature)

# tSNE coordinates
df.coord <- marvel.demo.10x.raw$pca
head(df.coord)

```



```

# GTF
gtf <- marvel.demo.10x.raw$gtf
head(gtf)

# Create MARVEL object
marvel.demo.10x <- CreateMarvelObject.10x(gene.norm.matrix=df.gene.norm,
    gene.norm.pheno=df.gene.norm.pheno,
    gene.norm.feature=df.gene.norm.feature,
    gene.count.matrix=df.gene.count,
    gene.count.pheno=df.gene.count.pheno,
    gene.count.feature=df.gene.count.feature,
    sj.count.matrix=df.sj.count,
    sj.count.pheno=df.sj.count.pheno,
    sj.count.feature=df.sj.count.feature,
    pca=df.coord,
    gtf=gtf
)

```

---

DetectEvents

*Detect Splicing Events*


---

### Description

Detects splicing events, specifically alternative first and last exons (AFE, ALE) from GTF. This is a wrapper function for DetectEvents.ALE and DetectEvents.AFE functions.

### Usage

```

DetectEvents(
  MarvelObject,
  min.cells = 50,
  min.expr = 1,
  track.progress = FALSE,
  EventType
)

```

### Arguments

|                |                                                                                                                                                                                                                                                             |
|----------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| MarvelObject   | Marvel object. S3 object generated from CreateMarvelObject function.                                                                                                                                                                                        |
| min.cells      | Numeric value. The minimum number of cells in which the gene is expressed for the gene to included for splicing event detected and quantification. To be used in conjunction with min.expr argument. Default value is 50.                                   |
| min.expr       | Numeric value. The minimum expression value for the gene to be considered to be expressed in a cell. Default value is 1.                                                                                                                                    |
| track.progress | Logical. If set to TRUE, progress bar will appear to track the progress of the rate-limiting step of this function, which is the extraction of the final exon-exon junctions. Default value is FALSE. Only applicable when EventType set to "ALE" or "AFE". |

**EventType** Character string. Indicate which splicing event type to calculate the PSI values for. Can take value "ALE" or "AFE".

### Value

An object of class S3 with new slot `MarvelObject$SpliceFeature$ALE` or `MarvelObject$SpliceFeature$AFE`.

### Examples

```
marvel.demo <- readRDS(system.file("extdata/data", "marvel.demo.rds", package="MARVEL"))

marvel.demo <- DetectEvents(MarvelObject=marvel.demo,
                           min.cells=5,
                           min.expr=1,
                           track.progress=FALSE,
                           EventType="AFE"
                           )
```

---

DetectEvents.AFE      *Detect alternative first exons*

---

### Description

Detects alternative first exons from GTF. This is a wrapper function for `DetectEvents.AFE.PosStrand` and `DetectEvents.AFE.NegStrand` functions.

### Usage

```
DetectEvents.AFE(
  MarvelObject,
  min.cells = 50,
  min.expr = 1,
  track.progress = FALSE
)
```

### Arguments

**MarvelObject** Marvel object. S3 object generated from `CreateMarvelObject` function.

**min.cells** Numeric value. The minimum number of cells in which the gene is expressed for the gene to included for splicing event detected and quantification. To be used in conjunction with `min.expr` argument. Default value is 50.

**min.expr** Numeric value. The minimum expression value for the gene to be considered to be expressed in a cell. Default value is 1.

**track.progress** Logical. If set to TRUE, progress bar will appear to track the progress of the rate-limiting step of this function, which is the extraction of the final exon-exon junctions. Default value is FALSE.

**Value**

An object of class S3 with new slot `MarvelObject$SpliceFeature$AFE`.

**Examples**

```
marvel.demo <- readRDS(system.file("extdata/data", "marvel.demo.rds", package="MARVEL"))

marvel.demo <- DetectEvents.AFE(MarvelObject=marvel.demo,
                                min.cells=5,
                                min.expr=1,
                                track.progress=FALSE
                                )
```

---

DetectEvents.AFE.NegStrand

*Detect alternative first exons on negative strand*

---

**Description**

Detects alternative first exons, specifically for genes transcribed on the negative strand of the DNA.

**Usage**

```
DetectEvents.AFE.NegStrand(
  MarvelObject,
  parsed.gtf = NULL,
  min.cells = 50,
  min.expr = 1,
  track.progress = FALSE
)
```

**Arguments**

|                             |                                                                                                                                                                                                                                        |
|-----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>MarvelObject</code>   | S3 object generated from <code>CreateMarvelObject</code> function.                                                                                                                                                                     |
| <code>parsed.gtf</code>     | Data frame. GTF file with the <code>gene_id</code> parsed. Generated from the <code>DetectEvents.AFE</code> function.                                                                                                                  |
| <code>min.cells</code>      | Numeric value. The minimum number of cells in which the gene is expressed for the gene to included for splicing event detected and quantification. To be used in conjunction with <code>min.expr</code> argument. Default value is 50. |
| <code>min.expr</code>       | Numeric value. The minimum expression value for the gene to be considered to be expressed in a cell. Default value is 1.                                                                                                               |
| <code>track.progress</code> | Logical. If set to <code>TRUE</code> , progress bar will appear to track the progress of the rate-limiting step of this function, which is the extraction of the final exon-exon junctions. Default value is <code>FALSE</code> .      |

**Value**

An object of class S3 with new slot `MarvelObject$SpliceFeature$AFE.NegStrand`.

**Examples**

```
marvel.demo <- readRDS(system.file("extdata/data", "marvel.demo.rds", package="MARVEL"))

marvel.demo <- DetectEvents.AFE.NegStrand(MarvelObject=marvel.demo,
                                           parsed.gtf=NULL,
                                           min.cells=5,
                                           min.expr=1,
                                           track.progress=FALSE
                                           )
```

---

DetectEvents.AFE.PosStrand

*Detect alternative first exons on positive strand*

---

**Description**

Detects alternative first exons, specifically for genes transcribed on the positive strand of the DNA.

**Usage**

```
DetectEvents.AFE.PosStrand(
  MarvelObject,
  parsed.gtf = NULL,
  min.cells = 50,
  min.expr = 1,
  track.progress = FALSE
)
```

**Arguments**

|                             |                                                                                                                                                                                                                                        |
|-----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>MarvelObject</code>   | S3 object generated from <code>CreateMarvelObject</code> function.                                                                                                                                                                     |
| <code>parsed.gtf</code>     | Data frame. GTF file with the <code>gene_id</code> parsed. Generated from the <code>DetectEvents.AFE</code> function.                                                                                                                  |
| <code>min.cells</code>      | Numeric value. The minimum number of cells in which the gene is expressed for the gene to included for splicing event detected and quantification. To be used in conjunction with <code>min.expr</code> argument. Default value is 50. |
| <code>min.expr</code>       | Numeric value. The minimum expression value for the gene to be considered to be expressed in a cell. Default value is 1.                                                                                                               |
| <code>track.progress</code> | Logical. If set to <code>TRUE</code> , progress bar will appear to track the progress of the rate-limiting step of this function, which is the extraction of the final exon-exon junctions. Default value is <code>FALSE</code> .      |

**Value**

An object of class S3 with new slot `MarvelObject$SpliceFeature$AFE.PosStrand`.

**Examples**

```
marvel.demo <- readRDS(system.file("extdata/data", "marvel.demo.rds", package="MARVEL"))

marvel.demo <- DetectEvents.AFE.PosStrand(MarvelObject=marvel.demo,
                                          parsed.gtf=NULL,
                                          min.cells=5,
                                          min.expr=1,
                                          track.progress=FALSE
                                          )
```

---

DetectEvents.ALE      *Detect alternative last exons*

---

**Description**

Detects alternative last exons from GTF. This is a wrapper function for `DetectEvents.ALE.PosStrand` and `DetectEvents.ALE.NegStrand` functions.

**Usage**

```
DetectEvents.ALE(
  MarvelObject,
  min.cells = 50,
  min.expr = 1,
  track.progress = FALSE
)
```

**Arguments**

|                             |                                                                                                                                                                                                                                           |
|-----------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>MarvelObject</code>   | Marvel object. S3 object generated from <code>CreateMarvelObject</code> function.                                                                                                                                                         |
| <code>min.cells</code>      | Numeric value. The minimum number of cells in which the gene is expressed for the gene to be included for splicing event detected and quantification. To be used in conjunction with <code>min.expr</code> argument. Default value is 50. |
| <code>min.expr</code>       | Numeric value. The minimum expression value for the gene to be considered to be expressed in a cell. Default value is 1.                                                                                                                  |
| <code>track.progress</code> | Logical. If set to TRUE, progress bar will appear to track the progress of the rate-limiting step of this function, which is the extraction of the final exon-exon junctions. Default value is FALSE.                                     |

**Value**

An object of class S3 with new slot `MarvelObject$SpliceFeature$ALE`.

**Examples**

```
marvel.demo <- readRDS(system.file("extdata/data", "marvel.demo.rds", package="MARVEL"))

marvel.demo <- DetectEvents.ALE(MarvelObject=marvel.demo,
                                min.cells=5,
                                min.expr=1,
                                track.progress=FALSE
                                )
```

---

DetectEvents.ALE.NegStrand

*Detect alternative last exons on negative strand*

---

**Description**

Detects alternative last exons, specifically for genes transcribed on the negative strand of the DNA.

**Usage**

```
DetectEvents.ALE.NegStrand(
  MarvelObject,
  parsed.gtf = NULL,
  min.cells = 50,
  min.expr = 1,
  track.progress = FALSE
)
```

**Arguments**

|                |                                                                                                                                                                                                                           |
|----------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| MarvelObject   | S3 object generated from CreateMarvelObject function.                                                                                                                                                                     |
| parsed.gtf     | Data frame. GTF file with the gene_id parsed. Generated from the DetectEvents.ALE function.                                                                                                                               |
| min.cells      | Numeric value. The minimum number of cells in which the gene is expressed for the gene to included for splicing event detected and quantification. To be used in conjunction with min.expr argument. Default value is 50. |
| min.expr       | Numeric value. The minimum expression value for the gene to be considered to be expressed in a cell. Default value is 1.                                                                                                  |
| track.progress | Logical. If set to TRUE, progress bar will appear to track the progress of the rate-limiting step of this function, which is the extraction of the final exon-exon junctions. Default value is FALSE.                     |

**Value**

An object of class S3 with new slot MarvelObject\$SpliceFeature\$ALE.NegStrand.

## Examples

```
marvel.demo <- readRDS(system.file("extdata/data", "marvel.demo.rds", package="MARVEL"))

marvel.demo <- DetectEvents.ALE.NegStrand(MarvelObject=marvel.demo,
                                           parsed.gtf=NULL,
                                           min.cells=5,
                                           min.expr=1,
                                           track.progress=FALSE
                                           )
```

---

DetectEvents.ALE.PosStrand

*Detect alternative last exons on positive strand*

---

## Description

Detects alternative last exons, specifically for genes transcribed on the positive strand of the DNA.

## Usage

```
DetectEvents.ALE.PosStrand(
  MarvelObject,
  parsed.gtf = NULL,
  min.cells = 50,
  min.expr = 1,
  track.progress = FALSE
)
```

## Arguments

|                |                                                                                                                                                                                                                           |
|----------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| MarvelObject   | S3 object generated from CreateMarvelObject function.                                                                                                                                                                     |
| parsed.gtf     | Data frame. GTF file with the gene_id parsed. Generated from the DetectEvents.ALE function.                                                                                                                               |
| min.cells      | Numeric value. The minimum number of cells in which the gene is expressed for the gene to included for splicing event detected and quantification. To be used in conjunction with min.expr argument. Default value is 50. |
| min.expr       | Numeric value. The minimum expression value for the gene to be considered to be expressed in a cell. Default value is 1.                                                                                                  |
| track.progress | Logical. If set to TRUE, progress bar will appear to track the progress of the rate-limiting step of this function, which is the extraction of the final exon-exon junctions. Default value is FALSE.                     |

## Value

An object of class S3 with new slot MarvelObject\$SpliceFeature\$ALE.PosStrand.

**Examples**

```
marvel.demo <- readRDS(system.file("extdata/data", "marvel.demo.rds", package="MARVEL"))

marvel.demo <- DetectEvents.ALE.PosStrand(MarvelObject=marvel.demo,
                                          parsed.gtf=NULL,
                                          min.cells=5,
                                          min.expr=1,
                                          track.progress=FALSE
                                          )
```

---

FilterGenes.10x      *Filter specific gene types*

---

**Description**

Retain genes of specific type, e.g., protein-coding genes.

**Usage**

```
FilterGenes.10x(MarvelObject, gene.type = "protein_coding")
```

**Arguments**

**MarvelObject**      Marvel object. S3 object generated from AnnotateGenes.10x function.  
**gene.type**          Character string. Gene type to keep. Specification should match that of GTF.

**Value**

An object of class S3 containing the updated slots `MarvelObject$gene.metadata`, `MarvelObject$gene.norm.matrix`, `MarvelObject$sj.metadata`, and `MarvelObject$sj.count.matrix`.

**Examples**

```
# Load un-processed MARVEL object
marvel.demo.10x.raw <- readRDS(system.file("extdata/data",
                                          "marvel.demo.10x.raw.rds",
                                          package="MARVEL"))
)

# Annotate gene metadata
marvel.demo.10x <- AnnotateGenes.10x(MarvelObject=marvel.demo.10x.raw)

# Annotate junction metadata
marvel.demo.10x <- AnnotateSJ.10x(MarvelObject=marvel.demo.10x)

# Validate junctions
marvel.demo.10x <- ValidateSJ.10x(MarvelObject=marvel.demo.10x)
```





















---

FindPTC.SE.PosStrand *Find premature terminal codon (PTC) for skipped-exon (SE) located on the positive strand of the transcript*

---

### Description

Finds PTC(s) introduced by alternative exons into protein-coding transcripts.

### Usage

```
FindPTC.SE.PosStrand(MarvelObject, tran_id, gene_id)
```

### Arguments

MarvelObject S3 object generated from CompareValues.PSI and ParseGTF function.  
 tran\_id Character string. Vector of tran\_id to look for PTCs.  
 gene\_id Character string. Vector of gene\_id corresponding to the tran\_id argument.

### Details

This function finds PTC(s) introduced by alternative exons into protein-coding transcripts. It also records the distance between a PTCs and the final splice junction for a given protein-coding transcript. Non-protein-coding transcripts or transcripts in which splicing events are located outside of the transcripts' open-reading frame (ORF) are not analysed for PTCs but are noted.

### Value

A data frame of transcripts containing splicing events meeting the psi.de.sig and psi.de.diff criteria are categorised based on the presence or absence of PTCs.

### Examples

```
marvel.demo <- readRDS(system.file("extdata/data", "marvel.demo.rds", package="MARVEL"))

# Define relevant event type
results <- marvel.demo$DE$PSI$Table[["ad"]]
index.1 <- which(results$event_type=="SE")
index.2 <- grep(":+@", results$tran_id, fixed=TRUE)
index <- intersect(index.1, index.2)
results <- results[index, ]
tran_id <- results$tran_id[1]
gene_id <- results$gene_id[1]

# Find PTC
results <- FindPTC.SE.PosStrand(MarvelObject=marvel.demo,
                               tran_id=NULL,
                               gene_id=gene_id
                              )
```

```
# Check output
head(results)
```

---

IsoSwitch

*Classify gene-splicing relationship*

---

## Description

Classify gene-splicing relative changes to each other from cell group 1 to group 2. Classifications are coordinated, opposing, isoform-switching, and complex. In coordinated relationship, both gene and splicing changes in the same direction from cell group 1 to group 2. In opposing relationship, gene changes in the opposite direction relative to splicing from cell group 1 to group 2. In isoform-switching, there is differential splice junction usage without differential expression of the corresponding gene between cell group 1 and group 2. Complex relationship involves genes with both coordinated and opposing relationships with splicing. Only differentially spliced junctions are included for analysis here.

## Usage

```
IsoSwitch(
  MarvelObject,
  method,
  psi.pval = 0.1,
  psi.delta = 0,
  gene.pval = 0.1,
  gene.log2fc = 0.5,
  event.type = NULL,
  custom.tran_ids = NULL
)
```

## Arguments

|              |                                                                                                                                                                                                                                                                                                                    |
|--------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| MarvelObject | Marvel object. S3 object generated from <code>CompareValues.Genes.10x</code> function.                                                                                                                                                                                                                             |
| method       | Character string. The statistical method used for differential splicing analysis.                                                                                                                                                                                                                                  |
| psi.pval     | Numeric value. Adjusted p-value below which the splicing event is considered differentially spliced and included for isoform switching analysis. To be used in conjunction with <code>psi.delta</code> .                                                                                                           |
| psi.delta    | Numeric value. The absolute minimum difference in PSI values between the two cell groups above which the splicing event is considered differentially spliced and included for isoform switching analysis. To be used in conjunction with <code>psi.pval</code> . Specify 0 (default) to switch this threshold off. |
| gene.pval    | Numeric value. Adjusted p-value below which the gene is considered differentially expressed. Default value is 0.1.                                                                                                                                                                                                 |

|                              |                                                                                                                                                                                                                                                                                            |
|------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>gene.log2fc</code>     | Numeric value. The absolute log2 fold change in mean gene expression values between the two cell groups above which the gene is considered differentially expressed. To be used in conjunction with <code>gene.pval</code> . Specify 0 to switch this threshold off. Default value is 0.5. |
| <code>event.type</code>      | Character string. Indicate which splicing event type to include for analysis. Can take any combination of values: "SE", "MXE", "RI", "A5SS", "A3SS", "AFE", or <code>\code{"ALE}</code> .                                                                                                  |
| <code>custom.tran_ids</code> | Vector of character strings. Subset of <code>tran_ids</code> to be brought forward for analysis after filtering based on <code>psi.pval</code> and <code>psi.delta</code> .                                                                                                                |

**Value**

An object of class S3 containing with new slots `MarvelObject$DE$Cor$Table`, `MarvelObject$DE$Cor$Plot`, and `MarvelObject$DE$Cor$Plot.Stats`.

**Examples**

```
marvel.demo <- readRDS(system.file("extdata/data", "marvel.demo.rds", package="MARVEL"))

marvel.demo <- IsoSwitch(MarvelObject=marvel.demo,
                        method="ad",
                        psi.pval=0.1,
                        psi.delta=0,
                        gene.pval=0.1,
                        gene.log2fc=0.5
                        )

# Check outputs
head(marvel.demo$DE$Cor$Table_Raw)
head(marvel.demo$DE$Cor$Table)
marvel.demo$DE$Cor$Plot
marvel.demo$DE$Cor$Plot.Stats
```

---

IsoSwitch.10x

*Classify gene-splicing relationship*

---

**Description**

Classify gene-splicing relative changes to each other from cell group 1 to group 2. Classifications are coordinated, opposing, isoform-switching, and complex. In coordinated relationship, both gene and splicing changes in the same direction from cell group 1 to group 2. In opposing relationship, gene changes in the opposite direction relative to splicing from cell group 1 to group 2. In isoform-switching, there is differential splice junction usage without differential expression of the corresponding gene between cell group 1 and group 2. Complex relationship involves genes with both coordinated and opposing relationships with splicing. Only differentially spliced junctions are included for analysis here.

**Usage**

```

IsoSwitch.10x(
  MarvelObject,
  pval.sj = 0.05,
  log2fc.sj = NULL,
  delta.sj = 5,
  min.gene.norm = 0,
  pval.adj.gene = 0.05,
  log2fc.gene = 0.5
)

```

**Arguments**

|                            |                                                                                                                                                                                                                                                    |
|----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>MarvelObject</code>  | Marvel object. S3 object generated from <code>CompareValues.Genes.10x</code> function.                                                                                                                                                             |
| <code>pval.sj</code>       | Numeric value. p-value from differential splicing analysis, below which, the splice junction is considered differentially spliced. Default is <code>0.05</code> .                                                                                  |
| <code>log2fc.sj</code>     | Numeric value. Absolute log2 fold change from differential splicing analysis, above which, the splice junction is considered differentially spliced. This option should be <code>NULL</code> if <code>delta.sj</code> has been specified.          |
| <code>delta.sj</code>      | Numeric value. Absolute difference in average PSI values between the two cell groups, above which, the splice junction is considered differentially spliced. This option should be <code>NULL</code> if <code>log2fc.sj</code> has been specified. |
| <code>min.gene.norm</code> | Numeric value. The average normalised gene expression across the two cell groups above which the splice junction is considered differentially spliced. Default is <code>0</code> .                                                                 |
| <code>pval.adj.gene</code> | Numeric value. Adjusted p-value from differential gene expression analysis, below which, the gene is considered differentially expressed. Default is <code>0.05</code> .                                                                           |
| <code>log2fc.gene</code>   | Numeric value. Absolute log2 fold change from differential gene expression analysis, above which, the gene is considered differentially expressed. This option should be <code>NULL</code> if <code>delta.sj</code> has been specified.            |

**Value**

An object of class `S3` containing new slots `MarvelObject$SJ.Gene.Cor$Data`, `MarvelObject$SJ.Gene.Cor$Proportion$` and `MarvelObject$SJ.Gene.Cor$Proportion$Table`.

**Examples**

```

marvel.demo.10x <- readRDS(system.file("extdata/data",
  "marvel.demo.10x.rds",
  package="MARVEL"))
)

marvel.demo.10x <- readRDS(system.file("extdata/data",
  "marvel.demo.10x.rds",
  package="MARVEL"))
)

```

```
marvel.demo.10x <- IsoSwitch.10x(
  MarvelObject=marvel.demo.10x,
  pval.sj=0.05,
  delta.sj=5,
  min.gene.norm=1.0,
  pval.adj.gene=0.05,
  log2fc.gene=0.5
)

# Check outputs
marvel.demo.10x$SJ.Gene.Cor$Proportion$Plot
marvel.demo.10x$SJ.Gene.Cor$Proportion$Table
cols <- c("coord.intron", "gene_short_name", "cor.complete")
head(marvel.demo.10x$SJ.Gene.Cor$Data[,cols])
```

---

IsoSwitch.PlotExpr      *Plot gene-splicing relative change*

---

## Description

Plots delta PSI vs gene log2-fold change

## Usage

```
IsoSwitch.PlotExpr(MarvelObject, anno = FALSE)
```

## Arguments

|              |                                                                                                                                                                      |
|--------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| MarvelObject | Marvel object. S3 object generated from CompareValues.Genes.10x function.                                                                                            |
| anno         | Logical value. If set to TRUE, genes with coordinated, opposing or complex change relative to splicing change will be annotated on the plot. Default value is FALSE. |

## Value

An object of class S3 containing with new slots MarvelObject\$DE\$Cor\$PSIvsExpr\$Plot.

## Examples

```
marvel.demo <- readRDS(system.file("extdata/data", "marvel.demo.rds", package="MARVEL"))

marvel.demo <- IsoSwitch.PlotExpr(MarvelObject=marvel.demo, anno=TRUE)

# Check output
marvel.demo$DE$Cor$PSIvsExpr$Plot
```

---

**ModalityChange***Classify modality changes*

---

**Description**

Classifies the type of modality change for each splicing event that has taken place between 2 groups of cells.

**Usage**

```
ModalityChange(MarvelObject, method, psi.pval, psi.delta = 0)
```

**Arguments**

|                           |                                                                                                                                                                                                     |
|---------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>MarvelObject</code> | Marvel object. S3 object generated from <code>CompareValues</code> function.                                                                                                                        |
| <code>method</code>       | Character string. The statistical method used for differential splicing analysis.                                                                                                                   |
| <code>psi.pval</code>     | Numeric value. Adjusted p-value below which the splicing event is considered differentially spliced and included for modality analysis.                                                             |
| <code>psi.delta</code>    | Numeric value. The absolute difference between the means PSI values of cell group 1 and 2, above which, the splicing event is considered differentially spliced and included for modality analysis. |

**Value**

An object of class S3 with new slots `MarvelObject$DE$Modality$Table`, `MarvelObject$DE$Modality$Plot`, and `MarvelObject$DE$Modality$Plot.Stats`.

**Examples**

```
marvel.demo <- readRDS(system.file("extdata/data", "marvel.demo.rds", package="MARVEL"))

marvel.demo <- ModalityChange(MarvelObject=marvel.demo,
                              method="ad",
                              psi.pval=0.1,
                              psi.delta=0
                              )

# Check outputs
head(marvel.demo$DE$Modality$Table)
marvel.demo$DE$Modality$Plot
marvel.demo$DE$Modality$Plot.Stats
```

---

|          |                                       |
|----------|---------------------------------------|
| ParseGTF | <i>Parse gene transfer file (GTF)</i> |
|----------|---------------------------------------|

---

**Description**

Parses the gene transfer file (GTF) for downstream nonsense-mediated decay (NMD) prediction.

**Usage**

```
ParseGTF(MarvelObject)
```

**Arguments**

MarvelObject    Marvel object. S3 object generated from CompareValues.PSI function.

**Details**

This function parses the GTF in order to generate new columns for gene IDs, transcript IDs, and transcript type. These information are extracted from the attribute (9th) column for a standard GTF. These information will be used for downstream NMD prediction.

**Value**

An object of class S3 with new slot MarvelObject\$NMD\$GTF.

**Examples**

```
marvel.demo <- readRDS(system.file("extdata/data", "marvel.demo.rds", package="MARVEL"))  
marvel.demo <- ParseGTF(MarvelObject=marvel.demo)
```

---

|        |                                                       |
|--------|-------------------------------------------------------|
| PctASE | <i>Tabulate differentially spliced splicing event</i> |
|--------|-------------------------------------------------------|

---

**Description**

Tabulates the percentage or absolute number of significant splicing events for each splicing type.

**Usage**

```
PctASE(
  MarvelObject,
  method,
  psi.pval,
  psi.mean.diff,
  ylabels.size = 8,
  barlabels.size = 3,
  x.offset = 0,
  direction.color = NULL,
  mode = "percentage"
)
```

**Arguments**

|                              |                                                                                                                                                                                                                                            |
|------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>MarvelObject</code>    | Marvel object. S3 object generated from <code>CompareValues</code> function.                                                                                                                                                               |
| <code>method</code>          | Character string. The statistical method used for differential splicing analysis.                                                                                                                                                          |
| <code>psi.pval</code>        | Numeric value. Adjusted p-value below which the splicing event is considered differentially spliced and included for tabulation.                                                                                                           |
| <code>psi.mean.diff</code>   | Numeric value. The minimum absolute differences in PSI values between the two cell groups above which the splicing event is considered differentially spliced and included for tabulation.                                                 |
| <code>ylabels.size</code>    | Numeric value. Size of the xtick labels. Default is 8.                                                                                                                                                                                     |
| <code>barlabels.size</code>  | Numeric value. Size of the labels above each bar. Default is 3                                                                                                                                                                             |
| <code>x.offset</code>        | Numeric value. The values on the x-axis to offset by. Useful when right margin overshadow the numbers above the bars. Default value is 0.                                                                                                  |
| <code>direction.color</code> | Character strings. Vector of length 2 to specify the colors for significantly down- and up-regulated splicing events. Default is <code>NULL</code> , which corresponds to default <code>ggplot2</code> color scheme.                       |
| <code>mode</code>            | Character strings. When set to "percentage" (default), percentage of significant splicing events over total splicing events detected will be tabulated. When set to absolute, the number of significant splicing events will be tabulated. |

**Value**

An object of class S3 with new slots `MarvelObject$DE$AbsASE$Table` and `MarvelObject$DE$AbsASE$Plot`.

**Examples**

```
marvel.demo <- readRDS(system.file("extdata/data", "marvel.demo.rds", package="MARVEL"))

marvel.demo <- PctASE(MarvelObject=marvel.demo,
  method="ad",
  psi.pval=0.1,
  psi.mean.diff=0
)
```



PlotDEValues

*Plot differential splicing and gene expression analysis results***Description**

Volcano plot of differential splicing and gene expression analysis results. This is a wrapper function for PlotDEValues.PSI.Mean, PlotDEValues.Exp.Global, and PlotDEValues.Exp.Spliced.

**Usage**

```
PlotDEValues(
  MarvelObject,
  method = NULL,
  pval,
  level,
  delta = NULL,
  log2fc = NULL,
  psi.pval = NULL,
  psi.delta = NULL,
  gene.pval = NULL,
  gene.log2fc = NULL,
  point.size = 1,
  xlabel.size = 8,
  point.alpha = 1,
  anno = FALSE,
  anno.gene_short_name = NULL,
  anno.tran_id = NULL,
  label.size = 2.5,
  y.upper.offset = 5,
  event.types = c("SE", "MXE", "RI", "A5SS", "A3SS", "AFE", "ALE"),
  event.types.colors = NULL
)
```

**Arguments**

|              |                                                                                                                                                                                                                                                                                                                                                                                                   |
|--------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| MarvelObject | Marvel object. S3 object generated from CompareValues function.                                                                                                                                                                                                                                                                                                                                   |
| method       | Character string. The statistical method used for differential splicing analysis.                                                                                                                                                                                                                                                                                                                 |
| pval         | Numeric value. Only applicable when level set to "splicing.mean", "splicing.distance", and "gene.global". Adjusted p-value below which the splicing events or genes are considered as statistically significant and will consequently be color-annotated on the plot.                                                                                                                             |
| level        | Character string. Indicate "splicing.distance" if the percent spliced-in (PSI) values' distribution was previously tested between 2 groups of cells using the CompareValues function. Statistical tests for distribution include Kolmogorov-Smirnov, Kuiper, and Anderson-Darling test. Indicate "splicing.mean" or gene if the PSI or gene expression values' mean was previously tested between |

|                      |                                                                                                                                                                                                                                                                 |
|----------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                      | 2 groups of cells using the CompareValues function. Statistical tests for comparing mean are t-test and Wilcoxon rank-sum test.                                                                                                                                 |
| delta                | Numeric value. Only applicable when level set to "splicing.mean". The positive (and negative) value specified above (and below) which the splicing events are considered to be statistically significant and will consequently be color-annotated on the plot.  |
| log2fc               | Numeric value. Only applicable when level set to "gene.global". The positive (and negative) value specified above (and below) which the genes are considered to be statistically significant and will consequently be color-annotated on the plot.              |
| psi.pval             | Numeric value. Only applicable when level set to "gene.spliced". The adjusted p-value from differential splicing analysis, below which, the splicing event is considered differentially spliced. Default is 0.1.                                                |
| psi.delta            | Numeric value. Only applicable when level set to "gene.spliced". The absolute differences in average PSI value between two cell groups from differential splicing analysis, above which, the splicing event is considered differentially spliced. Default is 0. |
| gene.pval            | Numeric value. Only applicable when level set to "gene.spliced". The adjusted p-value from differential gene expression analysis, below which, the gene is considered differentially expressed. Default is 0.1.                                                 |
| gene.log2fc          | Numeric value. Only applicable when level set to "gene.spliced". The absolute log2 fold change in gene expression between two cell groups from differential splicing analysis, above which, the gene is considered differentially expressed. Default is 0.5.    |
| point.size           | Numeric value. Size of data points. Default is 1.                                                                                                                                                                                                               |
| xlabel.size          | Numeric value. Font size of the xtick labels. Default is 8.                                                                                                                                                                                                     |
| point.alpha          | Numeric value. Only applicable when level set to "splicing.mean.g2vsg1". Transparency of data points. Default is 1.                                                                                                                                             |
| anno                 | Logical value. If set to TRUE, the specific gene names or splicing events will be annotated on the plot.                                                                                                                                                        |
| anno.gene_short_name | Vector of character strings. When anno set to TRUE, the gene names to be annotated on the plot.                                                                                                                                                                 |
| anno.tran_id         | Vector of character strings. When anno set to TRUE, the coordinates of the splicing events to be annotated on the plot.                                                                                                                                         |
| label.size           | Numeric value. Only applicable if anno set to TRUE. Size of the gene name labels.                                                                                                                                                                               |
| y.upper.offset       | Numeric value. The value in $-\log_{10}(\text{p-value})$ to increase the upper limit of the y-axis. To be used when anno set to TRUE so that gene labels will not be truncated at the upper limit of the y-axis.                                                |
| event.types          | Vector of character string(s). Only applicable when level set to "splicing.mean.g2vsg1". The specific splicing event to plot. May take any one or more of the following values "SE", "MXE", "RI", "A5SS", "A3SS", "AFE", and "ALE".                             |

```
event.types.colors
```

Vector of character string(s). Only applicable when level set to "splicing.mean.g2vsg1".  
Customise colors as per splicing event type specified in event.types option.  
Should be of same length as event.types option.

### Value

An object of class S3 with new slot `MarvelObject$DE$PSI$Plot[["method"]]` when level set to "splicing.mean" or "splicing.distance" or `MarvelObject$DE$Exp.Global$Table` and `MarvelObject$DE$Exp.Global$Plot` when level set to "gene.global" or `MarvelObject$DE$Exp.Spliced$Table` and `MarvelObject$DE$Exp.Spliced$Plot` when level set to "gene.spliced".

### Examples

```
marvel.demo <- readRDS(system.file("extdata/data", "marvel.demo.rds", package="MARVEL"))

marvel.demo <- PlotDEValues(MarvelObject=marvel.demo,
                           method="ad",
                           pval=0.10,
                           level="splicing.distance"
                           )

# Check output
marvel.demo$DE$PSI$Plot[["ad"]]
```

---

PlotDEValues.Exp.Global

*Plot global differential gene expression analysis results*

---

### Description

Volcano plot of differential splicing analysis results based on all expressed genes between 2 groups of cells. x-axis represents the log<sub>2</sub> fold change in gene expression. y-axis represents the adjusted p-values.

### Usage

```
PlotDEValues.Exp.Global(
  MarvelObject,
  pval = 0.1,
  log2fc = 0.5,
  point.size = 1,
  anno = FALSE,
  anno.gene_short_name = NULL,
  label.size = 2.5,
  y.upper.offset = 5,
  xlabel.size = 8
)
```

**Arguments**

|                      |                                                                                                                                                                                                                  |
|----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| MarvelObject         | Marvel object. S3 object generated from CompareValues function.                                                                                                                                                  |
| pval                 | Numeric value. Adjusted p-value below which the genes are considered as statistically significant and will consequently be color-annotated on the plot.                                                          |
| log2fc               | Numeric value. The positive (and negative) value specified above (and below) which the genes are considered to be statistically significant and will consequently be color-annotated on the plot.                |
| point.size           | Numeric value. The point size for the data points. Default value is 1.                                                                                                                                           |
| anno                 | Logical value. If set to TRUE, the specific gene names will be annotated on the plot as defined in anno.gene_short_name option.                                                                                  |
| anno.gene_short_name | Vector of character strings. When anno set to TRUE, the gene names to be annotated on the plot.                                                                                                                  |
| label.size           | Numeric value. Only applicable if anno set to TRUE. Size of the gene name labels.                                                                                                                                |
| y.upper.offset       | Numeric value. The value in $-\log_{10}(\text{p-value})$ to increase the upper limit of the y-axis. To be used when anno set to TRUE so that gene labels will not be truncated at the upper limit of the y-axis. |
| xlabel.size          | Numeric value. Font size of the xtick labels. Default is 8.                                                                                                                                                      |

**Value**

An object of class S3 with new slots `MarvelObject$DE$Exp.Global$Table`, `MarvelObject$DE$Exp.Global$Summary`, and `MarvelObject$DE$Exp.Global$Plot`

**Examples**

```
marvel.demo <- readRDS(system.file("extdata/data", "marvel.demo.rds", package="MARVEL"))

marvel.demo <- PlotDEValues.Exp.Global(MarvelObject=marvel.demo,
                                       pval=0.10,
                                       log2fc=0.5
                                       )

# Check output
head(marvel.demo$DE$Exp.Global$Table)
marvel.demo$DE$Exp.Global$Plot
marvel.demo$DE$Exp.Global$Summary
```

---

PlotDEValues.Exp.Spliced

*Plot differential gene expression analysis of differentially spliced genes*

---

**Description**

Volcano plot of differential splicing analysis results based on differentially spliced genes between 2 groups of cells. x-axis represents the log<sub>2</sub> fold change in gene expression. y-axis represents the adjusted p-values.

**Usage**

```
PlotDEValues.Exp.Spliced(
  MarvelObject,
  method,
  psi.pval = 0.1,
  psi.delta = 0,
  gene.pval = 0.1,
  gene.log2fc = 0.5,
  point.size = 1,
  anno = FALSE,
  anno.gene_short_name = NULL,
  label.size = 2.5,
  y.upper.offset = 5,
  xlabel.size = 8
)
```

**Arguments**

|                      |                                                                                                                                                                                                                        |
|----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| MarvelObject         | S3 object generated from CompareValues function.                                                                                                                                                                       |
| method               | (Vector of) Character string(s). The method specified in CompareValues function when level option set to "splicing".                                                                                                   |
| psi.pval             | Numeric value. The adjusted p-value from differential splicing analysis, below which, the splicing event is considered differentially spliced. Default is 0.1.                                                         |
| psi.delta            | Numeric value. The absolute differences in average PSI value between two cell groups from differential splicing analysis, above which, the splicing event is considered differentially spliced. Default is 0.          |
| gene.pval            | Numeric value. The adjusted p-value from differential gene expression analysis, below which, the gene is considered differentially expressed. Default is 0.1.                                                          |
| gene.log2fc          | Numeric value. The absolute log <sub>2</sub> fold change in gene expression between two cell groups from differential splicing analysis, above which, the gene is considered differentially expressed. Default is 0.5. |
| point.size           | Numeric value. Size of data points. Default is 1.                                                                                                                                                                      |
| anno                 | Logical value. If set to TRUE, the specific gene names will be annotated on the plot as defined in anno.gene_short_name option.                                                                                        |
| anno.gene_short_name | Vector of character strings. When anno set to TRUE, the gene names to be annotated on the plot.                                                                                                                        |
| label.size           | Numeric value. Only applicable if anno set to TRUE. Size of the gene name labels.                                                                                                                                      |

`y.upper.offset` Numeric value. The value in  $-\log_{10}(\text{p-value})$  to increase the upper limit of the y-axis. To be used when `anno` set to `TRUE` so that gene labels will not be truncated at the upper limit of the y-axis.

`xlabel.size` Numeric value. Font size of the xtick labels. Default is 8.

### Value

An object of class `S3` with new slots `MarvelObject$DE$Exp.Spliced$Table`, `MarvelObject$DE$Exp.Spliced$Summary`, and `MarvelObject$DE$Exp.Spliced$Plot`.

### Examples

```
marvel.demo <- readRDS(system.file("extdata/data", "marvel.demo.rds", package="MARVEL"))

marvel.demo <- PlotDEValues.Exp.Spliced(MarvelObject=marvel.demo,
                                         method="ad",
                                         psi.pval=0.1,
                                         psi.delta=0,
                                         gene.pval=0.1,
                                         gene.log2fc=0.5
                                         )

# Check output
marvel.demo$DE$Exp.Spliced$Summary
marvel.demo$DE$Exp.Spliced$Plot
```

---

PlotDEValues.Genes.10x

*Plot differential gene analysis results*

---

### Description

Volcano plot of results from differential gene expression analysis. x-axis represents the  $\log_2$  fold change between two cell groups. y-axis represents  $-\log_{10}(\text{adjusted p-value})$ . Only genes whose splice junctions were considered to be differentially spliced are included for plotting.

### Usage

```
PlotDEValues.Genes.10x(
  MarvelObject,
  pval.sj = 0.05,
  log2fc.sj = NULL,
  delta.sj = 5,
  min.gene.norm = 0,
  pval.adj.gene = 0.05,
  log2fc.gene = 0.5,
  anno = FALSE,
  anno.gene_short_name = NULL,
  label.size = 2
)
```

**Arguments**

|                      |                                                                                                                                                                                                                          |
|----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| MarvelObject         | Marvel object. S3 object generated from CompareValues.Genes.10x function.                                                                                                                                                |
| pval.sj              | Numeric value. p-value from differential splicing analysis, below which, the splice junction is considered differentially spliced. Default is 0.05.                                                                      |
| log2fc.sj            | Numeric value. Absolute log2 fold change from differential splicing analysis, above which, the splice junction is considered differentially spliced. This option should be NULL if delta.sj has been specified.          |
| delta.sj             | Numeric value. Absolute difference in average PSI values between the two cell groups, above which, the splice junction is considered differentially spliced. This option should be NULL if log2fc.sj has been specified. |
| min.gene.norm        | Numeric value. The average normalised gene expression across the two cell groups above which the splice junction is considered differentially spliced. Default is 0.                                                     |
| pval.adj.gene        | Numeric value. Adjusted p-value from differential gene expression analysis, below which, the gene is considered differentially expressed. Default is 0.05.                                                               |
| log2fc.gene          | Numeric value. Absolute log2 fold change from differential gene expression analysis, above which, the gene is considered differentially expressed. This option should be NULL if delta.sj has been specified.            |
| anno                 | Logical value. If set to TRUE, user-specific genes in anno.gene_short_name will be annotated on the plot. Default is FALSE.                                                                                              |
| anno.gene_short_name | Vector of character strings. If anno set to TRUE, genes specified here will be annotated on the plot.                                                                                                                    |
| label.size           | Numeric value. If anno set to TRUE, the font size of the annotations on the plot will be adjusted to the size specified here. Default is 2.                                                                              |

**Value**

An object of class S3 with a new slots `MarvelObject$DE$SJ$VolcanoPlot$Gene$Plot` and `MarvelObject$DE$SJ$Volcano`

**Examples**

```
marvel.demo.10x <- readRDS(system.file("extdata/data",
                                     "marvel.demo.10x.rds",
                                     package="MARVEL"))

marvel.demo.10x <- PlotDEValues.Genes.10x(
  MarvelObject=marvel.demo.10x,
  pval.sj=0.05,
  delta.sj=5,
  min.gene.norm=1.0,
  pval.adj.gene=0.05,
  log2fc.gene=0.5
)
```

```
# Check outputs
marvel.demo.10x$DE$SJ$VolcanoPlot$Gene$Plot
head(marvel.demo.10x$DE$SJ$VolcanoPlot$Gene$Data)
```

---

PlotDEValues.PSI.Distance

*Plot differential splicing analysis results based on distance statistics.*

---

## Description

Ranked plot for differential splicing analysis results based on distance statistics. Only statistical test that assess the overall PSI distribution between two cell groups will be eligible for plotting here, e.g., Anderson-Darling and DTS. x-axis represents the distance statistics. y-axis represents the adjusted p-values.

## Usage

```
PlotDEValues.PSI.Distance(
  MarvelObject,
  method,
  pval,
  point.size = 1,
  xlabel.size = 8,
  anno = FALSE,
  anno.tran_id = NULL,
  label.size = 2.5,
  y.upper.offset = 5
)
```

## Arguments

|                |                                                                                                                                                                                                                  |
|----------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| MarvelObject   | Marvel object. S3 object generated from CompareValues function.                                                                                                                                                  |
| method         | Character string. The statistical method used for differential splicing analysis.                                                                                                                                |
| pval           | Numeric value. Adjusted p-value below which the splicing events are considered as statistically significant and will consequently be color-annotated on the plot.                                                |
| point.size     | Numeric value. The point size for the data points. Default value is 1.                                                                                                                                           |
| xlabel.size    | Numeric value. Font size of the xtick labels. Default is 8.                                                                                                                                                      |
| anno           | Logical value. If set to TRUE, the specific gene names will be annotated on the plot. Specified together with anno.tran_id.                                                                                      |
| anno.tran_id   | Vector of character strings. When anno set to TRUE, the coordinates of the splicing events to be annotated on the plot.                                                                                          |
| label.size     | Numeric value. Only applicable if anno set to TRUE. Size of the gene name labels.                                                                                                                                |
| y.upper.offset | Numeric value. The value in $-\log_{10}(\text{p-value})$ to increase the upper limit of the y-axis. To be used when anno set to TRUE so that gene labels will not be truncated at the upper limit of the y-axis. |



**Value**

An object of class S3 containing with new slot `MarvelObject$DE$PSI$Plot[["method"]]`.

**Examples**

```
marvel.demo <- readRDS(system.file("extdata/data", "marvel.demo.rds", package="MARVEL"))

marvel.demo <- PlotDEValues.PSI.Distance(MarvelObject=marvel.demo,
                                         method="ad",
                                         pval=0.10
                                         )

# Check output
marvel.demo$DE$PSI$Plot[["ad"]]
```

---

`PlotDEValues.PSI.Mean` *Plot differential splicing analysis results based on mean PSI difference*

---

**Description**

Volcano plot of differential splicing analysis results based on mean PSI difference between 2 groups of cells. x-axis represents the mean delta PSI. y-axis represents the adjusted p-values.

**Usage**

```
PlotDEValues.PSI.Mean(
  MarvelObject,
  method,
  pval = 0.1,
  delta = 5,
  point.size = 1,
  xlabel.size = 8,
  anno = FALSE,
  anno.tran_id = NULL,
  label.size = 2.5,
  y.upper.offset = 5
)
```

**Arguments**

|                           |                                                                                                                                                                                                             |
|---------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>MarvelObject</code> | Marvel object. S3 object generated from <code>CompareValues</code> function.                                                                                                                                |
| <code>method</code>       | Character string. The statistical method used for differential splicing analysis.                                                                                                                           |
| <code>pval</code>         | Numeric value. Adjusted p-value below which the splicing event are considered as statistically significant and will consequently be color-annotated on the plot.                                            |
| <code>delta</code>        | Numeric value. The positive (and negative) value specified above (and below) which the splicing events are considered to be statistically significant and will consequently be color-annotated on the plot. |

|                             |                                                                                                                                                                                                                               |
|-----------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>point.size</code>     | Numeric value. The point size for the data points. Default value is 1.                                                                                                                                                        |
| <code>xlabel.size</code>    | Numeric value. Font size of the xtick labels. Default is 8.                                                                                                                                                                   |
| <code>anno</code>           | Logical value. If set to TRUE, the specific gene names will be annotated on the plot. Specified together with <code>anno.tran_id</code> .                                                                                     |
| <code>anno.tran_id</code>   | Vector of character strings. When <code>anno</code> set to TRUE, the coordinates of the splicing events to be annotated on the plot.                                                                                          |
| <code>label.size</code>     | Numeric value. Only applicable if <code>anno</code> set to TRUE. Size of the gene name labels.                                                                                                                                |
| <code>y.upper.offset</code> | Numeric value. The value in $-\log_{10}(\text{p-value})$ to increase the upper limit of the y-axis. To be used when <code>anno</code> set to TRUE so that gene labels will not be truncated at the upper limit of the y-axis. |

### Value

An object of class S3 containing with new slot `MarvelObject$DE$PSI$Plot[["method"]]`.

### Examples

```
marvel.demo <- readRDS(system.file("extdata/data", "marvel.demo.rds", package="MARVEL"))

marvel.demo <- PlotDEValues.PSI.Mean(MarvelObject=marvel.demo,
                                     method="ad",
                                     pval=0.10,
                                     delta=5
                                   )

# Check output
marvel.demo$DE$PSI$Plot[["ad"]]
```

---

PlotDEValues.PSI.Mean.g2vsg1

*Plot differential splicing analysis results based on mean PSI difference*

---

### Description

Scatterplot of differential splicing analysis results based on mean PSI difference between 2 groups of cells. x-axis represents the mean PSI values of cell group 1. y-axis represents the mean PSI values of cell group 2.

### Usage

```
PlotDEValues.PSI.Mean.g2vsg1(
  MarvelObject,
  method,
  pval,
  delta = 5,
  point.size = 1,
```

```

xlabel.size = 8,
anno = FALSE,
anno.tran_id = NULL,
label.size = 2.5,
point.alpha = 1,
event.types = c("SE", "MXE", "RI", "A5SS", "A3SS", "AFE", "ALE"),
event.types.colors = NULL
)

```

## Arguments

|                    |                                                                                                                                                                                                             |
|--------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| MarvelObject       | Marvel object. S3 object generated from CompareValues function.                                                                                                                                             |
| method             | Character string. The statistical method used for differential splicing analysis.                                                                                                                           |
| pval               | Numeric value. Adjusted p-value below which the splicing event are considered as statistically significant and will consequently be color-annotated on the plot.                                            |
| delta              | Numeric value. The positive (and negative) value specified above (and below) which the splicing events are considered to be statistically significant and will consequently be color-annotated on the plot. |
| point.size         | Numeric value. The point size for the data points. Default value is 1.                                                                                                                                      |
| xlabel.size        | Numeric value. Font size of the xtick labels. Default is 8.                                                                                                                                                 |
| anno               | Logical value. If set to TRUE, the specific gene names will be annotated on the plot. Specified together with anno.tran_id.                                                                                 |
| anno.tran_id       | Vector of character strings. When anno set to TRUE, the coordinates of the splicing events to be annotated on the plot.                                                                                     |
| label.size         | Numeric value. Only applicable if anno set to TRUE. Size of the gene name labels.                                                                                                                           |
| point.alpha        | Numeric value. Transparency of data points. Default is 1.                                                                                                                                                   |
| event.types        | Vector of character string(s). The specific splicing event to plot. May take any one or more of the following values "SE", "MXE", "RI", "A5SS", "A3SS", "AFE", and "ALE".                                   |
| event.types.colors | Vector of character string(s). Customise colors as per splicing event type specified in event.types option. Should be of same length as event.types option.                                                 |

## Value

An object of class S3 containing with new slot `MarvelObject$DE$PSI$Plot[["method"]]`.

## Examples

```

marvel.demo <- readRDS(system.file("extdata/data", "marvel.demo.rds", package="MARVEL"))

marvel.demo <- PlotDEValues.PSI.Mean.g2vsg1(MarvelObject=marvel.demo,
                                             method="ad",
                                             pval=0.10,
                                             delta=5
                                             )

```

```
# Check output
marvel.demo$DE$PSI$Plot
marvel.demo$DE$PSI$Summary
```

---

PlotDEValues.SJ.10x *Plot differential splice junction analysis results*

---

### Description

Volcano plot of results from differential splice junction analysis. x-axis represents the average normalised gene expression across the two cell groups. y-axis represents the differences or log2 fold change between the two cell groups.

### Usage

```
PlotDEValues.SJ.10x(
  MarvelObject,
  pval = 0.05,
  log2fc = NULL,
  delta = 5,
  min.gene.norm = 0,
  anno = FALSE,
  anno.coord.intron = NULL,
  label.size = 2
)
```

### Arguments

|               |                                                                                                                                                                                                                        |
|---------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| MarvelObject  | Marvel object. S3 object generated from CompareValues.Genes.10x function.                                                                                                                                              |
| pval          | Numeric value. p-value, below which, the splice junction is considered differentially spliced. To be used in conjunction with log2fc, delta, and min.gene.norm. Default is 0.05.                                       |
| log2fc        | Numeric value. Absolute log2 fold change, above which, the splice junction is considered differentially spliced. This option should be NULL if delta has been specified.                                               |
| delta         | Numeric value. Absolute differences in average PSI values between the two cell groups, above which, the splice junction is considered differentially spliced. This option should be NULL if log2fc has been specified. |
| min.gene.norm | Numeric value. The average normalised gene expression across the two cell groups above which the splice junction is considered differentially spliced. Default is 0.                                                   |
| anno          | Logical value. If set to TRUE, user-specific spliced genes in anno.coord.intron will be annotated on the plot. Default is FALSE.                                                                                       |

`anno.coord.intron` Vector of character strings. If `anno` set to TRUE, splice junction coordinates specified here will be annotated on the plot.

`label.size` Numeric value. If `anno` set to TRUE, the font size of the annotations on the plot will be adjusted to the size specified here. Default is 2.

**Value**

An object of class S3 with a new slots `MarvelObject$DE$SJ$VolcanoPlot$SJ$Plot` and `MarvelObject$DE$SJ$VolcanoPlot`

**Examples**

```
marvel.demo.10x <- readRDS(system.file("extdata/data",
                                     "marvel.demo.10x.rds",
                                     package="MARVEL"))

marvel.demo.10x <- PlotDEValues.SJ.10x(
  MarvelObject=marvel.demo.10x,
  pval=0.05,
  delta=5,
  min.gene.norm=1.0,
  anno=FALSE
)

# Check outputs
marvel.demo.10x$DE$SJ$VolcanoPlot$SJ$Plot
head(marvel.demo.10x$DE$SJ$VolcanoPlot$SJ$Data)
```

---

PlotPctExprCells.Genes.10x

*Plot gene expression distribution*

---

**Description**

Generates a plot of gene expression distribution (percentage of cells expressing a particular gene) to determine normalised gene expression threshold for downstream differential splice junction analysis.

**Usage**

```
PlotPctExprCells.Genes.10x(
  MarvelObject,
  cell.group.g1,
  cell.group.g2,
  min.pct.cells = 1
)
```

**Arguments**

|                            |                                                                                                                                                                                                                         |
|----------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>MarvelObject</code>  | Marvel object. S3 object generated from <code>CheckAlignment.10x</code> function.                                                                                                                                       |
| <code>cell.group.g1</code> | Vector of character strings. Cell IDs corresponding to Group 1 (reference group) of downstream differential splice junction analysis.                                                                                   |
| <code>cell.group.g2</code> | Vector of character strings. Cell IDs corresponding to Group 2 of downstream differential splice junction analysis.                                                                                                     |
| <code>min.pct.cells</code> | Numeric value. Minimum percentage of cells in which the gene is expressed for that gene to be included for gene expression distribution analysis. Expressed genes defined as genes with non-zero normalised UMI counts. |

**Value**

An object of class S3 with a new slots `MarvelObject$pct.cells.expr$Gene$Plot` and `MarvelObject$pct.cells.expr$Gene$Data`.

**Examples**

```
marvel.demo.10x <- readRDS(system.file("extdata/data",
                                     "marvel.demo.10x.rds",
                                     package="MARVEL"))

# Define cell groups
# Retrieve sample metadata
sample.metadata <- marvel.demo.10x$sample.metadata

# Group 1 (reference)
index <- which(sample.metadata$cell.type=="iPSC")
cell.ids.1 <- sample.metadata[index, "cell.id"]
length(cell.ids.1)

# Group 2
index <- which(sample.metadata$cell.type=="Cardio day 10")
cell.ids.2 <- sample.metadata[index, "cell.id"]
length(cell.ids.2)

# Explore % of cells expressing genes
marvel.demo.10x <- PlotPctExprCells.Genes.10x(
  MarvelObject=marvel.demo.10x,
  cell.group.g1=cell.ids.1,
  cell.group.g2=cell.ids.2,
  min.pct.cells=5
)

# Check output
marvel.demo.10x $pct.cells.expr$Gene$Plot
head(marvel.demo.10x $pct.cells.expr$Gene$Data)
```

---

 PlotPctExprCells.SJ.10x

*Plot splice junction expression distribution*


---

### Description

Generates a plot of splice junction expression distribution (percentage of cells expressing a particular splice junction) to determine splice junction expression threshold for downstream differential splice junction analysis.

### Usage

```
PlotPctExprCells.SJ.10x(
  MarvelObject,
  cell.group.g1,
  cell.group.g2,
  min.pct.cells.genes = 10,
  min.pct.cells.sj = 10,
  downsample = FALSE,
  downsample.pct.sj = 10,
  seed = 1
)
```

### Arguments

|                     |                                                                                                                                                                                                                                                                                                            |
|---------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| MarvelObject        | Marvel object. S3 object generated from CheckAlignment.10x function.                                                                                                                                                                                                                                       |
| cell.group.g1       | Vector of character strings. Cell IDs corresponding to Group 1 (reference group) of downstream differential splice junction analysis.                                                                                                                                                                      |
| cell.group.g2       | Vector of character strings. Cell IDs corresponding to Group 2 of downstream differential splice junction analysis.                                                                                                                                                                                        |
| min.pct.cells.genes | Numeric value. Minimum percentage of cells in which the gene is expressed for that gene to be included for splice junction expression distribution analysis. Expressed genes defined as genes with non-zero normalised UMI counts. This threshold may be determined from PlotPctExprCells.SJ.10x function. |
| min.pct.cells.sj    | Numeric value. Minimum percentage of cells in which the splice junction is expressed for that splice junction to be included for splice junction expression distribution analysis. Expressed splice junctions defined as splice junctions with raw UMI counts $\geq 1$ .                                   |
| downsample          | Logical value. If set to TRUE, the splice junctions will be downsampled so that only a smaller number of splice junctions will be included for expression exploration analysis here. Default value is FALSE.                                                                                               |
| downsample.pct.sj   | Numeric value. If downsample set to TRUE, the minimum percentage of splice junctions to include for expression exploration analysis here.                                                                                                                                                                  |

seed                    Numeric value. To ensure the splice junctions downsampled will always be reproducible.

### Value

An object of class S3 with a new slots `MarvelObject$pct.cells.expr$SJ$Plot` and `MarvelObject$pct.cells.expr$SJ$Data`.

### Examples

```
marvel.demo.10x <- readRDS(system.file("extdata/data",
                                     "marvel.demo.10x.rds",
                                     package="MARVEL")
                          )

# Define cell groups
# Retrieve sample metadata
sample.metadata <- marvel.demo.10x$sample.metadata

# Group 1 (reference)
index <- which(sample.metadata$cell.type=="iPSC")
cell.ids.1 <- sample.metadata[index, "cell.id"]
length(cell.ids.1)

# Group 2
index <- which(sample.metadata$cell.type=="Cardio day 10")
cell.ids.2 <- sample.metadata[index, "cell.id"]
length(cell.ids.2)

# Explore % of cells expressing SJ
marvel.demo.10x <- PlotPctExprCells.SJ.10x(
  MarvelObject=marvel.demo.10x,
  cell.group.g1=cell.ids.1,
  cell.group.g2=cell.ids.2,
  min.pct.cells.genes=5,
  min.pct.cells.sj=5,
  downsample=TRUE,
  downsample.pct.sj=100
)

marvel.demo.10x$pct.cells.expr$SJ$Plot
head(marvel.demo.10x$pct.cells.expr$SJ$Data)
```

---

PlotValues

*Plot percent spliced-in (PSI) or gene expression values*

---

### Description

Plots percent spliced-in (PSI) or gene expression values across different groups of cells. This is a wrapper function for `PlotValues.Exp` and `PlotValues.PSI`.



**Usage**

```

PlotValues(
  MarvelObject,
  cell.group.list,
  feature,
  maintitle = "gene_short_name",
  xlabel.size = 8,
  level,
  min.cells = NULL,
  sigma.sq = 0.001,
  bimodal.adjust = NULL,
  seed = NULL,
  modality.column = "modality.bimodal.adj",
  scale.y.log = FALSE,
  max.cells.jitter = 10000,
  max.cells.jitter.seed = 1,
  cell.group.colors = NULL,
  point.alpha = 0.2
)

```

**Arguments**

|                 |                                                                                                                                                                                                                                                                                                                             |
|-----------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| MarvelObject    | Marvel object. S3 object generated from TransformExpValues function.                                                                                                                                                                                                                                                        |
| cell.group.list | List of character strings. Each element of the list is a vector of cell IDs corresponding to a cell group. The name of the element will be the cell group label.                                                                                                                                                            |
| feature         | Character string. tran_id or gene_id for plotting. Should match tran_id or gene_id column of MarvelObject\$ValidatedSpliceFeature or MarvelObject\$GeneFeature slot when level set to "splicing" or "gene", respectively.                                                                                                   |
| maintitle       | Character string. Column to use as plot main title as per MarvelObject\$ValidatedSpliceFeature or MarvelObject\$GeneFeature when level set to "splicing" or "gene", respectively. Default is "gene_short_name" column.                                                                                                      |
| xlabel.size     | Numeric value. Size of x-axis labels as per ggplot2 function. Default is 8.                                                                                                                                                                                                                                                 |
| level           | Character string. Indicate "splicing" or "gene" for PSI or gene expression value plotting, respectively.                                                                                                                                                                                                                    |
| min.cells       | Numeric value. Only applicable when level set to "splicing". The minimum no. of cells expressing the splicing event to be included for analysis.                                                                                                                                                                            |
| sigma.sq        | Numeric value. Only applicable when level set to "splicing". The variance threshold below which the included/excluded modality will be defined as primary sub-modality, and above which it will be defined as dispersed sub-modality. Please refer to AssignModality function help page for more details. Default is 0.001. |
| bimodal.adjust  | Logical. Only applicable when level set to "splicing". When set to TRUE, MARVEL will identify false bimodal modalities and reassign them as included/excluded modality. Please refer to AssignModality function help page for more details.                                                                                 |

|                       |                                                                                                                                                                                                                                                                                                                                                                                                                         |
|-----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| seed                  | Numeric value. Only applicable when level set to "splicing". Ensure the fitdist function returns the same values for alpha and beta parameters each time this function is executed using the same random number generator. Please refer to AssignModality function help page for more details.                                                                                                                          |
| modality.column       | Character string. Only applicable when level set to "splicing". Can take the value "modality", "modality.var" or "modality.bimodal.adj". Please refer to AssignModality function help page for more details. Default is "modality.bimodal.adj".                                                                                                                                                                         |
| scale.y.log           | Logical value. Only applicable when level set to "splicing". If set to TRUE, the y-axis will be log10-scaled. Useful when most PSI values are extremely small (< 0.02) or big (> 0.98). Default is FALSE.                                                                                                                                                                                                               |
| max.cells.jitter      | Numeric value. Only applicable when level set to "splicing". Maximum number of cells for jitter points. Cells are randomly downsampled to show on jitter plot. Useful when there are large number of cells so that individual jitter points do not overcrowd the violin plot. Specified together with max.cells.jitter.seed. To disable this option, specify a value large than the number of cells in each cell group. |
| max.cells.jitter.seed | Numeric value. Only applicable when level set to "splicing". Cells downsampled are reproducible. Specified together with max.cells.jitter.                                                                                                                                                                                                                                                                              |
| cell.group.colors     | Character string. Vector of colors for the cell groups specified for PCA analysis using cell.type.columns, cell.type.variable, and cell.type.labels. If not specified, default ggplot2 colors will be used.                                                                                                                                                                                                             |
| point.alpha           | Numeric value. Transparency of the data points. Takes any values between 0-1. Default value is 0.2.                                                                                                                                                                                                                                                                                                                     |

### Value

An object of class S3 with new slot \$adhocPlot\$PSI or MarvelObject\$adhocPlot\$Exp when level set to "splicing" or "gene", respectively.

### Examples

```
marvel.demo <- readRDS(system.file("extdata/data", "marvel.demo.rds", package="MARVEL"))

# Define cell groups to plot
df.pheno <- marvel.demo$splicePheno
cell.group.g1 <- df.pheno[which(df.pheno$cell.type=="iPSC"), "sample.id"]
cell.group.g2 <- df.pheno[which(df.pheno$cell.type=="Endoderm"), "sample.id"]
cell.group.list <- list(cell.group.g1, cell.group.g2)
names(cell.group.list) <- c("iPSC", "Endoderm")

# Plot
marvel.demo <- PlotValues(MarvelObject=marvel.demo,
                          cell.group.list=cell.group.list,
                          feature="chr17:8383254:8382781|8383157:~@chr17:8382143:8382315",
                          level="splicing",
```

```

        min.cells=5,
        xlabel.size=5
    )

# Check output
marvel.demo$adhocPlot$PSI

```

---

PlotValues.Exp      *Plot gene expression values*

---

### Description

Boxplot of gene expression values across different groups of cells.

### Usage

```

PlotValues.Exp(
  MarvelObject,
  cell.group.list,
  feature,
  maintitle = "gene_short_name",
  xlabel.size = 8,
  cell.group.colors = NULL,
  point.alpha = 0.2
)

```

### Arguments

|                   |                                                                                                                                                                                                             |
|-------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| MarvelObject      | Marvel object. S3 object generated from TransformExpValues function.                                                                                                                                        |
| cell.group.list   | List of character strings. Each element of the list is a vector of cell IDs corresponding to a cell group. The name of the element will be the cell group label.                                            |
| feature           | Character string. gene_id for plotting. Should match gene_id column of MarvelObject\$GeneFeature slot.                                                                                                      |
| maintitle         | Character string. Column to use as plot main title as per MarvelObject\$GeneFeature. Default is "gene_short_name" column.                                                                                   |
| xlabel.size       | Numeric value. Size of x-axis labels as per ggplot2 function. Default is 8.                                                                                                                                 |
| cell.group.colors | Character string. Vector of colors for the cell groups specified for PCA analysis using cell.type.columns, cell.type.variable, and cell.type.labels. If not specified, default ggplot2 colors will be used. |
| point.alpha       | Numeric value. Transparency of the data points. Takes any values between 0-1. Default value is 0.2.                                                                                                         |

### Value

An object of class S3 with new slot MarvelObject\$adhocPlot\$Exp.

**Examples**

```
marvel.demo <- readRDS(system.file("extdata/data", "marvel.demo.rds", package="MARVEL"))

df.pheno <- marvel.demo$splicePheno
cell.group.g1 <- df.pheno[which(df.pheno$cell.type=="iPSC"), "sample.id"]
cell.group.g2 <- df.pheno[which(df.pheno$cell.type=="Endoderm"), "sample.id"]
cell.group.list <- list(cell.group.g1, cell.group.g2)
names(cell.group.list) <- c("iPSC", "Endoderm")

# Plot
marvel.demo <- PlotValues.Exp(MarvelObject=marvel.demo,
                             cell.group.list=cell.group.list,
                             feature="ENSG00000161970.15",
                             xlabel.size=8
                             )

# Check output
marvel.demo$adhocPlot$Exp
```

---

PlotValues.PCA.CellGroup.10x

*Annotate reduced dimension space with cell feature*

---

**Description**

Annotates reduced dimension space, e.g., UMAP and tSNE, with cell features such as cell group, donor ID, sample ID, etc.

**Usage**

```
PlotValues.PCA.CellGroup.10x(
  MarvelObject,
  cell.group.list,
  legendtitle = "Cell group",
  alpha = 0.75,
  point.size = 1,
  point.stroke = 0.1,
  point.colors = NULL,
  point.size.legend = 2,
  type
)
```

**Arguments**

**MarvelObject**    Marvel object. S3 object generated from `CheckAlignment.10x` function.

**cell.group.list**    List of character strings. Each element of the list is a vector of cell IDs corresponding to a feature, e.g. cell group. The names of the element will be the cell feature label.

|                   |                                                                                                                                                 |
|-------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|
| legendtitle       | Character string. Legend title. Default is "Cell group".                                                                                        |
| alpha             | Numeric value. Transparency of the data points. Takes any values between 0-1 whereby 0 is totally transparent and 1 is opaque. Default is 0.75. |
| point.size        | Numeric value. Size of data points. Default is 1.                                                                                               |
| point.stroke      | Numeric value. Outline thickness of data points. Default is 0.1.                                                                                |
| point.colors      | Vector of character strings. Colors of cell groups and should be same length as cell.group.list. Default ggplot2 colors are used.               |
| point.size.legend | Numeric value. Size of legend keys. Default is 2.                                                                                               |
| type              | Character string. Type of reduced dimension space. Options are "umap" and "tsne".                                                               |

**Value**

An object of class S3 with new slot `MarvelObject$adhocPlot$PCA$CellGroup`.

**Examples**

```
marvel.demo.10x <- readRDS(system.file("extdata/data",
                                     "marvel.demo.10x.rds",
                                     package="MARVEL"))
)

# Define cell groups
# Retrieve sample metadata
sample.metadata <- marvel.demo.10x$sample.metadata

# iPSC
index <- which(sample.metadata$cell.type=="iPSC")
cell.ids.1 <- sample.metadata[index, "cell.id"]
length(cell.ids.1)

# Cardio day 10
index <- which(sample.metadata$cell.type=="Cardio day 10")
cell.ids.2 <- sample.metadata[index, "cell.id"]
length(cell.ids.2)

# Save into list
cell.group.list <- list("iPSC"=cell.ids.1,
                       "Cardio d10"=cell.ids.2
)

# Plot cell groups
marvel.demo.10x <- PlotValues.PCA.CellGroup.10x(
  MarvelObject=marvel.demo.10x,
  cell.group.list=cell.group.list,
  legendtitle="Cell group",
  type="tsne"
)
```

```
# Check output
marvel.demo.10x$adhocPlot$PCA$CellGroup
```

---

```
PlotValues.PCA.Gene.10x
```

*Annotate reduced dimension space with gene expression values*

---

### Description

Annotates reduced dimension space, e.g., UMAP and tSNE, with gene expression values. Values will be automatically be log2-transformed prior to plotting.

### Usage

```
PlotValues.PCA.Gene.10x(
  MarvelObject,
  cell.ids = NULL,
  gene_short_name,
  log2.transform = TRUE,
  point.size = 0.1,
  color.gradient = c("grey90", "blue", "red"),
  type
)
```

### Arguments

|                 |                                                                                                                                              |
|-----------------|----------------------------------------------------------------------------------------------------------------------------------------------|
| MarvelObject    | Marvel object. S3 object generated from <code>CheckAlignment.10x</code> function.                                                            |
| cell.ids        | Vector of character strings. Specify specific cells to plot.                                                                                 |
| gene_short_name | Character string. Gene name whose expression will be plotting.                                                                               |
| log2.transform  | Logical value. If set to TRUE (default), normalised gene expression values will be off-set by 1 and then log2-transformed prior to analysis. |
| point.size      | Numeric value. Size of data points. Default is 1.                                                                                            |
| color.gradient  | Vector of character strings. Colors to indicate low, moderate, and high expression. Default is <code>c("grey90", "blue", "red")</code> .     |
| type            | Character string. Type of reduced dimension space. Options are "umap" and "tsne".                                                            |

### Value

An object of class S3 with new slot `MarvelObject$adhocPlot$PCA$Gene`.

**Examples**

```

marvel.demo.10x <- readRDS(system.file("extdata/data",
                                     "marvel.demo.10x.rds",
                                     package="MARVEL")
                          )

# Define cell groups
# Retrieve sample metadata
sample.metadata <- marvel.demo.10x$sample.metadata

# iPSC
index <- which(sample.metadata$cell.type=="iPSC")
cell.ids.1 <- sample.metadata[index, "cell.id"]
length(cell.ids.1)

# Cardio day 10
index <- which(sample.metadata$cell.type=="Cardio day 10")
cell.ids.2 <- sample.metadata[index, "cell.id"]
length(cell.ids.2)

# Save into list
cell.group.list <- list("iPSC"=cell.ids.1,
                       "Cardio d10"=cell.ids.2
                       )

# Plot expression
marvel.demo.10x <- PlotValues.PCA.Gene.10x(
  MarvelObject=marvel.demo.10x,
  gene_short_name="TPM2",
  color.gradient=c("grey", "cyan", "green", "yellow", "red"),
  type="tsne"
)

# Check output
marvel.demo.10x$adhocPlot$PCA$Gene

```

---

PlotValues.PCA.PSI.10x

*Annotate reduced dimension space with PSI values*


---

**Description**

Annotates reduced dimension space, e.g., UMAP and tSNE, with PSI values.

**Usage**

```

PlotValues.PCA.PSI.10x(
  MarvelObject,

```

```

cell.ids = NULL,
coord.intron,
min.gene.count = 3,
point.size = 0.1,
log2.transform = FALSE,
color.gradient = c("grey90", "blue", "red"),
type
)

```

### Arguments

|                |                                                                                                                                                                |
|----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| MarvelObject   | Marvel object. S3 object generated from CheckAlignment.10x function.                                                                                           |
| cell.ids       | Vector of character strings. Specific set of cells to plot.                                                                                                    |
| coord.intron   | Character string. Coordinates of splice junction whose expression will be plotted.                                                                             |
| min.gene.count | Numeric value. Minimum raw gene count, above which, the PSI value will be calculate for the cell. Default is 3.                                                |
| point.size     | Numeric value. Size of data points. Default is 1.                                                                                                              |
| log2.transform | Logical value. If set to TRUE, PSI values will be log2-transformed. Useful for highlighting small changes in PSI values between cell groups. Default is FALSE. |
| color.gradient | Vector of character strings. Colors to indicate low, moderate, and high expression. Default is c("grey90", "blue", "red").                                     |
| type           | Character string. Type of reduced dimension space. Options are "umap" and "tsne".                                                                              |

### Value

An object of class S3 with new slot `MarvelObject$adhocPlot$PCA$PSI`.

### Examples

```

marvel.demo.10x <- readRDS(system.file("extdata/data",
                                     "marvel.demo.10x.rds",
                                     package="MARVEL")
)

# Define cell groups
# Retrieve sample metadata
sample.metadata <- marvel.demo.10x$sample.metadata

# iPSC
index <- which(sample.metadata$cell.type=="iPSC")
cell.ids.1 <- sample.metadata[index, "cell.id"]
length(cell.ids.1)

# Cardio day 10
index <- which(sample.metadata$cell.type=="Cardio day 10")
cell.ids.2 <- sample.metadata[index, "cell.id"]

```



```

length(cell.ids.2)

# Save into list
cell.group.list <- list("iPSC"=cell.ids.1,
                       "Cardio d10"=cell.ids.2
                       )

# Plot expression
marvel.demo.10x <- PlotValues.PCA.PSI.10x(
  MarvelObject=marvel.demo.10x,
  coord.intron="chr1:23693914:23694659",
  min.gene.count=3,
  log2.transform=FALSE,
  color.gradient=c("grey", "cyan", "green", "yellow", "red"),
  type="tsne"
)

# Check output
marvel.demo.10x$adhocPlot$PCA$PSI

```

---

PlotValues.PSI

*Plot percent spliced-in (PSI) values*


---

## Description

Violin plot of percent spliced-in (PSI) values across different groups of cells.

## Usage

```

PlotValues.PSI(
  MarvelObject,
  cell.group.list,
  feature,
  maintitle = "gene_short_name",
  xlabel.size = 8,
  max.cells.jitter = 10000,
  max.cells.jitter.seed = 1,
  min.cells = 25,
  sigma.sq = 0.001,
  bimodal.adjust = TRUE,
  seed = 1,
  modality.column = "modality.bimodal.adj",
  scale.y.log = FALSE,
  cell.group.colors = NULL,
  point.alpha = 0.2
)

```

**Arguments**

|                                    |                                                                                                                                                                                                                                                                                            |
|------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>MarvelObject</code>          | Marvel object. S3 object generated from <code>TransformExpValues</code> function.                                                                                                                                                                                                          |
| <code>cell.group.list</code>       | List of character strings. Each element of the list is a vector of cell IDs corresponding to a cell group. The name of the element will be the cell group label.                                                                                                                           |
| <code>feature</code>               | Character string. Coordinates of splicing event to plot.                                                                                                                                                                                                                                   |
| <code>maintitle</code>             | Character string. Column to use as plot main title as per <code>MarvelObject\$ValidatedSpliceFeature</code> . Default is "gene_short_name" column.                                                                                                                                         |
| <code>xlabels.size</code>          | Numeric value. Size of x-axis labels as per <code>ggplot2</code> function. Default is 8.                                                                                                                                                                                                   |
| <code>max.cells.jitter</code>      | Numeric value. Maximum number of cells for jitter points. Cells are randomly downsampled to show on jitter plot. Useful when there are large number of cells so that individual jitter points do not overcrowd the violin plot.                                                            |
| <code>max.cells.jitter.seed</code> | Numeric value. Cells downsampled are reproducible.                                                                                                                                                                                                                                         |
| <code>min.cells</code>             | Numeric value. The minimum no. of cells expressing the splicing event to be included for analysis. Please refer to <code>AssignModality</code> function help page for more details.                                                                                                        |
| <code>sigma.sq</code>              | Numeric value. The variance threshold below which the included/excluded modality will be defined as primary sub-modality, and above which it will be defined as dispersed sub-modality. Please refer to <code>AssignModality</code> function help page for more details. Default is 0.001. |
| <code>bimodal.adjust</code>        | Logical. When set to TRUE, MARVEL will identify false bimodal modalities and reassign them as included/excluded modality. Please refer to <code>AssignModality</code> function help page for more details.                                                                                 |
| <code>seed</code>                  | Numeric value. Ensure the <code>fitdist</code> function returns the same values for alpha and beta parameters each time this function is executed using the same random number generator. Please refer to <code>AssignModality</code> function help page for more details.                 |
| <code>modality.column</code>       | Character string. Can take the value "modality", "modality.var" or "modality.bimodal.adj". Please refer to <code>AssignModality</code> function help page for more details. Default is "modality.bimodal.adj".                                                                             |
| <code>scale.y.log</code>           | Logical value. Only applicable when level set to "splicing". If set to TRUE, the y-axis will be log10-scaled. Useful when most PSI values are extremely small (< 0.02) or big (> 0.98). Default is FALSE.                                                                                  |
| <code>cell.group.colors</code>     | Character string. Vector of colors for the cell groups specified for PCA analysis using <code>cell.type.columns</code> , <code>cell.type.variable</code> , and <code>cell.type.labels</code> . If not specified, default <code>ggplot2</code> colors will be used.                         |
| <code>point.alpha</code>           | Numeric value. Transparency of the data points. Takes any values between 0-1. Default value is 0.2.                                                                                                                                                                                        |

**Value**

An object of class S3 with new slot `MarvelObject$adhocPlot$PSI`.

**Examples**

```

marvel.demo <- readRDS(system.file("extdata/data", "marvel.demo.rds", package="MARVEL"))

# Define cell groups to plot
df.pheno <- marvel.demo$splicePheno
cell.group.g1 <- df.pheno[which(df.pheno$cell.type=="iPSC"), "sample.id"]
cell.group.g2 <- df.pheno[which(df.pheno$cell.type=="Endoderm"), "sample.id"]
cell.group.list <- list(cell.group.g1, cell.group.g2)
names(cell.group.list) <- c("iPSC", "Endoderm")

# Plot
marvel.demo <- PlotValues.PSI(MarvelObject=marvel.demo,
                             cell.group.list=cell.group.list,
                             feature="chr17:8383254:8382781|8383157:-@chr17:8382143:8382315",
                             min.cells=5,
                             xlabel.size=5
                             )

# Check output
marvel.demo$adhocPlot$PSI

```

---

PropModality

*Tabulate modality proportion*


---

**Description**

Tabulates and plots the proportion of each modality. This is a wrapper function for PropModality.Doughnut and PropModality.Bar functions.

**Usage**

```

PropModality(
  MarvelObject,
  modality.column,
  modality.type,
  event.type,
  across.event.type,
  prop.test = NULL,
  prop.adj = NULL,
  xlabel.size = 8,
  zoom = FALSE,
  yinterval = NULL
)

```

**Arguments**

**MarvelObject**    Marvel object. S3 object generated from AssignModality function.

|                                |                                                                                                                                                                                                                                                                                                                                      |
|--------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>modality.column</code>   | Character string. Can take the value "modality", "modality.var" or "modality.bimodal.adj". Please refer to AssignModality function help page for more details.                                                                                                                                                                       |
| <code>modality.type</code>     | Character string. basic indicates that only the main modalities (included, excluded, bimodal, middle, multimodal) are analysed. Sub-modalities (primary and dispersed) will be merged. complete indicates that both main and sub-modalities are analysed. Sub-modalities will not be merged.                                         |
| <code>event.type</code>        | Character string. To indicate which event type to analyse. Can take the value "SE", "MXE", "RI", "A5SS" or "A3SS". Specify "all" to include all event types.                                                                                                                                                                         |
| <code>across.event.type</code> | Logical. If set to TRUE, the proportion of modality will be compared across the specified event types                                                                                                                                                                                                                                |
| <code>prop.test</code>         | Character string. Only applicable when <code>across.event.type</code> set to TRUE. <code>chisq</code> Chi-squared test used to compare the proportion of modalities across the different event splicing type. <code>fisher</code> Fisher test used to compare the proportion of modalities across the different splicing event type. |
| <code>prop.adj</code>          | Character string. Only applicable when <code>across.event.type</code> set to TRUE. Adjust p-values generated from <code>prop.test</code> for multiple testing. Options available as per <code>p.adjust</code> function.                                                                                                              |
| <code>xlabels.size</code>      | Numeric value. Only applicable when <code>across.event.type</code> set to TRUE. Size of x-axis labels as per <code>ggplot2</code> function. Default is 8.                                                                                                                                                                            |
| <code>zoom</code>              | Logical value. Only applicable if <code>across.event.type</code> set to TRUE. If set to TRUE, users can specify the range of the y-axis using <code>yinterval</code> argument. Useful when scrutinising low-frequency event types, e.g. middle and multimodal.                                                                       |
| <code>yinterval</code>         | Logical value. Only applicable if <code>across.event.type</code> set to TRUE and <code>zoom</code> set to TRUE.                                                                                                                                                                                                                      |

### Value

An object of class S3 containing with new slot `$Modality$Prop$DoughnutChart` or `$Modality$Prop$BarChart`.

### Examples

```
marvel.demo <- readRDS(system.file("extdata/data", "marvel.demo.rds", package="MARVEL"))

marvel.demo <- PropModality(MarvelObject=marvel.demo,
  modality.column="modality.bimodal.adj",
  modality.type="extended",
  event.type=c("SE", "MXE", "RI", "A5SS", "A3SS", "AFE", "ALE"),
  across.event.type=FALSE
)

# Check outputs
marvel.demo$Modality$Prop$DoughnutChart$Table
marvel.demo$Modality$Prop$DoughnutChart$Plot
```

---

|                  |                                                      |
|------------------|------------------------------------------------------|
| PropModality.Bar | <i>Modality proportion broken down by event type</i> |
|------------------|------------------------------------------------------|

---

### Description

Tabulates and plots the proportion of each modality broken down by splicing event type.

### Usage

```
PropModality.Bar(
  MarvelObject,
  modality.column,
  modality.type,
  event.type,
  xlabel.size = 8,
  zoom = FALSE,
  yinterval = NULL,
  prop.test,
  prop.adj
)
```

### Arguments

|                 |                                                                                                                                                                                                                                                                                               |
|-----------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| MarvelObject    | Marvel object. S3 object generated from AssignModality function.                                                                                                                                                                                                                              |
| modality.column | Character string. Can take the value "modality", "modality.var" or "modality.bimodal.adj". Please refer to AssignModality function help page for more details.                                                                                                                                |
| modality.type   | Character string. basic indicates that only the main modalities (included, excluded, bimodal, middle, multimodal) are analysed. Sub-modalities (primary and dispersed) will be merged. extended indicates that both main and sub-modalities are analysed. Sub-modalities will not be merged.  |
| event.type      | Character string. To indicate which event type to analyse. Can take the value "SE", "MXE", "RI", "A5SS" or "A3SS". Specify "all" to include all event types.                                                                                                                                  |
| xlabel.size     | Numeric value. Size of x-axis labels as per ggplot2 function. Default is 8.                                                                                                                                                                                                                   |
| zoom            | Logical value. If set to TRUE, users can specify the range of the y-axis using yinterval argument. Useful when scrutinising low-frequency event types, e.g. middle and multimodal.                                                                                                            |
| yinterval       | Logical value. Only applicable when zoom is set to TRUE.                                                                                                                                                                                                                                      |
| prop.test       | Character string. Only applicable when across.event.type set to TRUE. chisq Chi-squared test used to compare the proportion of modalities across the different event splicing type. fisher Fisher test used to compare the proportion of modalities across the different splicing event type. |
| prop.adj        | Character string. Only applicable when across.event.type set to TRUE. Adjust p-values generated from prop.test for multiple testing. Options available as per p.adjust function.                                                                                                              |

**Value**

An object of class S3 containing new slots `MarvelObject$Modality$Prop$BarChart$Table` and `MarvelObject$Modality$Prop$BarChart$Stats`.

**Examples**

```
marvel.demo <- readRDS(system.file("extdata/data", "marvel.demo.rds", package="MARVEL"))

marvel.demo <- PropModality.Bar(MarvelObject=marvel.demo,
                               modality.column="modality.bimodal.adj",
                               modality.type="extended",
                               event.type=c("SE", "MXE", "RI", "A5SS", "A3SS", "AFE", "ALE"),
                               prop.test="fisher",
                               prop.adj="fdr"
                               )

# Check outputs
head(marvel.demo$Modality$Prop$BarChart$Table)
marvel.demo$Modality$Prop$BarChart$Plot
marvel.demo$Modality$Prop$BarChart$Stats
```

---

PropModality.Doughnut *Overall modality proportion*

---

**Description**

Tabulates and plots the proportion of each modality without breaking down by splicing event type.

**Usage**

```
PropModality.Doughnut(MarvelObject, modality.column, modality.type, event.type)
```

**Arguments**

|                              |                                                                                                                                                                                                                                                                                                                        |
|------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>MarvelObject</code>    | Marvel object. S3 object generated from <code>AssignModality</code> function.                                                                                                                                                                                                                                          |
| <code>modality.column</code> | Character string. Can take the value <code>"modality"</code> , <code>"modality.var"</code> or <code>"modality.bimodal.adj"</code> . Please refer to <code>AssignModality</code> function help page for more details.                                                                                                   |
| <code>modality.type</code>   | Character string. <code>basic</code> indicates that only the main modalities (included, excluded, bimodal, middle, multimodal) are analysed. Sub-modalities (primary and dispersed) will be merged. <code>complete</code> indicates that both main and sub-modalities are analysed. Sub-modalities will not be merged. |
| <code>event.type</code>      | Character string. To indicate which event type to analyse. Can take the value <code>"SE"</code> , <code>"MXE"</code> , <code>"RI"</code> , <code>"A5SS"</code> or <code>"A3SS"</code> . Specify <code>"all"</code> to include all event types.                                                                         |

**Value**

An object of class S3 with new slots `MarvelObject$Modality$Prop$DoughnutChart$Table` and `MarvelObject$Modality$Prop$DoughnutChart$Plot`.

**Examples**

```
marvel.demo <- readRDS(system.file("extdata/data", "marvel.demo.rds", package="MARVEL"))

marvel.demo <- PropModality.Doughnut(MarvelObject=marvel.demo,
                                     modality.column="modality.bimodal.adj",
                                     modality.type="extended",
                                     event.type=c("SE", "MXE", "RI", "A5SS", "A3SS", "AFE", "ALE")
                                     )

# Check outputs
marvel.demo$Modality$Prop$DoughnutChart$Table
marvel.demo$Modality$Prop$DoughnutChart$Plot
```

---

 PropPTC

*Tabulate proportion of transcripts with PTC*


---

**Description**

Tabulates and plots the proportion of transcripts with PTC for each splicing event type.

**Usage**

```
PropPTC(MarvelObject, xlabel.size = 8, show.NovelSJ.NoCDS = TRUE, prop.test)
```

**Arguments**

|                    |                                                                                                                                                                                                                                                                                         |
|--------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| MarvelObject       | Marvel object. S3 object generated from FindPTC function.                                                                                                                                                                                                                               |
| xlabel.size        | Numeric value. Size of the x-axis tick labels. Default is 8.                                                                                                                                                                                                                            |
| show.NovelSJ.NoCDS | Logical value. If set to TRUE transcripts not analysed for premature terminal codon (PTC), e.g. non-protein-coding transcripts are tabulated and plotted.                                                                                                                               |
| prop.test          | Character string. <code>chisq</code> Chi-squared test used to compare the proportion of transcripts with PTC across the different event splicing type. <code>fisher</code> Fisher test used to compare the proportion of transcripts with PTC across the different splicing event type. |

**Value**

An object of class S3 with new slots `MarvelObject$NMD$PTC.Prop$Table`, `MarvelObject$NMD$PTC.Prop$Plot`, and `MarvelObject$NMD$PTC.Prop$Plot.Stats`.

**Examples**

```
marvel.demo <- readRDS(system.file("extdata/data", "marvel.demo.rds", package="MARVEL"))

marvel.demo <- PropPTC(MarvelObject=marvel.demo,
                       xlabel.size=8,
                       show.NovelSJ.NoCDS=TRUE,
```

```

        prop.test="fisher"
    )

# Check outputs
head(marvel.demo$NMD$PTC.Prop$Table)
marvel.demo$NMD$PTC.Prop$Plot
marvel.demo$NMD$PTC.Prop$Plot.Stats

```

---

RunPCA

*Principle component analysis*


---

### Description

Performs principle component analysis on splicing or gene data. This is a wrapper function for RunPCA.PSI and RunPCA.Exp.

### Usage

```

RunPCA(
  MarvelObject,
  cell.group.column,
  cell.group.order = NULL,
  cell.group.colors = NULL,
  sample.ids = NULL,
  min.cells = 25,
  features,
  point.size = 0.5,
  point.alpha = 0.75,
  point.stroke = 0.1,
  seed = 1,
  method.impute = "random",
  cell.group.column.impute = NULL,
  level
)

```

### Arguments

**MarvelObject**    Marvel object. S3 object generated from TransformExpValues function.

**cell.group.column**  
                   Character string. The name of the sample metadata column in which the variables will be used to label the cell groups on the PCA.

**cell.group.order**  
                   Character string. The order of the variables under the sample metadata column specified in `cell.group.column` to appear in the PCA cell group legend.

**cell.group.colors**  
                   Character string. Vector of colors for the cell groups specified for PCA analysis using `cell.type.columns` and `cell.group.order`. If not specified, default ggplot2 colors will be used.



|                                       |                                                                                                                                                                                                                                                                                                              |
|---------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>sample.ids</code>               | Character strings. Specific cells to plot.                                                                                                                                                                                                                                                                   |
| <code>min.cells</code>                | Numeric value. The minimum no. of cells expressing the splicing event or gene for the event or gene, respectively, to be included for analysis.                                                                                                                                                              |
| <code>features</code>                 | Character string. Vector of <code>tran_id</code> or <code>gene_id</code> for analysis. Should match <code>tran_id</code> or <code>gene_id</code> column of <code>MarvelObject\$ValidatedSpliceFeature</code> or <code>MarvelObject\$GeneFeature</code> when level set to "splicing" or "gene", respectively. |
| <code>point.size</code>               | Numeric value. Size of data points on reduced dimension space.                                                                                                                                                                                                                                               |
| <code>point.alpha</code>              | Numeric value. Transparency of the data points on reduced dimension space. Take any values between 0 to 1. The smaller the value, the more transparent the data points will be.                                                                                                                              |
| <code>point.stroke</code>             | Numeric value. The thickness of the outline of the data points. The larger the value, the thicker the outline of the data points.                                                                                                                                                                            |
| <code>seed</code>                     | Numeric value. Only applicable when level set to "splicing". Ensures imputed values for NA PSIs are reproducible.                                                                                                                                                                                            |
| <code>method.impute</code>            | Character string. Only applicable when level set to "splicing". Indicate the method for imputing missing PSI values (low coverage). "random" method randomly assigns any values between 0-1. "population.mean" method uses the mean PSI value for each cell population. Default option is "population.mean". |
| <code>cell.group.column.impute</code> | Character string. Only applicable when <code>method.impute</code> set to "population.mean". The name of the sample metadata column in which the variables will be used to impute missing values.                                                                                                             |
| <code>level</code>                    | Character string. Indicate "splicing" or "gene" for splicing or gene expression analysis, respectively                                                                                                                                                                                                       |

## Value

An object of class `S3` with new slots `MarvelObject$PCA$PSI$Results`, `MarvelObject$PCA$PSI$Plot`, and `MarvelObject$PCA$PSI$Plot.Elbow` or `MarvelObject$PCA$Exp$Results`, `MarvelObject$PCA$Exp$Plot`, and `MarvelObject$PCA$Exp$Plot.Elbow`, when level option specified as "splicing" or "gene", respectively.

## Examples

```
marvel.demo <- readRDS(system.file("extdata/data", "marvel.demo.rds", package="MARVEL"))

# Define splicing events for analysis
df <- do.call(rbind.data.frame, marvel.demo$PSI)
tran_ids <- df$tran_id

# PCA
marvel.demo <- RunPCA(MarvelObject=marvel.demo,
  sample.ids=marvel.demo$SplicePheno$sample.id,
  cell.group.column="cell.type",
  cell.group.order=c("iPSC", "Endoderm"),
  cell.group.colors=NULL,
```

```

        min.cells=5,
        features=tran_ids,
        level="splicing",
        point.size=2
    )

# Check outputs
head(marvel.demo$PCA$PSI$Results$ind$coord)
marvel.demo$PCA$PSI$Plot

```

---

RunPCA.Exp

*Principle component analysis for gene Data*


---

### Description

Performs principle component analysis using gene expression values.

### Usage

```

RunPCA.Exp(
  MarvelObject,
  sample.ids = NULL,
  cell.group.column,
  cell.group.order = NULL,
  cell.group.colors = NULL,
  features,
  min.cells = 25,
  point.size = 0.5,
  point.alpha = 0.75,
  point.stroke = 0.1
)

```

### Arguments

|                   |                                                                                                                                                                                        |
|-------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| MarvelObject      | Marvel object. S3 object generated from TransformExpValues function.                                                                                                                   |
| sample.ids        | Character strings. Specific cells to plot.                                                                                                                                             |
| cell.group.column | Character string. The name of the sample metadata column in which the variables will be used to label the cell groups on the PCA.                                                      |
| cell.group.order  | Character string. The order of the variables under the sample metadata column specified in cell.group.column to appear in the PCA cell group legend.                                   |
| cell.group.colors | Character string. Vector of colors for the cell groups specified for PCA analysis using cell.type.columns and cell.group.order. If not specified, default ggplot2 colors will be used. |

|              |                                                                                                                                                                                 |
|--------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| features     | Character string. Vector of gene_id for analysis. Should match gene_id column of MarvelObject\$GeneFeature.                                                                     |
| min.cells    | Numeric value. The minimum no. of cells expressing the gene to be included for analysis.                                                                                        |
| point.size   | Numeric value. Size of data points on reduced dimension space.                                                                                                                  |
| point.alpha  | Numeric value. Transparency of the data points on reduced dimension space. Take any values between 0 to 1. The smaller the value, the more transparent the data points will be. |
| point.stroke | Numeric value. The thickness of the outline of the data points. The larger the value, the thicker the outline of the data points.                                               |

### Value

An object of class S3 containing with new slots MarvelObject\$PCA\$Exp\$Results, MarvelObject\$PCA\$Exp\$Plot, and MarvelObject\$PCA\$Exp\$Plot.Elbow.

### Examples

```
marvel.demo <- readRDS(system.file("extdata/data", "marvel.demo.rds", package="MARVEL"))

# Define genes for analysis
gene_ids <- marvel.demo$Exp$gene_id

# PCA
marvel.demo <- RunPCA.Exp(MarvelObject=marvel.demo,
                          sample.ids=marvel.demo$SplicePheno$sample.id,
                          cell.group.column="cell.type",
                          cell.group.order=c("iPSC", "Endoderm"),
                          min.cells=5,
                          features=gene_ids,
                          point.size=2
                          )

# Check outputs
head(marvel.demo$PCA$Exp$Results$ind$coord)
marvel.demo$PCA$Exp$Plot
```

---

RunPCA.PSI

*Principle component analysis for splicing data*

---

### Description

Performs principle component analysis using PSI values.

**Usage**

```
RunPCA.PSI(
  MarvelObject,
  sample.ids = NULL,
  cell.group.column,
  cell.group.order,
  cell.group.colors = NULL,
  features,
  min.cells = 25,
  point.size = 0.5,
  point.alpha = 0.75,
  point.stroke = 0.1,
  seed = 1,
  method.impute = "random",
  cell.group.column.impute = NULL
)
```

**Arguments**

|                                |                                                                                                                                                                                                                                                                |
|--------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>MarvelObject</code>      | Marvel object. S3 object generated from <code>TransformExpValues</code> function.                                                                                                                                                                              |
| <code>sample.ids</code>        | Character strings. Specific cells to plot.                                                                                                                                                                                                                     |
| <code>cell.group.column</code> | Character string. The name of the sample metadata column in which the variables will be used to label the cell groups on the PCA.                                                                                                                              |
| <code>cell.group.order</code>  | Character string. The order of the variables under the sample metadata column specified in <code>cell.group.column</code> to appear in the PCA cell group legend.                                                                                              |
| <code>cell.group.colors</code> | Character string. Vector of colors for the cell groups specified for PCA analysis using <code>cell.type.columns</code> and <code>cell.group.order</code> . If not specified, default ggplot2 colors will be used.                                              |
| <code>features</code>          | Character string. Vector of <code>tran_id</code> for analysis. Should match <code>tran_id</code> column of <code>MarvelObject\$ValidatedSpliceFeature</code> .                                                                                                 |
| <code>min.cells</code>         | Numeric value. The minimum no. of cells expressing the splicing event to be included for analysis.                                                                                                                                                             |
| <code>point.size</code>        | Numeric value. Size of data points on reduced dimension space.                                                                                                                                                                                                 |
| <code>point.alpha</code>       | Numeric value. Transparency of the data points on reduced dimension space. Take any values between 0 to 1. The smaller the value, the more transparent the data points will be.                                                                                |
| <code>point.stroke</code>      | Numeric value. The thickness of the outline of the data points. The larger the value, the thicker the outline of the data points.                                                                                                                              |
| <code>seed</code>              | Numeric value. Ensures imputed values for NA PSIs are reproducible.                                                                                                                                                                                            |
| <code>method.impute</code>     | Character string. Indicate the method for imputing missing PSI values (low coverage). "random" method randomly assigns any values between 0-1. "population.mean" method uses the mean PSI value for each cell population. Default option is "population.mean". |

```
cell.group.column.impute
```

Character string. Only applicable when method.impute set to "population.mean".  
The name of the sample metadata column in which the variables will be used to impute missing values.

### Value

An object of class S3 containing with new slots `MarvelObject$PCA$PSI$Results` and `MarvelObject$PCA$PSI$Plot`

### Examples

```
marvel.demo <- readRDS(system.file("extdata/data", "marvel.demo.rds", package="MARVEL"))

# Define splicing events for analysis
df <- do.call(rbind.data.frame, marvel.demo$PSI)
tran_ids <- df$tran_id

# PCA
marvel.demo <- RunPCA.PSI(MarvelObject=marvel.demo,
                          sample.ids=marvel.demo$SplicePheno$sample.id,
                          cell.group.column="cell.type",
                          cell.group.order=c("iPSC", "Endoderm"),
                          cell.group.colors=NULL,
                          min.cells=5,
                          features=tran_ids,
                          point.size=2
                          )

# Check outputs
head(marvel.demo$PCA$PSI$Results$ind$coord)
marvel.demo$PCA$PSI$Plot
```

---

SubsetCrypticA3SS

*Differential gene expression analysis for differentially spliced genes*

---

### Description

Performs differential gene expression analysis between 2 groups of cells only on differentially spliced genes.

### Usage

```
SubsetCrypticA3SS(MarvelObject, method, distance.to.ss = c(1, 100))
```

### Arguments

|                             |                                                                                                                                                    |
|-----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>MarvelObject</code>   | Marvel object. S3 object generated from <code>TransformExpValues</code> function.                                                                  |
| <code>method</code>         | Vector of character string(s). To include splicing events from these method(s) for differential splicing analysis.                                 |
| <code>distance.to.ss</code> | Character string. Range of distances between A3SS and canonical splice site to consider A3SS to be cryptic. Default value <code>c(1, 100)</code> . |

**Value**

An object of class S3 updated slot `MarvelObject$DE$PSI$Table` and new slot `MarvelObject$DE$PSI$A3SS.dist.to.ss`.

**Examples**

```
marvel.demo <- readRDS(system.file("extdata/data", "marvel.demo.rds", package="MARVEL"))

marvel.demo <- SubsetCrypticA3SS(MarvelObject=marvel.demo,
                                method="ad",
                                distance.to.ss=c(1,100)
                                )

# Check output
head(marvel.demo$DE$PSI$Table[["ad"]])
```

---

|               |                               |
|---------------|-------------------------------|
| SubsetSamples | <i>Subset samples (cells)</i> |
|---------------|-------------------------------|

---

**Description**

Subsets specific samples (cells) from sample metadata.

**Usage**

```
SubsetSamples(MarvelObject, sample.ids)
```

**Arguments**

`MarvelObject`    Marvel object. S3 object generated from `CreateMarvelObject` function.  
`sample.ids`        Vector of character strings. Sample IDs to subset.

**Value**

An object of class S3 with updated slot `MarvelObject$SplicePheno`.

**Examples**

```
marvel.demo <- readRDS(system.file("extdata/data", "marvel.demo.rds", package="MARVEL"))

sample.ids <- sample(marvel.demo$SplicePheno$sample.id, size=10)

marvel.demo <- SubsetSamples(MarvelObject=marvel.demo,
                             sample.ids=sample.ids
                             )
```

---

TransformExpValues      *Transform gene expression Values*

---

### Description

Transforms gene expression values and censor lowly-expressing genes.

### Usage

```
TransformExpValues(  
  MarvelObject,  
  offset = 1,  
  transformation = "log2",  
  threshold.lower = 1  
)
```

### Arguments

**MarvelObject**      Marvel object. S3 object generated from CheckAlignment function.

**offset**            Numeric value. To indicate the value to add to the expression values before log transformation. The only option for this argument is 1.

**transformation**    Character string. To indicate the type of transformation to use on the expression values after offsetting the values. The only option for this argument is log2.

**threshold.lower**    Numeric value. To indicate the value below which the expression values will be censored, i.e. re-coded as 0, after offsetting and transforming the values. The only option for this argument is 1.

### Value

An object of class S3 with updated slot `MarvelObject$Exp`.

### Examples

```
marvel.demo <- readRDS(system.file("extdata/data", "marvel.demo.rds", package="MARVEL"))  
  
marvel.demo <- TransformExpValues(MarvelObject=marvel.demo,  
  offset=1,  
  transformation="log2",  
  threshold.lower=1  
)
```

---

ValidateSJ.10x      *Validate splice junctions*

---

**Description**

Retains splice junctions whose start and end belong to the same gene.

**Usage**

```
ValidateSJ.10x(MarvelObject, keep.novel.sj = FALSE)
```

**Arguments**

**MarvelObject**      Marvel object. S3 object generated from AnnotateSJ.10x function.

**keep.novel.sj**      Logical value. If set to TRUE, novel splice junctions will be retained for downstream analysis. Novel splice junctions are defined as splice junctions with one end reported in GTF while the other was not reported in GTF. Default value is FALSE.

**Value**

An object of class S3 containing the updated slots `MarvelObject$sj.metadata` and `MarvelObject$sj.count.matrix`.

**Examples**

```
# Load un-processed MARVEL object
marvel.demo.10x.raw <- readRDS(system.file("extdata/data",
                                         "marvel.demo.10x.raw.rds",
                                         package="MARVEL"))

# Annotate gene metadata
marvel.demo.10x <- AnnotateGenes.10x(MarvelObject=marvel.demo.10x.raw)

# Annotate junction metadata
marvel.demo.10x <- AnnotateSJ.10x(MarvelObject=marvel.demo.10x)

# Validate junctions
marvel.demo.10x <- ValidateSJ.10x(MarvelObject=marvel.demo.10x)
```



# Index

adhocGene.DE.Gene.10x, 4  
adhocGene.DE.PSI.10x, 4  
adhocGene.PlotDEValues.10x, 5  
adhocGene.PlotSJPosition.10x, 7  
adhocGene.TabulateExpression.Gene.10x, 8  
adhocGene.TabulateExpression.PSI.10x, 10  
AnnotateGenes.10x, 11  
AnnotateSJ.10x, 11  
AnnoVolcanoPlot, 12  
AssignModality, 13  
  
BioPathways, 14  
BioPathways.10x, 16  
BioPathways.Plot, 17  
BioPathways.Plot.10x, 18  
  
CheckAlignment, 19  
CheckAlignment.10x, 20  
CheckAlignment.Exp, 21  
CheckAlignment.PSI, 22  
CheckAlignment.PSI.Exp, 22  
CheckAlignment.SJ, 23  
CompareExpr, 23  
CompareValues, 24  
CompareValues.Exp, 27  
CompareValues.Exp.Spliced, 29  
CompareValues.Genes.10x, 31  
CompareValues.PSI, 32  
CompareValues.SJ.10x, 34  
ComputePSI, 36  
ComputePSI.A3SS, 38  
ComputePSI.A5SS, 38  
ComputePSI.AFE, 39  
ComputePSI.ALE, 40  
ComputePSI.MXE, 40  
ComputePSI.RI, 41  
ComputePSI.SE, 43  
CountEvents, 44  
  
CreateMarvelObject, 45  
CreateMarvelObject.10x, 46  
  
DetectEvents, 49  
DetectEvents.AFE, 50  
DetectEvents.AFE.NegStrand, 51  
DetectEvents.AFE.PosStrand, 52  
DetectEvents.ALE, 53  
DetectEvents.ALE.NegStrand, 54  
DetectEvents.ALE.PosStrand, 55  
  
FilterGenes.10x, 56  
FindPTC, 57  
FindPTC.A3SS.NegStrand, 58  
FindPTC.A3SS.PosStrand, 59  
FindPTC.A5SS.NegStrand, 60  
FindPTC.A5SS.PosStrand, 61  
FindPTC.RI.NegStrand, 62  
FindPTC.RI.PosStrand, 63  
FindPTC.SE.NegStrand, 64  
FindPTC.SE.PosStrand, 65  
  
IsoSwitch, 66  
IsoSwitch.10x, 67  
IsoSwitch.PlotExpr, 69  
  
ModalityChange, 70  
  
ParseGTF, 71  
PctASE, 71  
PlotDEValues, 73  
PlotDEValues.Exp.Global, 75  
PlotDEValues.Exp.Spliced, 76  
PlotDEValues.Genes.10x, 78  
PlotDEValues.PSI.Distance, 80  
PlotDEValues.PSI.Mean, 81  
PlotDEValues.PSI.Mean.g2vsg1, 82  
PlotDEValues.SJ.10x, 84  
PlotPctExprCells.Genes.10x, 85  
PlotPctExprCells.SJ.10x, 87  
PlotValues, 88

PlotValues.Exp, [91](#)  
PlotValues.PCA.CellGroup.10x, [92](#)  
PlotValues.PCA.Gene.10x, [94](#)  
PlotValues.PCA.PSI.10x, [95](#)  
PlotValues.PSI, [97](#)  
PropModality, [99](#)  
PropModality.Bar, [101](#)  
PropModality.Doughnut, [102](#)  
PropPTC, [103](#)

RunPCA, [104](#)  
RunPCA.Exp, [106](#)  
RunPCA.PSI, [107](#)

SubsetCrypticA3SS, [109](#)  
SubsetSamples, [110](#)

TransformExpValues, [111](#)

ValidateSJ.10x, [112](#)