

Package ‘calidad’

October 16, 2024

Type Package

Title Assesses the Quality of Estimates Made by Complex Sample Designs

Version 0.6.0

Description Assesses the quality of estimates made by complex sample designs, following the methodology developed by the National Institute of Statistics Chile (2020, <<https://www.ine.cl/docs/default-source/institucionalidad/buenas-pr%C3%A1cticas/clasificaciones-y-estándares/est%C3%A1ndar-evaluaci%C3%B3n-de-calidad-de-estimaciones-publicaci%C3%B3n-27022020.pdf>>) and by Economic Commission for Latin America and Caribbean (2024, chrome-extension://efaidnbmnnibpcajpcglclefindmkaj/<https://repositorio.cepal.org/server/api/core/bitstreams/f04569e6-4f38-42e7-a32b-e0b298e0ab9c/content>).

License GPL-3

Encoding UTF-8

LazyData true

RoxygenNote 7.3.2

Suggests knitr, rmarkdown, testthat

VignetteBuilder knitr

Depends R (>= 3.5.0)

Imports rlang, dplyr, purrr, survey, kableExtra, stringr, tidyverse, haven

NeedsCompilation no

Author Klaus Lehmann [aut, cre],
Ricardo Pizarro [aut],
Ignacio Agloni [ctb],
Andrea López [ctb],
Javiera Preuss [ctb]

Maintainer Klaus Lehmann <klehmann@fen.uchile.cl>

Repository CRAN

Date/Publication 2024-10-16 19:40:02 UTC

Contents

| | |
|------------------------------|----|
| assess | 2 |
| casen | 4 |
| create_html | 5 |
| create_mean | 5 |
| create_prop | 7 |
| create_prop_internal | 8 |
| create_ratio_internal | 9 |
| create_size | 10 |
| create_total | 12 |
| eclac_standard | 13 |
| ene | 14 |
| enusc | 15 |
| epf_personas | 16 |
| get_cv | 17 |
| get_df | 17 |
| get_survey_table | 18 |
| quadratic | 19 |
| standardize_columns | 19 |
| standardize_design_variables | 20 |

Index

21

| | |
|--------|---|
| assess | <i>Assess the quality of mean estimations</i> |
|--------|---|

Description

assess evaluates the quality of mean estimations using the methodology created by INE Chile, which considers sample size, degrees of freedom, and coefficient of variation.

Usage

```
assess(
  table,
  publish = FALSE,
  scheme = c("chile", "eclac_2020", "eclac_2023"),
  domain_info = FALSE,
  ...
)
```

Arguments

| | |
|---------|---|
| table | dataframe created by <code>crear_insumos_media</code> . |
| publish | boolean indicating if the evaluation of the complete table must be added. If TRUE, the function adds a new column to the dataframe. |

| | |
|-------------|--|
| scheme | character variable indicating the evaluation protocol to use. Options are "chile", "eclac_2020", "eclac_2023". |
| domain_info | Logical. If TRUE, indicates that the study domain information is available and will be used for assessment. This affects how the evaluation is conducted, leveraging specific domain-level data to refine the assessment results. When FALSE, domain-specific adjustments are omitted, and a generalized assessment is performed. |
| ... | <p>additional parameters for the evaluation. The complete list of parameters is:</p> <ol style="list-style-type: none"> 1. General Parameters <ul style="list-style-type: none"> • df degrees of freedom. Default: 9. • n sample size. Default for chile scheme: 60. Default for CEPAL schemes: 100. 2. chile Parameters <ul style="list-style-type: none"> • cv_lower_ine lower limit for CV. Default: 0.15. • cv_upper_ine upper limit for CV. Default: 0.3. 3. CEPAL 2020 Parameters <ul style="list-style-type: none"> • cv_cepal limit for CV. Default: 0.2. • ess effective sample size. Default: 140. • unweighted unweighted count. Default: 50. • log_cv logarithmic coefficient of variation. Default: 0.175. 4. CEPAL 2023 Parameters <ul style="list-style-type: none"> • cv_lower_cepal lower limit for CV. Default: 0.2. • cv_upper_cepal upper limit for CV. Default: 0.3. • ess effective sample size. Default: 60. • cvlog_max maximum logarithmic coefficient of variation. Default: 0.175. • CCNP_b unweighted count before adjustment. Default: 50. • CCNP_a unweighted count after adjustment. Default: 30. |

Value

dataframe with all the columns included in the input table, plus a new column containing a label indicating the evaluation of each estimation: reliable, bit reliable, or unreliable.

Examples

```
dc <- survey::svydesign(ids = ~varunit, strata = ~varstrat, data = epf_personas, weights = ~fe)
assess(create_mean("gastot_hd", domains = "zona+sexo", design = dc))
```

casen

*Encuesta de Caracterización Socioeconómica Nacional 2020 -
CASEN en Pandemia 2020*

Description

CASEN data for the year 2020. Contains only a few variables.

Usage

casen

Format

dataframe with 185.437 rows y 6 columns

folio household id

sexo 1 = man; 2 = woman

edad age

activ Economic activity status

ing_aut_hog Household Income

pobreza poverty status: 1 = extreme poverty, 2 = non-extreme poverty, 3 = non-poverty

expr regional sample weights

estrato strata

cod_upm PSU

Source

[http://observatorio\[ministeriodesarrollosocial.gob.cl\]/encuesta-casen-en-pandemia-2020](http://observatorio[ministeriodesarrollosocial.gob.cl]/encuesta-casen-en-pandemia-2020)

Examples

```
data(casen)
```

create_html*Create html table with the results of the evaluation*

Description

Create html table with the results of the evaluation

Usage

```
create_html(table)
```

Arguments

table dataframe generated by evaluate function

Value

html table

Examples

```
library(survey)
library(dplyr)

hogar <- epf_personas %>%
  group_by(folio) %>%
  slice(1)
dc <- survey::svydesign(ids = ~varunit, strata = ~varstrat, data = hogar, weights = ~fe)
table <- assess(create_prop("ocupado", domains = "zona+sexo", design = dc))
```

create_mean*Create the inputs to evaluate the quality of mean estimations*

Description

create_mean generates a dataframe with the following elements: mean, degrees of freedom, sample size, and coefficient of variation. The function allows grouping in several domains.

Usage

```
create_mean(
  var,
  domains = NULL,
  subpop = NULL,
  design,
  ci = FALSE,
```

```

ess = FALSE,
ajuste_ene = FALSE,
standard_eval = FALSE,
rm.na = FALSE,
deff = FALSE,
rel_error = FALSE,
unweighted = FALSE,
eclac_input = FALSE
)

```

Arguments

| | |
|----------------------------|--|
| <code>var</code> | numeric variable within the dataframe. |
| <code>domains</code> | domains to be estimated separated by the + character. |
| <code>subpop</code> | integer dummy variable to filter the dataframe. |
| <code>design</code> | complex design created by survey package. |
| <code>ci</code> | boolean indicating if the confidence intervals must be calculated. |
| <code>ess</code> | boolean effective sample size. |
| <code>ajuste_ene</code> | boolean indicating if an adjustment for the sampling-frame transition period must be used. |
| <code>standard_eval</code> | boolean indicating if the function is wrapped inside another function, if TRUE avoid lazy eval errors. |
| <code>rm.na</code> | boolean remove NA values if required. |
| <code>deff</code> | boolean design effect. |
| <code>rel_error</code> | boolean relative error. |
| <code>unweighted</code> | boolean add non-weighted count if required. |
| <code>eclac_input</code> | boolean return eclac inputs. |

Value

dataframe that contains the inputs and all domains to be evaluated.

Examples

```

dc <- survey::svydesign(ids = ~varunit, strata = ~varstrat, data = epf_personas, weights = ~fe)
create_mean("gastot_hd", "zona+sexo", design = dc)

```

create_prop*Create the inputs to evaluate the quality of proportion estimations*

Description

create_prop generates a dataframe with the following elements: sum, degrees of freedom, sample size, standard error, and coefficient of variation. The function allows grouping in several domains.

Usage

```
create_prop(
  var,
  denominator = NULL,
  domains = NULL,
  subpop = NULL,
  design,
  ci = FALSE,
  deff = FALSE,
  ess = FALSE,
  ajuste_ene = FALSE,
  rel_error = FALSE,
  log_cv = FALSE,
  unweighted = FALSE,
  standard_eval = FALSE,
  eclac_input = FALSE
)
```

Arguments

| | |
|-------------|---|
| var | numeric variable within the dataframe, is the numerator of the ratio to be calculated. |
| denominator | numeric variable within the dataframe, is the denominator of the ratio to be calculated. If the var parameter is dummy, it can be NULL. |
| domains | domains to be estimated separated by the + character. |
| subpop | integer dummy variable to filter the dataframe. |
| design | complex design created by survey package. |
| ci | boolean indicating if the confidence intervals must be calculated. |
| deff | boolean design effect. |
| ess | boolean effective sample size. |
| ajuste_ene | boolean indicating if an adjustment for the sampling-frame transition period must be used. |
| rel_error | boolean relative error. |
| log_cv | boolean logarithmic coefficient of variation. |
| unweighted | boolean add non-weighted count if required. |

```
standard_eval boolean indicating if the function is wrapped inside another function, if TRUE
    avoid lazy eval errors.
eclac_input   boolean return eclac inputs
```

Value

dataframe that contains the inputs and all domains to be evaluated.

Examples

```
library(survey)
library(dplyr)

epf <- mutate(epf_personas, gasto_zona1 = if_else(zona == 1, gastot_hd, 0))
dc <- svydesign(ids = ~varunit, strata = ~varstrat, data = epf, weights = ~fe)
old_options <- options()
options(survey.lonely.psu = "certainty")

create_prop(var = "gasto_zona1", denominator = "gastot_hd", design = dc)

enusc <- filter(enusc, Kish == 1)

dc <- svydesign(ids = ~Conglomerado, strata = ~VarStrat, data = enusc, weights = ~Fact_Pers)
options(survey.lonely.psu = "certainty")
create_prop(var = "VP_DC", denominator = "hom_insg_taxi", design = dc)
options(old_options)
```

create_prop_internal *internal function to calculate proportion estimations*

Description

internal function to calculate proportion estimations

Usage

```
create_prop_internal(
  var,
  domains = NULL,
  subpop = NULL,
  disenio,
  ci = FALSE,
  deff = FALSE,
  ess = FALSE,
  ajuste_ene = FALSE,
  rel_error = FALSE,
  log_cv = FALSE,
  unweighted = FALSE,
```

```

    standard_eval = TRUE,
    rm.na = FALSE,
    env = parent.frame()
)

```

Arguments

| | |
|---------------|--|
| var | integer dummy variable within the dataframe |
| domains | domains to be estimated separated by the + character. |
| subpop | integer dummy variable to filter the dataframe |
| disenio | complex design created by survey package |
| ci | boolean indicating if the confidence intervals must be calculated |
| deff | boolean Design effect |
| ess | boolean Effective sample size |
| ajuste_ene | boolean indicating if an adjustment for the sampling-frame transition period must be used |
| rel_error | boolean Relative error |
| log_cv | boolean indicating if the log cv must be returned |
| unweighted | boolean Add non weighted count if it is required |
| standard_eval | boolean indicating if the function is inside another function, by default it is TRUE, avoid problems with lazy eval. |
| rm.na | boolean indicating if NA values must be removed |
| env | parent environment to get some variables |

Value

dataframe that contains the inputs and all domains to be evaluated

create_ratio_internal *internal function to calculate ratios estimations*

Description

internal function to calculate ratios estimations

Usage

```

create_ratio_internal(
  var,
  denominator,
  domains = NULL,
  subpop = NULL,
  disenio,

```

```

    ci = FALSE,
    deff = FALSE,
    ess = FALSE,
    ajuste_ene = FALSE,
    unweighted = FALSE,
    rel_error = FALSE,
    rm.na = FALSE
)

```

Arguments

| | |
|--------------------------|---|
| <code>var</code> | numeric variable within the dataframe, is the numerator of the ratio to be calculated. |
| <code>denominator</code> | numeric variable within the dataframe, is the denominator of the ratio to be calculated. |
| <code>domains</code> | domains to be estimated separated by the + character. |
| <code>subpop</code> | integer dummy variable to filter the dataframe |
| <code>disenio</code> | complex design created by survey package |
| <code>ci</code> | boolean indicating if the confidence intervals must be calculated |
| <code>deff</code> | boolean Design effect |
| <code>ess</code> | boolean Effective sample size |
| <code>ajuste_ene</code> | boolean indicating if an adjustment for the sampling-frame transition period must be used |
| <code>unweighted</code> | boolean Add non weighted count if it is required |
| <code>rel_error</code> | boolean Relative error |
| <code>rm.na</code> | boolean indicating if NA values must be removed |

Value

dataframe that contains the inputs and all domains to be evaluated

`create_size`

Create the inputs to evaluate the quality of total estimations

Description

`create_size` generates a dataframe with the following elements: sum, degrees of freedom, sample size, and coefficient of variation. The function allows grouping in several domains.

Usage

```
create_size(
  var,
  domains = NULL,
  subpop = NULL,
  design,
  ci = FALSE,
  ess = FALSE,
  ajuste_ene = FALSE,
  standard_eval = FALSE,
  rm.na = FALSE,
  deff = FALSE,
  rel_error = FALSE,
  unweighted = FALSE,
  df_type = c("chile", "eclac"),
  eclac_input = FALSE
)
```

Arguments

| | |
|---------------|---|
| var | numeric variable within the dataframe. When the domain parameter is not used, it is possible to include more than one variable using the + separator. When a value is introduced in the domain parameter, the estimation variable must be a dummy variable. |
| domains | domains to be estimated separated by the + character. |
| subpop | integer dummy variable to filter the dataframe. |
| design | complex design created by survey package. |
| ci | boolean indicating if the confidence intervals must be calculated. |
| ess | boolean effective sample size. |
| ajuste_ene | boolean indicating if an adjustment for the sampling-frame transition period must be used. |
| standard_eval | boolean indicating if the function is wrapped inside another function, if TRUE avoid lazy eval errors. |
| rm.na | boolean remove NA values if required. |
| deff | boolean design effect. |
| rel_error | boolean relative error. |
| unweighted | boolean add non-weighted count if required. |
| df_type | character use degrees of freedom calculation approach from INE Chile or CEPAL. Options are "chile" or "eclac". |
| eclac_input | boolean return eclac inputs |

Value

dataframe that contains the inputs and all domains to be evaluated.

Examples

```
dc <- survey::svydesign(ids = ~varunit, strata = ~varstrat, data = epf_personas, weights = ~fe)
create_size("ocupado", "zona+sexo", design = dc)
```

create_total

Create the inputs to evaluate the quality of the sum of continuous variables

Description

`create_total` generates a dataframe with the following elements: sum, degrees of freedom, sample size, and coefficient of variation. The function allows grouping in several domains.

Usage

```
create_total(
  var,
  domains = NULL,
  subpop = NULL,
  design,
  ci = FALSE,
  ess = FALSE,
  ajuste_ene = FALSE,
  standard_eval = FALSE,
  rm.na = FALSE,
  deff = FALSE,
  rel_error = FALSE,
  unweighted = FALSE,
  eclac_input = FALSE
)
```

Arguments

| | |
|----------------------------|--|
| <code>var</code> | numeric variable within the dataframe. |
| <code>domains</code> | domains to be estimated separated by the + character. |
| <code>subpop</code> | integer dummy variable to filter the dataframe. |
| <code>design</code> | complex design created by <code>survey</code> package. |
| <code>ci</code> | boolean indicating if the confidence intervals must be calculated. |
| <code>ess</code> | boolean effective sample size. |
| <code>ajuste_ene</code> | boolean indicating if an adjustment for the sampling-frame transition period must be used. |
| <code>standard_eval</code> | boolean indicating if the function is wrapped inside another function, if TRUE avoid lazy eval errors. |
| <code>rm.na</code> | boolean remove NA values if required. |

| | |
|-------------|---|
| deff | boolean design effect. |
| rel_error | boolean relative error. |
| unweighted | boolean add non-weighted count if required. |
| eclac_input | boolean return eclac inputs |

Value

dataframe that contains the inputs and all domains to be evaluated.

Examples

```
dc <- survey::svydesign(ids = ~varunit, strata = ~varstrat, data = epf_personas, weights = ~fe)
create_total("gastot_hd", "zona+sexo", subpop = "ocupado", design = dc)
```

| | |
|----------------|---|
| eclac_standard | <i>Turn on all the indicators needed for the eclac standard</i> |
|----------------|---|

Description

This function activates the appropriate indicators based on the selected eclac standard and whether proportion indicators are needed.

Usage

```
eclac_standard(eclac, env = parent.frame(), proportion = FALSE)
```

Arguments

| | |
|------------|---|
| eclac | A logical value indicating the eclac standard. |
| env | The environment from which to retrieve the existing indicator values. Defaults to the parent frame. |
| proportion | A logical value indicating whether proportion indicators should be turned on. Defaults to FALSE. |

Value

A list of logical values indicating which indicators are turned on.

ene

Encuesta Nacional de Empleo - ENE. 2020-efm

Description

Reduced version of the ENE database. Contains some sociodemographic variables and the necessary information to work with complex design

Usage

ene

Format

dataframe with 87.842 rows y 7 columns

sexo 1 = man; 2 = woman

region region

cae_especifico Economic activity status

fe sample weights

varunit PSU

varstrat strata

fdt It shows if the person belongs to labour force: 1 = yes; 0 = no

ocupado 1 = employed; 0 = non-employed

desocupado 1 = non-employed; 0 = employed

Source

<https://www.ine.cl/estadisticas/sociales/mercado-laboral/ocupacion-y-desocupacion>

Examples

```
data(ene)
```

enusc

*Encuesta Nacional Urbana de Seguridad ciudadana 2019 - ENUSC
2019*

Description

ENUSC data for the year 2019. Contains only a few variables.

Usage

enusc

Format

dataframe with 24.465 rows y 22 columns

rph_sexo 1 = man; 2 = woman

region 16 regions

Fact_Pers person sample weights

Fact_Hog household sample weights

Conglomerado PSU

VarStrat strata

VP_DC Individual victimization. It works combined with Fact_Pers

VA_DC Household victimization. It works combined with Fact_Hog

rph_edad age

P3_1_1 Perception of increased crime in the country. It works combined with Fact_Pers

P8_1_1 Cause of increased crime in the neighborhood. It works combined with Fact_Pers

muj_insg_taxi Female perception of insecurity inside taxis. Variable elaborated with variables P9 and rph_sexo . It works combined with Fact_Pers

hom_insg_taxi Male perception of insecurity inside taxis. Variable elaborated with variables P9 and rph_sexo. It works combined with Fact_Pers

muj_insg_micro Female perception of insecurity inside buses. Variable elaborated with variables P9 and rph_sexo. It works combined with Fact_Pers

hom_insg_micro Male perception of insecurity inside buses. Variable elaborated with variables P9 and rph_sexo. It works combined with Fact_Pers

muj_insg_centr.com Female perception of insecurity inside malls. Variable elaborated with variables P9 and rph_sexo. It works combined with Fact_Pers

hom_insg_centr.com Male perception of insecurity inside malls. Variable elaborated with variables P9 and rph_sexo. It works combined with Fact_Pers

muj_insg_loc.col Female perception of insecurity public transport. Variable elaborated with variables P9 and rph_sexo. It works combined with Fact_Pers

hom_insg_loc.col Male perception of insecurity public transport. Variable elaborated with variables P9 and rph_sexo. It works combined with Fact_Pers

muj_insg_barrio Female perception of insecurity neighborhood. Variable elaborated with variables P9 and rph_sexo. It works combined with Fact_Pers

hom_insg_barrio Male perception of insecurity neighborhood. Variable elaborated with variables P9 and rph_sexo. It works combined with Fact_Pers

Source

https://www.ine.cl/docs/default-source/seguridad-ciudadana/bbdd/2019/base-de-datos---xvi-enusc-2019.csv?sfvrsn=d3465758_2&download=true

Examples

```
data(enusc)
```

epf_personas

VIII Encuesta de Presupuestos Familiares

Description

Reduced version of the VIII EPF database. Contains some sociodemographic variables and the necessary information to work with complex design.

Usage

```
epf_personas
```

Format

dataframe compuesto por 48.308 observaciones y 8 variables

sexo 1 = male; 2 = female

zona 1 = metropolitan area; 2 = rest of the regional capitals

ecivil marital status

fe sample weights

varunit PSU

varstrat strata

gastot_hd household expenditure

ocupado 1 = employed; 0 = non-employed

Source

<https://www.ine.cl/estadisticas/sociales/ingresos-y-gastos/encuesta-de-presupuestos-familiares>

Examples

```
data(epf_personas)
```

`get_cv`

Get the coefficient of variation

Description

Receive a table created with survey and return the coefficient of variation for each cell

Usage

```
get_cv(table, design, domains, type_est = "all", env = parent.frame())
```

Arguments

| | |
|----------|----------------------------------|
| table | dataframe with results |
| design | design |
| domains | vector with domains |
| type_est | type of estimation: all or size. |
| env | parent environment |

Value

dataframe with results including including CV

`get_df`

Get degrees of freedom

Description

Receive data and domains. Returns a data frame with the psu, strata and df for each cell

Usage

```
get_df(data, domains, df_type = "eclac")
```

Arguments

| | |
|---------|---|
| data | dataframe |
| domains | string with domains |
| df_type | string Use degrees of freedom calculation approach from INE Chile or eclac, by default "chile". |

Value

`dataframe` with results including degrees of freedom

| | |
|-------------------------------|---|
| <code>get_survey_table</code> | <i>Calculates multiple estimations. Internal wrapper for survey package</i> |
|-------------------------------|---|

Description

Generates a table with estimates for a given aggregation

Usage

```
get_survey_table(
  var,
  domains,
  complex_design,
  estimation = "mean",
  env = parent.frame(),
  fun,
  denom = NULL,
  type_est = "all"
)
```

Arguments

| | |
|-----------------------------|--|
| <code>var</code> | string objective variable |
| <code>domains</code> | domains |
| <code>complex_design</code> | design from survey |
| <code>estimation</code> | string indicating if the mean must be calculated |
| <code>env</code> | parent environment |
| <code>fun</code> | function required regarding the estimation |
| <code>denom</code> | denominator. This parameter works for the ratio estimation |
| <code>type_est</code> | type of estimation: all or size |

Value

`dataframe` containing main results from survey

quadratic*Calcula el valor de una función cuadrática*

Description

`quadratic` returns the output of a particular function created by INE Chile, which is assessed at the value of the estimated proportion from a sample. If the output of the function is higher than the standard error, it is interpreted as a signal that the estimation is not reliable.

Usage

```
quadratic(p)
```

Arguments

`p` numeric vector with the values of the estimations for proportions

Value

numeric vector

standardize_columns*standardize and sort column names*

Description

Receive the survey table in raw state and sort it

Usage

```
standardize_columns(data, var, denom)
```

Arguments

`data` dataframe with results
`var` string with the objective variable
`denom` denominator

Value

dataframe with standardized data

standardize_design_variables
Standardize the name of design variables

Description

Rename design variables, so we can use the later

Usage

```
standardize_design_variables(design)
```

Arguments

| | |
|--------|-----------|
| design | dataframe |
|--------|-----------|

Value

design survey

Index

* datasets

casen, [4](#)
ene, [14](#)
enusc, [15](#)
epf_personas, [16](#)

assess, [2](#)

casen, [4](#)
create_html, [5](#)
create_mean, [5](#)
create_prop, [7](#)
create_prop_internal, [8](#)
create_ratio_internal, [9](#)
create_size, [10](#)
create_total, [12](#)

eclac_standard, [13](#)
ene, [14](#)
enusc, [15](#)
epf_personas, [16](#)

get_cv, [17](#)
get_df, [17](#)
get_survey_table, [18](#)

quadratic, [19](#)

standardize_columns, [19](#)
standardize_design_variables, [20](#)