

Package ‘tlsR’

December 18, 2025

Title Detection and Spatial Analysis of Tertiary Lymphoid Structures

Version 0.1.2

Description Fast, reproducible detection and quantitative analysis of tertiary lymphoid structures (TLS) in multiplexed tissue imaging. Implements Independent Component Analysis Trace (ICAT) index, local Ripley’s K scanning, automated K Nearest Neighbor (KNN)-based TLS detection, and T-cell clusters identification as described in Amiryousefi et al. (2025) <[doi:10.1101/2025.09.21.677465](https://doi.org/10.1101/2025.09.21.677465)>.

Note TLS, ICAT, KNN are correct technical acronyms.

License MIT + file LICENSE

Encoding UTF-8

LazyData true

RoxygenNote 7.3.2

Imports fastICA, spatstat.geom, spatstat.explore, dbscan, RANN, grDevices, graphics, stats, utils

Suggests testthat (>= 3.0.0)

Config/testthat/edition 3

Depends R (>= 3.5)

NeedsCompilation no

Author Ali Amiryousefi [aut, cre] (ORCID: <<https://orcid.org/0000-0002-6317-3860>>),
Jeremiah Wala [aut] (ORCID: <<https://orcid.org/0000-0001-6591-1620>>),
Peter Sorger [ctb] (ORCID: <<https://orcid.org/0000-0002-3364-1838>>)

Maintainer Ali Amiryousefi <ali_amiryousefi@hms.harvard.edu>

Repository CRAN

Date/Publication 2025-12-18 14:40:03 UTC

Contents

calc_icat	2
detect_tic	2

detect_TLS	3
scan_clustering	4
toy_ldata	4

Index 6

calc_icat *Calculate ICAT (Immune Cell Arrangement Trace) Index*

Description

Quantifies linear/organized arrangement of cells within a TLS using FastICA.

Arguments

patientID Character. Name of the sample in ldata.
 tlsID Numeric/integer. TLS identifier.
 ldata Named list of data frames (optional; defaults to global ldata).

Value

Numeric ICAT value.

Examples

```
data(toy_ldata)
ldata <- detect_TLS("ToySample", k = 30, ldata = toy_ldata) # First detect TLS
if (max(ldata[["ToySample"]]$tls_id_knn) > 0) {
  icat <- calc_icat("ToySample", tlsID = 1, ldata = ldata)
  icat
}
```

detect_tic *Detect Tumor-Infiltrating T-cell Clusters (TIC)*

Description

Uses HDBSCAN approximation on T cells outside TLS regions to find TIC.

Arguments

sample Character. Sample name.
 ldata Optional list.

Value

Modified data frame for the sample (invisibly).

Examples

```
data(toy_ldata)
ldata <- detect_TLS("ToySample", k = 30, ldata = toy_ldata) # Need TLS first
ldata <- detect_tic("ToySample", ldata = ldata)
table(ldata[["ToySample"]]$tcell_cluster_hdbscan)
```

detect_TLS	<i>Detect Tertiary Lymphoid Structures using a KNN-density approach</i>
------------	---

Description

This function identifies TLS candidates germinated with B cells (BIC) by: 1. Finding regions of high local B-cell density (KNN-based). 2. Requiring a minimum number of neighbouring T cells (T-B cell co-localisation). 3. Applying sensible size and shape filters.

Arguments

LSP	Character. Sample name in the global ldata list.
k	Integer. Number of nearest neighbours to consider (default 30 - works very well on 0.325 um/px imaging).
bcell_density_threshold	Numeric. Minimum average 1/k-distance for B cells to be considered "dense" (default 15 um).
min_B_cells	Integer. Minimum number of B cells in a candidate TLS (default 50).
min_T_cells_nearby	Integer. Minimum T cells within 50 um of the B-cell cluster centre (default 30).
max_distance_T	Numeric. Radius (um) to search for surrounding T cells (default 50).
ldata	Optional. Named list of data frames. If NULL, uses global ldata.

Value

The original data frame with two new columns:

tls_id_knn	0 = non-TLS, positive integer = TLS cluster ID
tls_center_x, tls_center_y	Coordinates of detected TLS centres (only for TLS cells)

Examples

```
data(toy_ldata)
ldata <- detect_TLS("ToySample", k = 30, ldata = toy_ldata)
table(ldata[["ToySample"]]$tls_id_knn)
plot(ldata[["ToySample"]]$x, ldata[["ToySample"]]$y,
     col = ifelse(ldata[["ToySample"]]$tls_id_knn > 0, "red", "gray"),
     pch = 19, cex = 0.5, main = "Detected TLS in toy data")
```

scan_clustering	<i>Scan Tissue for Local Immune Cell Clustering (K-integral)</i>
-----------------	--

Description

Sliding-window Centered L-Function (CLF) version of the Ripley's K analysis with whole tissue pseudo-plots.

Arguments

ws	Window size in microns.
sample	Character. Sample name in ldata.
phenotype	One of "T cells", "B cells", or "Both".
plot	Logical. Show diagnostic plot?
creep	Integer. Grid density factor.
ldata	Optional list (defaults to global ldata).

Value

List of Lest objects for significant windows.

Examples

```
data(toy_ldata)
# This one may produce plots and take ~10 sec
models <- scan_clustering(ws = 500, sample = "ToySample",
                          phenotype = "B cells", plot = FALSE, ldata = toy_ldata)
length(models)
```

toy_ldata	<i>Toy multiplexed imaging data for examples</i>
-----------	--

Description

A small synthetic dataset mimicking multiplexed tissue imaging data. It contains one sample named "ToySample" with columns required by tIsR functions.

Usage

```
toy_ldata
```

Format

A named list with one element:

ToySample A data frame with columns:

- x: x-coordinate in microns
- y: y-coordinate in microns
- coarse_phen_vec: Cell phenotype ("B cells", "T cells", or "Other")
- row_index: Integer row index (1 to nrow)
- cflag: Integer flag column (0 for all cells)

Examples

```
data(toy_ldata)
str(toy_ldata[["ToySample"]])
plot(toy_ldata[["ToySample"]]$x, toy_ldata[["ToySample"]]$y,
      col = as.factor(toy_ldata[["ToySample"]]$coarse_phen_vec),
      pch = 19, cex = 0.5, main = "Toy sample cells")
```

Index

* datasets

toy_ldata, 4

calc_icat, 2

detect_tic, 2

detect_TLS, 3

scan_clustering, 4

toy_ldata, 4