

Package ‘networkformat’

October 16, 2026

Type Package

Title Convert R Objects to Network Edgelists and Nodelists

Version 0.1.2

Description Network analysis and plotting packages such as 'igraph', 'tidygraph', and 'ggraph' expect the edges and nodes of a graph as flat tables. Methods are provided to build those tables from data frames (column-pair edges chosen with 'tidyselect' semantics), tree-based model objects ('randomForest', 'tree', 'rpart', 'xgboost', 'gbm'), lists (recursive parent-child edges), and atomic vectors (sequential edges). Graphs can also be constructed in one step via `as.igraph()` and `as_tbl_graph()` methods for tree models.

License MIT + file LICENSE

Encoding UTF-8

LazyData true

Depends R (>= 3.6.0)

Imports rlang, tidyselect

Suggests randomForest, tree, xgboost, gbm, rpart, testthat (>= 3.0.0), covr, igraph, tidygraph, ggraph, knitr, rmarkdown

Config/testthat/edition 3

URL <https://jessebrandtdata.github.io/networkformat/>,
<https://github.com/jessebrandtdata/networkformat>

BugReports <https://github.com/jessebrandtdata/networkformat/issues>

VignetteBuilder knitr

Config/roxygen2/version 8.0.0

NeedsCompilation no

Author Jesse Brandt [aut, cre] (ORCID:
<<https://orcid.org/0009-0005-7462-075X>>)

Maintainer Jesse Brandt <jesse.a.brandt@gmail.com>

Repository CRAN

Date/Publication 2026-10-16 12:50:07 UTC

Contents

as.igraph	2
as_tbl_graph	3
courses	4
edgelist	5
edgelist.data.frame	6
edgelist.default	8
edgelist.gbm	9
edgelist.list	10
edgelist.randomForest	11
edgelist.rpart	12
edgelist.tree	13
edgelist.xgb.Booster	14
nodelist	15
nodelist.data.frame	16
nodelist.default	17
nodelist.gbm	17
nodelist.list	18
nodelist.randomForest	19
nodelist.rpart	20
nodelist.tree	21
nodelist.xgb.Booster	22
Index	24

as.igraph	<i>Convert to igraph</i>
-----------	--------------------------

Description

S3 methods for converting tree-based model objects into **igraph** graph objects. Each method calls **edgelist** and **nodelist** internally and handles column reconciliation so you get a ready-to-use graph. These methods are registered against the **as.igraph** generic from **igraph** via delayed S3 registration and are available whenever **igraph** is loaded.

Usage

```
## S3 method for class 'tree'
as.igraph(x, ...)

## S3 method for class 'randomForest'
as.igraph(x, treenum = NULL, ...)

## S3 method for class 'rpart'
as.igraph(x, ...)

## S3 method for class 'xgb.Booster'
```

```
as.igraph(x, treenum = NULL, ...)

## S3 method for class 'gbm'
as.igraph(x, treenum = NULL, ...)
```

Arguments

x	An object to convert (tree, randomForest, rpart, xgb.Booster, or gbm).
...	Additional arguments passed to methods.
treenum	Integer vector of tree numbers to extract. Default NULL returns all trees combined into one graph with disconnected components. Pass a single integer (e.g. 1) to extract one tree.

Value

An [igraph](#) object. For randomForest with multiple trees, the graph contains disconnected components (one per tree) and a treenum vertex/edge attribute.

Examples

```
if (requireNamespace("rpart", quietly = TRUE) &&
    requireNamespace("igraph", quietly = TRUE)) {
  fit <- rpart::rpart(Sepal.Length ~ ., data = iris)
  g <- igraph::as.igraph(fit)
  igraph::vcount(g)
  igraph::ecount(g)
}
```

as_tbl_graph	<i>Convert to tbl_graph</i>
--------------	-----------------------------

Description

S3 methods for converting tree-based model objects into [tbl_graph](#) objects. Each method wraps the corresponding [as.igraph](#) method. These methods are registered against the [as_tbl_graph](#) generic from **tidygraph** via delayed S3 registration and are available whenever **tidygraph** is loaded.

Usage

```
## S3 method for class 'tree'
as_tbl_graph(x, ...)

## S3 method for class 'randomForest'
as_tbl_graph(x, treenum = NULL, ...)

## S3 method for class 'rpart'
as_tbl_graph(x, ...)
```

```
## S3 method for class 'xgb.Booster'
as_tbl_graph(x, treenum = NULL, ...)

## S3 method for class 'gbm'
as_tbl_graph(x, treenum = NULL, ...)
```

Arguments

<code>x</code>	An object to convert (currently <code>tree</code> , <code>randomForest</code> , <code>rpart</code> , <code>xgb.Booster</code> , or <code>gbm</code>).
<code>...</code>	Additional arguments passed to as.igraph .
<code>treenum</code>	Integer vector of tree numbers to extract. Default <code>NULL</code> returns all trees combined into one graph with disconnected components. Pass a single integer (e.g. 1) to extract one tree.

Value

A [tbl_graph](#) object.

Examples

```
if (requireNamespace("rpart", quietly = TRUE) &&
    requireNamespace("tidygraph", quietly = TRUE) &&
    requireNamespace("igraph", quietly = TRUE)) {
  fit <- rpart::rpart(Sepal.Length ~ ., data = iris)
  tg <- tidygraph::as_tbl_graph(fit)
  tg
}
```

courses

Course prerequisite and crosslisting network

Description

A small dataset of university courses with prerequisite and crosslisting relationships, suitable for demonstrating `edgelist()` and `nodelist()`.

Usage

```
courses
```

Format

A data.frame with 13 rows and 7 columns:

dept Department code (STAT, MATH, DATA, CS)

course Course identifier, used as node ID

prereq Prerequisite course (NA if none)

prereq2 Second prerequisite course (NA if none)
crosslist Crosslisted equivalent course (NA if none)
credits Number of credit hours (integer)
level Course level: 100, 200, or 300 (integer)

Examples

```
# Prerequisite edgelist (course -> prereq)
edgelist(courses, source_cols = course, target_cols = prereq)

# Node list with course as ID column
nodelist(courses, id_col = course)
```

edgelist

Extract Edgelist from Various Object Types

Description

Generic function to extract a network edgelist from various object types. Methods exist for atomic vectors (sequential edges), data frames (column-pair edges), lists (recursive parent-child edges), and tree-based model objects (randomForest, tree, rpart, xgb.Booster, gbm). The specific columns returned depend on the input type.

Usage

```
edgelist(input_object, ...)
```

Arguments

input_object An object to extract an edgelist from
... Additional arguments passed to specific methods

Value

A data.frame representing an edgelist. The specific columns depend on the input object type.

Examples

```
# Vector --- sequential edges
edgelist(c("A", "B", "C", "D"))

# Data.frame example using bundled dataset
edgelist(courses, source_cols = course, target_cols = prereq)

# RandomForest example
if (requireNamespace("randomForest", quietly = TRUE)) {
  rf <- randomForest::randomForest(Species ~ ., data = iris, ntree = 5)
  edges_rf <- edgelist(rf)
```

```

    head(edges_rf)
  }

  # Tree example
  if (requireNamespace("tree", quietly = TRUE)) {
    tr <- tree::tree(Species ~ ., data = iris)
    edges_tr <- edgelist(tr)
    head(edges_tr)
  }

```

edgelist.data.frame *Extract Edgelist from Data Frame*

Description

Converts a data.frame to network edgelist format by specifying which columns represent source and target nodes. This is useful for creating edgelists from tabular data where node relationships are stored in columns.

Usage

```

## S3 method for class 'data.frame'
edgelist(
  input_object,
  source_cols = 1,
  target_cols = 2,
  attr_cols = NULL,
  na.rm = TRUE,
  symmetric_cols = NULL,
  dedupe = TRUE,
  weights = FALSE,
  ...
)

```

Arguments

input_object	A data.frame containing network information
source_cols	Column(s) for source nodes (default: 1). Accepts tidyselect expressions: bare names, strings, numeric indices, or helpers like starts_with().
target_cols	Column(s) for target nodes (default: 2). Same syntax as source_cols.
attr_cols	Columns to carry as edge attributes (default: NULL keeps all columns not used as source or target). Pass an empty c() to keep only from, to, and metadata columns. Accepts the same tidyselect syntax as source_cols.
na.rm	Logical; if TRUE (the default), rows where from or to is NA are removed from the result. Set to FALSE to keep all rows including those with NA endpoints.

<code>symmetric_cols</code>	Target column names that represent undirected (symmetric) relationships. When non-NULL, a directed column is added: FALSE for edges from target columns named in <code>symmetric_cols</code> , TRUE otherwise. Accepts the same tidyselect syntax as <code>target_cols</code> ; names must be a subset of <code>target_cols</code> .
<code>dedupe</code>	Logical; if TRUE (the default) and <code>symmetric_cols</code> is non-NULL, duplicate undirected edges are removed by keeping only rows where <code>from</code> <= <code>to</code> (lexicographic comparison). Set to FALSE to preserve both directions.
<code>weights</code>	Logical; if TRUE, fully identical rows (same <code>from</code> , <code>to</code> , and all attribute columns) are collapsed and a weight column is added with the count. Rows that share (<code>from</code> , <code>to</code>) but differ in any attribute are kept separate. Applied after NA removal and symmetric deduplication. Defaults to FALSE.
<code>...</code>	Additional arguments (currently unused)

Value

A data.frame with columns:

from Source node values

to Target node values

from_col Name of the original column each source value came from

to_col Name of the original column each target value came from

directed (only when `symmetric_cols` is provided) Logical: FALSE for edges from symmetric target columns, TRUE otherwise

weight (only when `weights` = TRUE) Integer count of how many times each unique (`from`, `to`) pair occurred

... Additional attribute columns selected by `attr_cols`

Examples

```
# Basic usage --- all non-source/target columns kept by default
edgelist(courses, source_cols = course, target_cols = prereq)

# Multiple target columns --- to_col identifies the relationship type
edgelist(courses, source_cols = course, target_cols = c(prereq, crosslist))

# Keep only the edgelist (no attribute columns)
edgelist(courses, source_cols = course, target_cols = prereq, attr_cols = c())

# Select specific attribute columns
edgelist(courses, source_cols = course, target_cols = prereq,
        attr_cols = c(dept, credits))

# NA removal (default) vs preservation
edgelist(courses, source_cols = course, target_cols = c(prereq, crosslist))
edgelist(courses, source_cols = course, target_cols = c(prereq, crosslist),
        na.rm = FALSE)

# Mark symmetric (undirected) target columns
```

```
edgelist(courses, source_cols = course,
        target_cols = c(prereq, crosslist),
        symmetric_cols = crosslist)
```

edgelist.default	<i>Extract Edgelist from a Vector or Unsupported Object</i>
------------------	---

Description

When called on an atomic vector (character, numeric, integer, logical, factor), creates a sequential edgelist connecting each element to the next: element i is connected to element $i + 1$. For all other unsupported types, an informative error is raised.

Usage

```
## Default S3 method:
edgelist(input_object, weights = FALSE, ...)
```

Arguments

<code>input_object</code>	An atomic vector, or an object for which no specific edgelist method exists.
<code>weights</code>	Logical; if TRUE, duplicate edges are collapsed and a weight column is added with the count of each unique (from, to) pair. Defaults to FALSE.
<code>...</code>	Additional arguments (currently unused)

Value

A data.frame with columns from and to (and weight when weights = TRUE). For unsupported types, an error is raised.

Examples

```
# Character vector
edgelist(c("A", "B", "C", "D"))

# Numeric vector
edgelist(1:5)

# With duplicate counting
edgelist(c("A", "B", "A", "B", "C"), weights = TRUE)

# Unsupported type
try(edgelist(as.formula(y ~ x)))
```

edgelist.gbm

*Extract Edgelist from GBM Model***Description**

Converts a gbm model object into a network edgelist representation using `pretty.gbm.tree()`. Missing-sentinel nodes (the phantom routing nodes gbm creates for NA handling) are excluded — only real LeftNode/RightNode edges are returned.

Usage

```
## S3 method for class 'gbm'
edgelist(input_object, treenum = NULL, ...)
```

Arguments

<code>input_object</code>	A gbm model object from the gbm package
<code>treenum</code>	Integer vector of 1-based tree numbers to extract (default: NULL extracts all trees). For multinomial models, this indexes physical trees (not boosting iterations).
<code>...</code>	Additional arguments (currently unused)

Details

Node IDs are 0-based integers per tree. For models with `num.classes > 1` (multinomial), physical trees are stored as `n.trees * num.classes` entries; `treenum` indexes into this flat sequence.

Value

A data.frame with the following columns:

from Parent node ID (0-based integer)

to Child node ID (0-based integer)

split_var 0-based variable index

split_point Split threshold for continuous variables, or `c.splits` index for categorical variables

prediction Prediction value at the child node

treenum 1-based tree number

split_var_name Human-readable variable name

Examples

```
if (requireNamespace("gbm", quietly = TRUE)) {
  set.seed(1)
  fit <- gbm::gbm(mpg ~ ., data = mtcars,
                  distribution = "gaussian", n.trees = 5,
                  interaction.depth = 3, n.minobsinnode = 3)
  el <- edgelist(fit)
  head(el)

  # Single tree
  el1 <- edgelist(fit, treenum = 1)
}
```

edgelist.list	<i>Extract Edgelist from a List</i>
---------------	-------------------------------------

Description

Recursively traverses a nested list structure, producing a parent-child edgelist. Each element of the list becomes a node; nested lists create deeper edges. Path-style IDs ensure unique node names even when element names repeat at different levels.

Usage

```
## S3 method for class 'list'
edgelist(input_object, name_root = "root", max_depth = NULL, ...)
```

Arguments

<code>input_object</code>	A list (or S3 object falling through to this method).
<code>name_root</code>	Character; label for the root node. Defaults to "root".
<code>max_depth</code>	Integer or NULL; maximum node depth to include (root is depth 0, its children are depth 1). NULL (the default) means unlimited. <code>max_depth = 0</code> returns an empty edgelist (root only).
<code>...</code>	Additional arguments (currently unused).

Details

When called on an S3 object that has no dedicated `edgelist` method (e.g. an `lm` object), the object is treated as a plain list and a diagnostic message is emitted. To force structural decomposition of an object that has its own method (e.g. a `tree`), use `edgelist(unclass(x))`.

Value

A data.frame with columns `from`, `to`, and `depth` (integer depth of the child node, root children are depth 1). An empty list returns a zero-row data.frame with the same columns.

Examples

```
edgelist(list(a = 1, b = list(c = 2, d = 3)))

# Unnamed elements use positional indices
edgelist(list(1, 2, list(3, 4)))

# Limit depth (root = 0, children = 1, ...)
edgelist(list(a = list(b = list(c = 1))), max_depth = 2)
```

`edgelist.randomForest` *Extract Edgelist from RandomForest Model*

Description

Converts a randomForest model object into a network edgelist representation by extracting parent-child relationships from one or more trees in the forest. Each edge represents a split in the decision tree, with additional attributes including split variable, split point, and prediction values.

Usage

```
## S3 method for class 'randomForest'
edgelist(input_object, treenum = NULL, ...)
```

Arguments

<code>input_object</code>	A randomForest model object from the randomForest package
<code>treenum</code>	Integer vector of tree numbers to extract (default: NULL extracts all trees). Values must be between 1 and <code>input_object\$ntree</code> .
<code>...</code>	Additional arguments (currently unused)

Value

A data.frame with the following columns:

from Parent node index within the tree
to Child node index (left or right daughter)
split_var Numeric index of the variable used for splitting
split_point Threshold value for the split
prediction Prediction value at the child node
direction Branch direction: "left" or "right"
treenum Tree number within the forest
split_var_name Character vector with human-readable variable names

Examples

```
if (requireNamespace("randomForest", quietly = TRUE)) {
  set.seed(12)
  rf_model <- randomForest::randomForest(
    Species ~ .,
    data = iris,
    ntree = 5,
    maxnodes = 10
  )

  # Extract all trees
  rf_edges <- edgelist(rf_model)
  head(rf_edges)

  # Extract specific trees
  rf_edges_1 <- edgelist(rf_model, treenum = 1)
  rf_edges_13 <- edgelist(rf_model, treenum = c(1, 3))
}
```

edgelist.rpart

Extract Edgelist from rpart Model

Description

Converts an rpart model object into a network edgelist representation. The rpart package uses binary heap numbering for node IDs (root = 1, left child of $k = 2k$, right child of $k = 2k + 1$), so parent-child edges are derived directly from the node IDs in `rownames(input_object$frame)`.

Usage

```
## S3 method for class 'rpart'
edgelist(input_object, ...)
```

Arguments

<code>input_object</code>	An rpart model object from the rpart package
<code>...</code>	Additional arguments (currently unused)

Details

Edge labels come from `labels(input_object, collapse = TRUE)`, which correctly handles the `ncat` sign that controls split direction (left child does not always get "<").

Value

A data.frame with the following columns:

from Parent node ID (binary heap index)

to Child node ID (binary heap index)

label Split condition label from labels()

split_var Variable name used for the split

split_op Operator: "<" or ">=" for numeric splits, NA for categorical splits

split_point Numeric threshold for the split (NA for categorical splits)

Examples

```
if (requireNamespace("rpart", quietly = TRUE)) {
  fit <- rpart::rpart(Species ~ ., data = iris)
  el <- edgelist(fit)
  head(el)

  # Parsed split components
  el[, c("split_var", "split_op", "split_point")]
}
```

edgelist.tree	<i>Extract Edgelist from Tree Model</i>
---------------	---

Description

Converts a tree model object (from the tree package) into a network edgelist representation. The tree package uses binary heap numbering for node IDs (root = 1, left child of k = 2k, right child of k = 2k + 1), so parent-child edges are derived directly from the node IDs in rownames(input_object\$frame).

Usage

```
## S3 method for class 'tree'
edgelist(input_object, ...)
```

Arguments

input_object A tree model object from the tree package

... Additional arguments (currently unused)

Value

A data.frame with the following columns:

from Parent node ID (binary heap index)

to Child node ID (binary heap index)

label Split condition label (variable and threshold)

split_var Variable name used for the split

split_op Operator: "<" or ">" for numeric splits, NA for categorical splits

split_point Numeric threshold for the split (NA for categorical splits)

Examples

```
if (requireNamespace("tree", quietly = TRUE)) {
  # Fit a classification tree
  tree_model <- tree::tree(Species ~ ., data = iris)

  # Extract edgelist
  tree_edges <- edgelist(tree_model)
  head(tree_edges)

  # Parsed split components
  tree_edges[, c("split_var", "split_op", "split_point")]
}
```

edgelist.xgb.Booster *Extract Edgelist from XGBoost Model*

Description

Converts an xgboost model object into a network edgelist representation using `xgb.model.dt.tree()`. Each edge connects a split node to one of its two children (yes/no branches). Node IDs are globally unique strings in "Tree-Node" format (e.g., "0-3").

Usage

```
## S3 method for class 'xgb.Booster'
edgelist(input_object, treenum = NULL, ...)
```

Arguments

<code>input_object</code>	An xgboost model object (xgb.Booster)
<code>treenum</code>	Integer vector of 1-based tree numbers to extract (default: NULL extracts all trees).
<code>...</code>	Additional arguments (currently unused)

Value

A data.frame with the following columns:

from Parent node ID string ("Tree-Node" format)

to Child node ID string

feature Name of the split variable (or 0-based index string when feature names are absent)

split Numeric split threshold

quality Information gain at the split

cover Number of observations covered

treenum 1-based tree number

Examples

```
if (requireNamespace("xgboost", quietly = TRUE)) {
  data(agaricus.train, package = "xgboost")
  bst <- xgboost::xgboost(
    x = agaricus.train$data,
    y = factor(agaricus.train$label),
    max_depth = 2, nrounds = 2, nthreads = 1
  )
  el <- edgelist(bst)
  head(el)
}
```

nodelist

Extract Node List from Various Objects

Description

Generic function to extract a node list (with attributes) from various object types including atomic vectors (unique values with frequencies), data frames, lists (recursive node decomposition), and tree models (randomForest, tree, rpart, xgb.Booster, gbm). The node list provides metadata about each node in the network.

Usage

```
nodelist(input_object, ...)
```

Arguments

input_object An object containing node information (vector, data.frame, tree model, etc.)

... Additional arguments passed to specific methods

Value

A data.frame where the first column is the node ID and subsequent columns contain node attributes

Examples

```
# Vector --- unique values with frequency counts
nodelist(c("A", "B", "A", "C"))

# Node list with course as ID (column 2)
nodelist(courses, id_col = 2)
```

nodelist.data.frame	<i>Extract Node List from Data Frame</i>
---------------------	--

Description

Reorders a data.frame to place the ID column first, creating a proper node list format. All other columns are treated as node attributes.

Usage

```
## S3 method for class 'data.frame'
nodelist(input_object, id_col = 1, ...)
```

Arguments

input_object	A data.frame containing node information
id_col	Column for the node ID (default: 1). Accepts tidyselect expressions: a bare name, string, or numeric index.
...	Additional arguments (currently unused)

Value

A data.frame with the ID column first, followed by all attribute columns

Examples

```
# Default: first column (dept) is ID
nodelist(courses)

# Use bare column name
nodelist(courses, id_col = course)

# Numeric index still works
nodelist(courses, id_col = 2)
```

nodelist.default	<i>Extract Node List from a Vector or Unsupported Object</i>
------------------	--

Description

When called on an atomic vector (character, numeric, integer, logical, factor), returns the unique values as a node list with a name column (preserving order of first appearance) and an n column giving the frequency of each value. For all other unsupported types, an informative error is raised.

Usage

```
## Default S3 method:
nodelist(input_object, ...)
```

Arguments

input_object	An atomic vector, or an object for which no specific nodelist method exists.
...	Additional arguments (currently unused)

Value

A data.frame with columns name (unique values in order of first appearance) and n (frequency count). For unsupported types, an error is raised.

Examples

```
# Character vector
nodelist(c("A", "B", "C", "A", "B"))

# Numeric vector
nodelist(c(1, 2, 3, 2, 1))

# Unsupported type
try(nodelist(as.formula(y ~ x)))
```

nodelist.gbm	<i>Extract Node List from GBM Model</i>
--------------	---

Description

Extracts node-level attributes from a gbm model via pretty.gbm.tree(). Missing-sentinel nodes are excluded by keeping only nodes reachable through LeftNode/RightNode edges from the root.

Usage

```
## S3 method for class 'gbm'
nodelist(input_object, treenum = NULL, ...)
```

Arguments

<code>input_object</code>	A gbm model object from the gbm package
<code>treenum</code>	Integer vector of 1-based tree numbers to extract (default: NULL extracts all trees).
<code>...</code>	Additional arguments (currently unused)

Value

A data.frame with one row per real node and the following columns:

name	0-based node ID within the tree
is_leaf	Logical: TRUE for terminal nodes
split_var	0-based variable index (NA for leaves)
split_var_name	Variable name (NA for leaves)
split_point	Split threshold (NA for leaves)
prediction	Prediction value at the node
error_reduction	Impurity reduction from the split (0 for leaves); per-node variable importance from ErrorReduction
weight	Number of training observations reaching the node, from Weight
treenum	1-based tree number
label	Display label: "<var>\n< threshold>" for splits, rounded prediction for leaves

Examples

```
if (requireNamespace("gbm", quietly = TRUE)) {
  set.seed(1)
  fit <- gbm::gbm(mpg ~ ., data = mtcars,
                  distribution = "gaussian", n.trees = 5,
                  interaction.depth = 3, n.minobsinnode = 3)
  nl <- nodelist(fit)
  head(nl)
}
```

nodelist.list	<i>Extract Node List from a List</i>
---------------	--------------------------------------

Description

Recursively traverses a nested list structure, producing one row per node with metadata about each element.

Usage

```
## S3 method for class 'list'
nodelist(input_object, name_root = "root", max_depth = NULL, ...)
```

Arguments

input_object	A list (or S3 object falling through to this method).
name_root	Character; label for the root node. Defaults to "root".
max_depth	Integer or NULL; maximum node depth to include (root is depth 0, its children are depth 1). NULL (the default) means unlimited. max_depth = 0 returns the root node only.
...	Additional arguments (currently unused).

Details

When called on an S3 object that has no dedicated `nodelist` method, the object is treated as a plain list and a diagnostic message is emitted. To force structural decomposition of an object that has its own method (e.g. a tree), use `nodelist(unclass(x))`.

Value

A data.frame with columns name (path-style ID), depth (integer), type (character class of the element), n_children (integer, 0 for leaves), and label (element name or positional index). An empty list returns a one-row data.frame for the root node only.

Examples

```
nodelist(list(a = 1, b = list(c = 2, d = 3)))

# Unnamed elements
nodelist(list(1, 2, list(3, 4)))
```

`nodelist.randomForest` *Extract Node List from RandomForest Model*

Description

Extracts node-level attributes from every tree in a `randomForest` model. Node IDs match the from/to indices produced by [edgelist.randomForest](#), so the two outputs can be passed directly to `igraph::graph_from_data_frame()` (after filtering to a single treenum).

Usage

```
## S3 method for class 'randomForest'
nodelist(input_object, treenum = NULL, ...)
```

Arguments

input_object	A randomForest model object from the randomForest package
treenum	Integer vector of tree numbers to extract (default: NULL extracts all trees). Values must be between 1 and input_object\$ntree.
...	Additional arguments (currently unused)

Value

A data.frame with one row per node (across all trees) and the following columns:

name Integer node ID within the tree (matches edgelist from/to)
is_leaf Logical: TRUE for terminal nodes
split_var Numeric index of the split variable (NA for leaves)
split_var_name Name of the split variable (NA for leaves)
split_point Split threshold (NA for leaves)
prediction Predicted value (numeric for regression, integer class index for classification)
treenum Integer identifying which tree the node belongs to
label Display label: "<var>\n< <threshold>" for internal nodes, predicted class name (classification) or numeric value (regression) for leaves

Examples

```
if (requireNamespace("randomForest", quietly = TRUE)) {
  set.seed(12)
  rf <- randomForest::randomForest(Species ~ ., data = iris, ntree = 3)
  nodes <- nodelist(rf)
  head(nodes)

  # Extract a single tree
  nodes1 <- nodelist(rf, treenum = 1)
}
```

nodelist.rpart

Extract Node List from rpart Model

Description

Extracts node-level attributes from an rpart model object. Node IDs are the binary heap indices from rownames(input_object\$frame) and match the from/to values produced by [edgelist.rpart](#), so the two outputs can be passed directly to `igraph::graph_from_data_frame()`.

Usage

```
## S3 method for class 'rpart'
nodelist(input_object, ...)
```

Arguments

input_object An rpart model object from the **rpart** package
... Additional arguments (currently unused)

Value

A data.frame with one row per node and the following columns:

- name** Integer node ID (binary heap index, matches edgelist from/to)
- var** Split variable name, or "<leaf>" for terminal nodes
- n** Number of observations routed to this node
- dev** Deviance (impurity) at this node
- yval** Predicted value (numeric for regression, character class label for classification)
- is_leaf** Logical: TRUE for terminal nodes
- depth** Integer tree depth (root = 0)
- wt** Weighted observation count
- complexity** CP pruning parameter at this node
- ncompete** Number of competing splits considered
- nsurrogate** Number of surrogate splits used
- dev_improvement** Numeric deviance reduction from this node's split (NA for leaves)
- n_*** (Classification only) One column per class with the count of observations of that class at the node, named n_<classname>. Class names are sanitized via `make.names()` and lowercased.
- prob_*** (Classification only) One column per class with the class probability at that node, named prob_<classname>. Class names are sanitized via `make.names()` and lowercased.
- nodeprob** (Classification only) Proportion of training data reaching this node
- label** Display label: "<var>\nn=<n>" for internal nodes, "<yval>\nn=<n>" for leaves

Examples

```
if (requireNamespace("rpart", quietly = TRUE)) {
  fit <- rpart::rpart(Species ~ Sepal.Length + Sepal.Width, data = iris)
  nodelist(fit)

  # Labels ready for plotting
  nodelist(fit)$label
}
```

nodelist.tree

Extract Node List from Tree Model

Description

Extracts node-level attributes from a tree model object. Node IDs are the binary heap indices from `rownames(input_object$frame)` and match the from/to values produced by [edgelist.tree](#), so the two outputs can be passed directly to `igraph::graph_from_data_frame()`.

Usage

```
## S3 method for class 'tree'
nodelist(input_object, ...)
```

Arguments

```
input_object    A tree model object from the tree package
...             Additional arguments (currently unused)
```

Value

A data.frame with one row per node and the following columns:

name Integer node ID (binary heap index, matches edgelist from/to)
var Split variable name, or "<leaf>" for terminal nodes
n Number of observations routed to this node
dev Deviance (impurity) at this node
yval Predicted value (numeric for regression, character for classification)
is_leaf Logical: TRUE for terminal nodes
depth Integer tree depth (root = 0)
dev_improvement Numeric deviance reduction from this node's split (NA for leaves)
prob_* (Classification only) One column per class with the class probability at that node, named prob_<classname>. Class names are sanitized via `make.names()` and lowercased.
label Display label: "<var>\nn=<n>" for internal nodes, "<yval>\nn=<n>" for leaves

Examples

```
if (requireNamespace("tree", quietly = TRUE)) {
  tr <- tree::tree(Species ~ Sepal.Length + Sepal.Width, data = iris)
  nodelist(tr)

  # Labels ready for plotting
  nodelist(tr)$label
}
```

nodelist.xgb.Booster *Extract Node List from XGBoost Model*

Description

Extracts node-level attributes from an xgboost model via `xgb.model.dt.tree()`. Node IDs are globally unique strings in "Tree-Node" format and match the from/to columns produced by [edgelist.xgb.Booster](#).

Usage

```
## S3 method for class 'xgb.Booster'
nodeList(input_object, treenum = NULL, ...)
```

Arguments

<code>input_object</code>	An xgboost model object (xgb.Booster)
<code>treenum</code>	Integer vector of 1-based tree numbers to extract (default: NULL extracts all trees).
<code>...</code>	Additional arguments (currently unused)

Value

A data.frame with one row per node and the following columns:

name Node ID string ("Tree-Node" format, matches edgelist from/to)

is_leaf Logical: TRUE for leaf nodes

feature Split variable name (NA for leaves)

split Split threshold (NA for leaves)

quality Information gain for splits, leaf score for leaves

cover Cover (sum of second-order gradient)

missing Node ID ("Tree-Node" format) where observations with missing values are routed; NA for leaves

treenum 1-based tree number

label Display label: "<feature>\n<threshold>" for splits, rounded leaf score for leaves

Examples

```
if (requireNamespace("xgboost", quietly = TRUE)) {
  data(agaricus.train, package = "xgboost")
  bst <- xgboost::xgboost(
    x = agaricus.train$data,
    y = factor(agaricus.train$label),
    max_depth = 2, nrounds = 2, nthreads = 1
  )
  nl <- nodeList(bst)
  head(nl)
}
```

Index

* **datasets**

courses, [4](#)

as.igraph, [2](#), [2](#), [3](#), [4](#)

as_tbl_graph, [3](#), [3](#)

courses, [4](#)

edgelist, [2](#), [5](#)

edgelist.data.frame, [6](#)

edgelist.default, [8](#)

edgelist.gbm, [9](#)

edgelist.list, [10](#)

edgelist.randomForest, [11](#), [19](#)

edgelist.rpart, [12](#), [20](#)

edgelist.tree, [13](#), [21](#)

edgelist.xgb.Booster, [14](#), [22](#)

igraph, [2](#), [3](#)

nodelist, [2](#), [15](#)

nodelist.data.frame, [16](#)

nodelist.default, [17](#)

nodelist.gbm, [17](#)

nodelist.list, [18](#)

nodelist.randomForest, [19](#)

nodelist.rpart, [20](#)

nodelist.tree, [21](#)

nodelist.xgb.Booster, [22](#)

tbl_graph, [3](#), [4](#)